<u>District I</u> 1625 N. French Dr., Hobbs, NM 88240 District II
1301 W. Grand Avenue, Artesia, NM 88210 District III
1000 Rio Brazos Road, Aztec, NM 87410 District IV 1220 S. St. Francis Dr., Santa Fe, NM 87505

State of New Mexico Energy Minerals and Natural Resources

Oil Conservation Division 1220 South St. Francis Dr. Santa Fe, NM 87505

For drilling and production facilities, submit to appropriate NMOCD District Office.
For downstream facilities, submit to Santa Fe office

Form C-144

June 1, 2004

Pit or Below-Grade Tank Registration or Closure Is pit or below-grade tank covered by a "general plan"? Yes No No

Type of action: Registration of a pit of	or below-grade tank Closure of a pit or below-grade	de tank 🔀						
Operator: BP America Production Company Telephone: (505)326-9200 e-mail address:								
Address: 200 Energy Ct, Farmington, NM 87401								
Facility or well name: Vandewart 8#1 API#: 3004523340 U/L or Qtr/Qtr I Sec 14 T29N R 8W								
	County: San Juan Latitude Longitude NAD: 1997 V 1983							
Surface Owner: Federal State Private Indian								
Pit	Below-grade tank							
Type: Drilling Production Disposal	Volume:bbl Type of fluid:	DEC 2005						
Workover ☐ Emergency ☐	Construction material: Double-walled, with leak detection? Yes T If not, explain why not. CONS. DAY							
Lined Unlined	Construction material: Double-walled, with leak detection? Yes If not, explain why not.							
Liner type: Synthetic Thicknessmil Clay	Double-waited, with leak detection? Tes 11 not, explain with not.							
Pit Volumebbl								
Depth to ground water (vertical distance from bottom of pit to seasonal	Less than 50 feet	(20 points) DE 7						
high water elevation of ground water.)	50 feet or more, but less than 100 feet	(10 points)						
nigh water elevation of ground water.)	100 feet or more	(0 points)						
W. III. 1	Yes	(20 points)						
Wellhead protection area: (Less than 200 feet from a private domestic	No	(0 points)						
water source, or less than 1000 feet from all other water sources.)								
Distance to surface water: (horizontal distance to all wetlands, playas, irrigation canals, ditches, and perennial and ephemeral watercourses.)	Less than 200 feet	(20 points)						
	200 feet or more, but less than 1000 feet	(10 points)						
	1000 feet or more	(0 points)						
	Ranking Score (Total Points)							
If this is a pit closure: (1) Attach a diagram of the facility showing the pit's	s relationship to other equipment and tanks. (2) Indica	ate disposal location: (check the onsite box if						
If this is a pit closure: (1) Attach a diagram of the facility showing the pit's relationship to other equipment and tanks. (2) Indicate disposal location: (check the onsite box if your are burying in place) onsite If offsite, name of facility (3) Attach a general description of remedial action taken including								
remediation start date and end date. (4) Groundwater encountered: No Yes I f yes, show depth below ground surface ft. and attach sample results.								
(5) Attach soil sample results and a diagram of sample locations and excaval	•	The district Sumple results.						
	ions.							
Additional Comments:								
See Attached Documentation								
		<u> </u>						
		·						
I hereby certify that the information above is true and complete to the heat	of my knowledge and helief. I further contifu that the	se above described nit or below grade tonk						
I hereby certify that the information above is true and complete to the best of my knowledge and belief. I further certify that the above-described pit or below-grade tank has been/will be constructed or closed according to NMOCD guidelines , a general permit , or an (attached) alternative OCD-approved plan .								
Date:								
Date: 11/01/2005 Printed Name/Title Jeffrey C. Blagg, Agent Signature C. Sligg								
Your certification and NMOCD approval of this application/closure does not relieve the operator of liability should the contents of the pit or tank contaminate ground water or otherwise endanger public health or the environment. Nor does it relieve the operator of its responsibility for compliance with any other federal, state, or local laws and/or regulations.								
Approval:	3 / ~ M	DEC 1 0 200c						
Approval: Printed Name/Title Printed Name/Title Signature Signature Signature Signature								

CLIENT: BP	BLAGG ENGINEERING, INC. P.O. BOX 87, BLOOMFIELD, NM 87413			13	LOCATION NO: <u>81066</u>				
	(505) 632	-1199			R NO:			
FIELD REPORT: PIT CLOSURE VERIFICATION PAGE No: _/_ of/									
LOCATION: NAME: VANDEWART B WELL#: (TYPE: BLOW				——— I	DATE STARTED: 9/19/52				
QUAD/UNIT: I SEC: 14 TWP: 290 RNG: 80 PM: NM CNTY: 57 ST: NM						FINISHED:			
QTR/FOOTAGE: 1740'5 /	100 E N	E/SE CONTE	RACTOR: L+	- <i>(v</i> en)	SPECI	ONMENTAL . ALIST:	NV		
EXCAVATION APPROX. NA FT. x NA FT. x NA FT. DEEP. CUBIC YARDAGE: NA									
DISPOSAL FACILITY: ON -SITE REMEDIATION METHOD: CLOSE AS IS									
LAND USE: RANGE -	Bun	LEASE:	5F 0785	٥٧	FORMAT	ON:	OK		
FIELD NOTES & REMAR			(IMATELY _/5		558 E	_	,		
DEPTH TO GROUNDWATER: 3100 NEAREST WATER SOURCE: 31000 NEAREST SURFACE WATER: 31000									
NMOCD RANKING SCORE:O NMOCD TPH CLOSURE STD: PPM									
SOIL AND EXCAVATION DESCRIPTION: OVM CALIB. RI				READ. = 5		RF = 0.52			
TIME: /Z:ZS						9/18/02			
SOIL TYPE: SAND / SILTY SAI	ND / SILT / SILTY (CLL. ORANGE T	CLAY / CLAY /	GRAVEL / OTHI				2.3		
COHESION (ALL OTHERS): NON C					ock - Jan	16 45 36	,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,		
CONSISTENCY (NON COHESIVE S				LUCULV DI ACT	10				
PLASTICITY (CLAYS): NON PLAST DENSITY (COHESIVE CLAYS & SILT				HIGHLY PLAST					
MOISTURE: DRY (SLIGHTLY MOISD MOISD) WET / SATURATED / SUPER SATURATED									
DISCOLORATION/STAINING OBSEFT HC ODOR DETECTED: YES (NO) E		LANATION							
SAMPLE TYPE: GRAB COMPOSIT	E - # OF PTS			_	- 2				
ADDITIONAL COMMENTS: STE						•			
BEDROCK BOTTOM TO CREW'S ARRIVAL. COLLECTED SAMPLE FROM BEDROCK TURFACE BEDROCK - HARD FRIABLE. NO TPH ANALYSIS WAS CONDUCTED.									
SCALE SAMP TO	(n) (1) (n)	1	ELD 418.1 CALC		l =	nn. nn.o			
SAMP. TI	ME SAMP. ID	LAB NO.	WEIGHT (g)	mL FREON	DILUTION	READING	CALC. (ppm)		
0 FT									
PIT PERIME	TER N				PITF	ROFIL	E		
P. D .	-4.1	, c	VM ADING						
~5.5′	1.5 B.P.D.	SAMPLE	FIELD HEADSPACE	E					
8.G. 20'	/	1@ 7'	(ppm)						
85 Rm 2 @ 3 @									
	1	4@							
1	19'	5 @		-	OT APP	LICABLE			
To WELL	()								
HEAD				-					
	<u> </u>			\equiv					
		CAMBLE	AMPLES						
	4,	A ID A	NALYSIS TIME						
PROD.	<i>y</i>]					
AREA) V CRADE: B = BELOW]					
P.D. = PIT DEPRESSION; B.G. = BELOV T.H. = TEST HOLE; ~ = APPROX.; T.B.					·				
TRAVEL NOTES: CALLOUT: 9/19/02 -MORN. ONSITE: 9/19/02 - NOON									