District I
1625 N. French Dr., Hobbs, NM 88240
District II
1301 W. Grand Avenue, Artesia, NM 88210
District III
1000 Rio Brazos Road, Aztec, NM 87410
District IV
1220 S. St. Francis Dr., Santa Fe, NM 87505

State of New Mexico Energy Minerals and Natural Resources

Oil Conservation Division 1220 South St. Francis Dr. For drilling and production facilities, submit to appropriate NMOCD District Office.
For downstream facilities, submit to Santa Fe office

Form C-144

June 1, 2004

Santa Fe, NM 87505

Pit or Below-Grade Tank Registration or Closure
Is pit or below-grade tank covered by a "general plan"? Yes X No

Type of action: Registration of a pit or below-grade tank 🔲 Closure of a pit or below-grade tank 🔀		
Operator: BP America Production Company Telephon	e: (505)326-9200 e-mail address:	
Address: 200 Energy Ct, Farmington, NM 87401	e. <u>1303/320-9200</u> e-man address.	
Facility or well name: Barrett A #12 API #: 3	30045 210824 U/L or Otr/Otr 6	Sec 19 T 31N R 9W
	Longitude	
Surface Owner: Federal State Private Indian		14.0. 1527 (1505)
Pit	Below-grade tank	
Type: Drilling Production Disposal	Volume:bbl Type of fluid:	
Workover Emergency	Construction material:	
Lined [] Unlined []	Double-walled, with leak detection? Yes If not, explain why not.	
Liner type: Synthetic Thickness Mil Clay		,,,
Pit Volumebbl		
	Less than 50 feet	(20 points)
Depth to ground water (vertical distance from bottom of pit to seasonal	50 feet or more, but less than 100 feet	(10 points)
high water elevation of ground water.)	100 feet or more	(0 points)
	Voc	(20 mainte)
Wellhead protection area: (Less than 200 feet from a private domestic	Yes No	(20 points)
water source, or less than 1000 feet from all other water sources.)	NO	(0 points)
Distance to surface water: (horizontal distance to all wetlands, playas,	Less than 200 feet	(20 points)
irrigation canals, ditches, and perennial and ephemeral watercourses.)	200 feet or more, but less than 1000 feet	(10 points)
	1000 feet or more	(0 points)
	Ranking Score (Total Points)	
If this is a pit closure: (1) Attach a diagram of the facility showing the pit's	s relationship to other equipment and tanks (2) Indica	ate disposal location: (check the onsite boy if
your are burying in place) onsite offsite foffsite, name of facility		
remediation start date and end date. (4) Groundwater encountered: No 🗆 Y		
5) Attach soil sample results and a diagram of sample locations and excavat		tt. and attach şample results.
Additional Comments:	ions.	
See Attached Documentation	DEC 2008	
	archive 3	
- OF COMS. We as		
I hereby certify that the information above is true and complete to the best of my knowledge and select Later the certify that the above-described pit or below-grade tank		
has been/will be constructed or closed according to NMOCD guidelines 🔀, a general permit 🗌, or an (attached) alternative OCD-approved plan 🗌.		
Date: 11/01/0005	1	
Printed Name/Title Jeffrey C. Blagg. Agent Signature C. Slegy		
Printed Name/Title		
otherwise endanger public health or the environment. Nor does it relieve the operator of its responsibility for compliance with any other federal, state, or local laws and/or regulations.		
Approval: PENTY OIL & GAS INSPECTOR, DIST. &	/	// DEC 1.0.2005
Printed Name/Title	Signature Bok Dock	Date:DEC 1 9 2003
į		

BLAGG ENGINEERING, INC. P.O. BOX 87, BLOOMFIELD, NM 87413 (505) 632-1199 C.D.C. ND: 8712
FIELD REPORT: CLOSURE VERIFICATION PAGE No: 1 of 1
OCATION: NAME: BARRETT A WELL #: 12 PIT: SEP/DEHF DATE STARTED: 9-18-01 QUAD/UNIT: 6 SEC: 19 TWP: 31N RNG: 9W PM: NM CNTY: SS ST: NM DATE STARTED: 9-18-01 DATE FINISHED: 9-18-01
QTR/FOOTAGE:1790 N/1690 E SWINE CONTRACTOR: FLINT SPECIALIST: 3
EXCAVATION APPROX. 10 FT. x 10 FT. x 8 FT. DEEP. CUBIC YARDAGE:
DISPOSAL FACILITY: ON SITE REMEDIATION METHOD: COSE AS 15
LAND USE: LANGE-BLM LEASE: SF-078336 FORMATION: PC
TELD NOTES & REMARKS: PIT LOCATED APPROXIMATELY 80' FT. N16° WFROM WELLHEAD.
DEPTH TO GROUNDWATER: >100 NEAREST WATER SOURCE: >1000 NEAREST SURFACE WATER: >1000
NMOCD RANKING SCORE: O NMOCD TPH CLOSURE STD: 5000 PPM CHECK ONE
SOIL AND EXCAVATION OVM CALIB. READ. 129.20 ppm PIT ABANDONED VM CALIB. GAS = 250 ppm RF = 0.52 X STEEL TANK INSTALLED
DESCRIPTION: TIME: 1150 am/pm DATE: 9-18-01 FIBERGLASS TANK INSTALLED
SOIL TYPE: SAND / SILTY SAND / SILT / SILTY CLAY / CLAY / GRAVEL / OTHER
COHESION (ALL OTHERS): NON COHESIVE / SLIGHTLY COHESIVE / COHESIVE / HIGHLY COHESIVE
CONSISTENCY (NON COHESIVE SOILS): LOOSE / FIRM / DENSE / VERY DENSE
PLASTICITY (CLAYS): NON PLASTIC / SLIGHTLY PLASTIC / COHESIVE / MEDIUM PLASTIC / HIGHLY PLASTIC DENSITY (COHESIVE CLAYS & SILTS): SOFT / FIRM / STIFF / VERY STIFF / HARD
MDISTURE: DRY / SLIGHTLY MOIST / (MOIST) / WET / SATURATED / SUPER SATURATED (CLOSED)
DISCOLORATION/STAINING OBSERVED: (ES) NO EXPLANATION - LITE (CRAV) HC ODOR DETECTED: (YES) / NO EXPLANATION - MODELATE. HC ODOX
SAMPLE TYPE: (GDAR) COMPOSITE - # OF PTS
ADDITIONAL COMMENTS EXCAVATED EXISTING PIT TO INSTALL 21 BBL STEEL LANK.
SCALE SAMPLE LD LAB NO. WEIGHT (2) DI EPEON DILLITION PEAGING CALC.
SCALE SAMP. TIME SAMPLE I.D. LAB No: WEIGHT (g) ML. FREON DILUTION READING CALC. ppm
O _N FT
1 PIT PERIMETER PIT PROFILE
OVM
RESULTS
SAMPLE FIELD HEADSPACE PID (ppm) 1 @ 9' 188
↑ 2 e
3 @ 4 @
5 e A
A 8 10'a
8 1
LAB SAMPLES TO THE TOTAL PROPERTY OF THE PROPE
SAMPLE ANALYSIS TIME
Ceg TPH/BTEN 11-11
BOTH PASSED
SAMPLE PIT
→ 1"
TRAVEL NOTES: CALLOUT: 9-17-01 NOON ONSITE: 9-18-01 1120

revised: 07/16/01



EPA METHOD 8015 Modified Nonhalogenated Volatile Organics Total Petroleum Hydrocarbons

Client:	Blagg / BP	Project #:	94034-010
Sample ID:	Sep/Dehy C @ 9'	Date Reported:	09-21-01
Laboratory Number:	20993	Date Sampled:	09-18-01
Chain of Custody No:	8712	Date Received:	09-18-01
Sample Matrix:	Soil	Date Extracted:	09-19-01
Preservative:	Cool	Date Analyzed:	09-20-01
Condition:	Cool and Intact	Analysis Requested:	8015 TPH

Parameter	Concentration (mg/Kg)	Det. Limit (mg/Kg)
Gasoline Range (C5 - C10)	62.0	0.2
Diesel Range (C10 - C28)	ND	0.1
Total Petroleum Hydrocarbons	62.0	0.2

ND - Parameter not detected at the stated detection limit.

References:

Method 8015B, Nonhalogenated Volatile Organics, Test Methods for Evaluating Solid Waste,

SW-846, USEPA, December 1996.

Comments:

Barrett A #12.

Analyst Caperin

Mistri m Warters
Review



EPA METHOD 8021 AROMATIC VOLATILE ORGANICS

Client:	Blagg / BP	Project #:	94034-010
Sample ID:	Sep/Dehy C @ 9'	Date Reported:	09-20-01
Laboratory Number:	20993	Date Sampled:	09-18-01
Chain of Custody:	8712	Date Received:	09-18-01
Sample Matrix:	Soil	Date Analyzed:	09-20-01
Preservative:	Cool	Date Extracted:	09-19-01
Condition:	Cool & Intact	Analysis Requested:	BTEX

Parameter	Concentration (ug/Kg)	Det. Limit (ug/Kg)
Benzene	82.4	1.8
Toluene	503	1.7
Ethylbenzene	186	1.5
p,m-Xylene	1,240	2.2
o-Xylene	512	1.0
Total BTEX	2,520	

ND - Parameter not detected at the stated detection limit.

Surrogate Recoveries:	Parameter	Percent Recovery
	Fluorobenzene	98 %
•	1,4-difluorobenzene	98 %
	Bromochlorobenzene	98 %

References:

Method 5030B, Purge-and-Trap, Test Methods for Evaluating Solid Waste, SW-846, USEPA,

December 1996.

Method 8021B, Aromatic Volatile Organics, Test Methods for Evaluating Solid Waste, SW-846,

USEPA, December 1996.

Comments:

Barrett A #12.

Analyst P. Geren

Christin m Wallen
Review