District I
1625 N. French Dr., Hobbs, NM 88240
District II
1301 W. Grand Avenue, Artesia, NM 88210
District III
1000 Rio Brazos Road, Aztec, NM 87410
District IV
1220 S. St. Francis Dr., Santa Fe, NM 87505

State of New Mexico Energy Minerals and Natural Resources

Oil Conservation Division 1220 South St. Francis Dr. Santa Fe, NM 87505 For drilling and production facilities, submit to appropriate NMOCD District Office.
For downstream facilities, submit to Santa Fe office

Form C-144 June 1, 2004

Pit or Below-Grade Tank Registration or Closure

Is pit or below-grade tar Type of action: Registration of a pit	nk covered by a "general plan"? Yes 🔀 N or below-grade tank 🗌 Closure of a pit or below-	NO ∐ grade tank ⊠		
County: San Juan Latitude	ne:(505)326-9200	5 Sec 31 T 29N R BW		
Surface Owner: Federal	Below-grade tank Volume:bbl Type of fluid: Construction material: Double-walled, with leak detection? Yes If	_		
Depth to ground water (vertical distance from bottom of pit to seasonal high water elevation of ground water.)	Less than 50 feet 50 feet or more, but less than 100 feet 100 feet or more	(20 points) (10 points) (0 points)		
Wellhead protection area: (Less than 200 feet from a private domestic water source, or less than 1000 feet from all other water sources.)	Yes No	(20 points) (0 points)		
Distance to surface water: (horizontal distance to all wetlands, playas, irrigation canals, ditches, and perennial and ephemeral watercourses.)	Less than 200 feet 200 feet or more, but less than 1000 feet 1000 feet or more	(20 points) (10 points) (0 points)		
	Ranking Score (Total Points)			
If this is a pit closure: (1) Attach a diagram of the facility showing the pit your are burying in place) onsite offsite If offsite, name of facility_remediation start date and end date. (4) Groundwater encountered: No (5) Attach soil sample results and a diagram of sample locations and excava	Yes If yes, show depth below ground surface_	al description of remedial action taken including		
Additional Comments: See Attached Documentation		DEC 2005 OIL CONS. DIV.		
I hereby certify that the information above is true and complete to the best of my knowledge and belief. I further certify that the above described bit on blow-grade tank has been/will be constructed or closed according to NMOCD guidelines , a general permit , or an (attached) alternative OCD-approved bian . Date: 11/01/2005 Printed Name/Title Jeffrey C. Blagg, Agent Signature C - C - C - C - C - C - C - C - C - C				
Approval: CA & GAS INSPECTOR, DIST. CO	Signature BA SAK	DEC 1 9 2005		

BLAGG ENGINEERING, INC.	LOCATION NO: BIO76
CLIENT: P.O. BOX 87, BLOOMFIELD, NM 87413 (505) 632-1199	COCR NO: 10315
FIELD REPORT: PIT CLOSURE VERIFICATION	PAGE No: of
LOCATION: NAME: LARGO 31 B WELL#: 18 TYPE: RESERVE QUAD/UNIT: B SEC: 31 TWP: 29 N RNG: 8W PM: NM CNTY: 55 ST: NM	DATE STARTED: $10 - 1 - 02$ DATE FINISHED: $10 - 1 - 02$
QTR/FOOTAGE: 1149/2/1519 E NW/NE CONTRACTOR: FLINT (JUST)	ENVIRONMENTAL JCB
EXCAVATION APPROX. 105 FT. x 30 FT. x 4 FT. DEEP. CUBIC	YARDAGE: O
DISPOSAL FACILITY: NA REMEDIATION METHOD:	<u>Cuse</u> As is MATION: <u>FC</u>
	5°W FROM WELLHEAD.
DEPTH TO GROUNDWATER: >100 NEAREST WATER SOURCE: >1000 NEAREST SURFACE NMOCD RANKING SCORE: O NMOCD TPH CLOSURE STD: 5000 PPM	E WATER:
SOIL AND EXCAVATION DESCRIPTION: OVM CALIB. READ OVM CALIB. GAS =	
SOIL TYPE: SAND (SILTY SAND) SILT / SILTY CLAY / CLAY / GRAVEL / OTHER SANDS TO	am/pm DATE: 10-1-07 NE @ 71-BG
SOIL COLOR: (RAP - TAN) COHESION (ALL OTHERS): NON COHESIVE SLIGHTLY COHESIVE COHESIVE / HIGHLY COHESIVE	
CONSISTENCY (NON COHESIVE SOILS): LOOSE/ FIRM / DENSE / VERY DENSE PLASTICITY (CLAYS): NON PLASTIC / SLIGHTLY PLASTIC / COHESIVE / MEDIUM PLASTIC / HIGHLY PLASTIC	
DENSITY (COHESIVE CLAYS & SILTS): SOFT / FIRM / STIFF / VERY STIFF / HARD MOISTURE: DRY / SLIGHTLY MOIST (MOIST / WET) SATURATED / SUPER SATURATED	CLOSED
DISCOLORATION/STAINING OBSERVED: YES (NO EXPLANATION	
SAMPLE TYPE: GRAB COMPOSITE . # OF PTS ADDITIONAL COMMENTS: PLASTIC LINED RESERVE PIT WITH ~ 3 C	1 SEDIMENT FILL
BEDROCK FROM UPGRADIENT EROSION. WATER BOIOW SEDIME	IT Sittly ON Liner.
FIELD 418.1 CALCULATIONS	Soils immediately Above
SCALE SAMP. TIME SAMP. ID LAB NO. WEIGHT (g) mL FREON DILL	TION READING CALC. (ppm)
o FT	
Î PIT PERIMETER P	IT PROFILE
N	
READING Pastic	CENENT WY SEDIMEN
30 N 1@ 7 ND 2@ 7 ND	CEMENTAL PROPERTY FILE
	CEMENT WY SEDIMEN
A M 5@	´ / A1
K Tu Tu Tu	
TH, 300	
LAB SAMPLES	////
SAMPLE ANALYSIS TIME	
PD 7 TPH 1250	NDSTINE EXPACE
P) 200 70 well 187 TPH 1250 B	MD S NNE EDRUCK
P.D. = PIT DEPRESSION; B.G. = BELOW GRADE; B = BELOW T.H. = TEST HOLE; ~ = APPROX.; T.B. = TANK BOTTOM TRAVEL NOTES: 0.273 (1) = 1.07 (1) = 1	MDS TINE EDRUCK



EPA METHOD 8015 Modified Nonhalogenated Volatile Organics Total Petroleum Hydrocarbons

Client:	Blagg / BP	Project #:	94034-010
Sample ID:	Reserve #1 @ 7'	Date Reported:	10-03-02
Laboratory Number:	23925	Date Sampled:	10-01-02
Chain of Custody No:	10315	Date Received:	10-01-02
Sample Matrix:	Soil	Date Extracted:	10-02-02
Preservative:	Cool	Date Analyzed:	10-03-02
Condition:	Cool and Intact	Analysis Requested:	8015 TPH

Parameter	Concentration (mg/Kg)	Det. Limit (mg/Kg)
Gasoline Range (C5 - C10)	ND	0.2
Diesel Range (C10 - C28)	ND	0.1
Total Petroleum Hydrocarbons	ND	0.2

ND - Parameter not detected at the stated detection limit.

References:

Method 8015B, Nonhalogenated Volatile Organics, Test Methods for Evaluating Solid Waste,

SW-846, USEPA, December 1996.

Comments:

Largo 31 B #18.

Analyst C. Oplerson

Review