1625 N. French Dr., Hobbs, NM 88240 District II 1301 W. Grand Avenue, Artesia, NM 88210 District III 1000 Rio Brazos Road, Aztec, NM 87410 District IV 1220 S. St. Francis Dr., Santa Fe, NM 87505

Printed Name/Title

## State of New Mexico **Energy Minerals and Natural Resources**

Oil Conservation Division

For drilling and production facilities, submit to appropriate NMOCD District Office. For downstream facilities, submit to Santa Fe office

Form C-144

June 1, 2004

1220 South St. Francis Dr. Santa Fe, NM 87505

Pit or Below-Grade Tank Registration or Closure Is pit or below-grade tank covered by a "general plan"? Yes X No ... Type of action: Registration of a pit or below-grade tank \( \subseteq \) Closure of a pit or below-grade tank \( \subseteq \) Operator: BP America Production Company Telephone: (505)326-9200 e-mail address: Address: 200 Energy Ct, Farmington, NM 87401 Facility or well name: Shone GC#1 API#: 200450826/ U/L or Qtr/Qtr J Sec 14 T 29N R 9 W County: San Juan Longitude Surface Owner: Federal 

State 

Private 

Indian Below-grade tank Type: Drilling Production Disposal Volume: \_\_\_\_bbl Type of fluid: \_\_\_\_\_ Construction material: Double-walled, with leak detection? Yes If not, explain why not Lined Unlined Liner type: Synthetic Thickness \_\_\_ mil Clay \_\_ Pit Volume Less than 50 feet (20 points) Depth to ground water (vertical distance from bottom of pit to seasonal 50 feet or more, but less than 100 feet (10 points) high water elevation of ground water.) 100 feet or more ( 0 points) Yes (20 points) Wellhead protection area: (Less than 200 feet from a private domestic Nο ( 0 points) water source, or less than 1000 feet from all other water sources.) Less than 200 feet (20 points) Distance to surface water: (horizontal distance to all wetlands, playas, 200 feet or more, but less than 1000 feet (10 points) irrigation canals, ditches, and perennial and ephemeral watercourses.) 1000 feet or more ( 0 points) Ranking Score (Total Points) If this is a pit closure: (1) Attach a diagram of the facility showing the pit's relationship to other equipment and tanks. (2) Indicate disposal location: (check the onsite box if your are burying in place) onsite 🔲 offsite 🔲 If offsite, name of facility\_\_\_\_\_ . (3) Attach a general description of remedial action taken including remediation start date and end date. (4) Groundwater encountered: No 🗌 Yes 🔲 If yes, show depth below ground surface ft. and attach sample results. (5) Attach soil sample results and a diagram of sample locations and excavations. Additional Comments: See Attached Documentation I hereby certify that the information above is true and complete to the best of my knowledge and belief. I further certify that the above-described pit or below-grade tank has been/will be constructed or closed according to NMOCD guidelines X, a general permit , or an (attached) alternative OCD-approved plan ... Date: 11/01/2005 Jeffrey C. Blagg, Agent Signature Your certification and NMOCD approval of this application/closure does not relieve the operator of liability should the contents of the pit or tank contaminate ground water or otherwise endanger public health or the environment. Nor does it relieve the operator of its responsibility for compliance with any other federal, state, or local laws and/or regulations. CERUTY OIL & GAS INSPECTOR, DIST. DEC 19 2005 Approval:

BLAGG ENGINEERING, P.O. BOX 87, BLOOMFIELD, (505) 632-1199	NM 87413 GDS ND 9055
FIELD REPORT: PIT CLOSURE VERIFI	ICATION PAGE NO: 1 of 1
LOCATION: NAME: SHANE GC WELL #: 1 TYPE: QUAD/UNIT: J SEC: 14 TWP: 29N RNG: 9W PM: NM CN	TY: SJ ST: NM DATE FINISHED: 5 -/6-UZ
QTR/FOOTAGE: 18505/1790E NW/SE CONTRACTOR: L+L (L-EXCAVATION APPROX. 45 FT. x 40 FT. x 4 FT.	
DISPOSAL FACILITY: REMEDIA	ATION METHOD: CCOSE AS IS
LAND USE: RANGE -BM LEASE: SF - 0781	
FIELD NOTES & REMARKS: PIT LOCATED APPROXIMATELY  DEPTH TO GROUNDWATER: >100 NEAREST WATER SOURCE: >100	_ NEAREST SURFACE WATER:
NMOCD RANKING SCORE: NMOCD TPH CLOSURE STD: 5000 PPI	M OVM CALIB. READ. 131.2 ppm
SOIL AND EXCAVATION DESCRIPTION:	OVM CALIB. GAS = 250 ppm RF = 0.52
SOIL TYPE: SAND / SILT / SILTY CLAY / CLAY / GF	TIME: 1625 am/pm DATE: 5-16-02  RAVEL / OTHER BEDROCK @ 5'
SOIL COLOR: GRAP  COHESION (ALL OTHERS): NON COHESIVE SLIGHTLY COHESIVE CO	
CONSISTENCY (NON COHESIVE SOILS) LOOSE FIRM / DENSE / VER	
PLASTICITY (CLAYS): NON PLASTIC / SLIGHTLY PLASTIC / COHESIVE DENSITY (COHESIVE CLAYS & SILIS): SOFT / FIRM / STIFF / VERY	
MOISTURE: DRY / SLIGHTLY MOIST / MOIST / WET / SATURATED / DISCOLORATION/STAINING DBSERVED: YES / NO EXPLANATION -	
DISCOLORATION/STAINING OBSERVED: (YES) NO EXPLANATION - HO ODOR DETECTED: YES) NO EXPLANATION - STOWN	GRAF W/ Black Streaks
SAMPLE TYPE: GRAB / COMPOSITE - # OF PTS. ADDITIONAL COMMENTS: EARTHEN PLT W Surface Sta	July Use Lorkling to transle
BEOTOCK Y Souple FIRM Sandstu	me Bedruck (d 5° BGS.
FIELD 418.1 C	AL CULATIONS
SCALE	ML. FREON DILUTION READING CALC. ppm
O FT	
7. PIT PERIMETER	PIT PROFILE
MVO	
RESULTS SAMPLE FIELD MEADSPACE	
45 > 10 (ppm)	
1 <u>e s 192</u> 2 <u>e</u> 3 <u>e</u>	40'
1 @ 5 19Z 2 @ 3 @ 4 @ 5 @	40'
1 <u>e s 192</u> 2 <u>e</u> 3 <u>e</u> 4 <u>e</u>	40
1 @ 5 19Z 2 @ 3 @ 4 @ 5 @ 5 @	47
1 @ 5 19Z 2 @ 3 @ 4 @ 5 @ 5 @	47 5
1 @ \$ 197 2 @ 3 @ 4 @ 5 @ 5 @ LAB SAMPLES	4 5
1 @ \$ 197 2 @ 3 @ 4 @ 5 @ 5 @ 197 40 LAB SAMPLES SMPLE ANALYSIS TIME	4 5
1 @ \$ 197 2 @ 3 @ 4 @ 5 @ 5 @ 5 @ 5 @ 5 @ 5 @ 5 @ 5 @ 5	5 AND STONE BODD OF
I @ S 197 2 @ 3 @ 4 @ 5 @ 5 @ 5 @ 5 @ 5 @ 5 @ 5 @ 5 @ 5	4 5
I @ S 197  2 @ 3 @ 4 @ 5 @ 5 @ 5 @ 5 @ 5 @ 5 @ 5 @ 5 @ 5	4 5

revised: 02/27/02



## EPA METHOD 8015 Modified Nonhalogenated Volatile Organics Total Petroleum Hydrocarbons

Client:	Blagg / BP	Project #:	94034-010
Sample ID:	Blow C @ 5'	Date Reported:	05-20-02
Laboratory Number:	22757	Date Sampled:	05-16-02
Chain of Custody No:	9055	Date Received:	05-17-02
Sample Matrix:	Soil	Date Extracted:	05-19-02
Preservative:	Cool	Date Analyzed:	05-20-02
Condition:	Cool and Intact	Analysis Requested:	8015 TPH

Parameter_	Concentration (mg/Kg)	Det. Limit (mg/Kg)
Gasoline Range (C5 - C10)	12.0	0.2
Diesel Range (C10 - C28)	92.8	0.1
Total Petroleum Hydrocarbons	105	0.2

ND - Parameter not detected at the stated detection limit.

References:

Method 8015B, Nonhalogenated Volatile Organics, Test Methods for Evaluating Solid Waste,

SW-846, USEPA, December 1996.

Comments:

Shane GC #1.

Analyst C. Que

Misting Wasters Review



## EPA METHOD 8021 AROMATIC VOLATILE ORGANICS

Client:	Blagg / BP	Project #:	94034-010
Sample ID:	Blow C @ 5'	Date Reported:	05-20-02
Laboratory Number:	22757	Date Sampled:	05-16-02
Chain of Custody:	9055	Date Received:	05-17-02
Sample Matrix:	Soil	Date Analyzed:	05-20-02
Preservative:	Cool	Date Extracted:	05-19-02
Condition:	Cool & Intact	Analysis Requested:	BTEX

Parameter	Concentration (ug/Kg)	Det. Limit (ug/Kg)
D	40.4	4.0
Benzene	42.4	1.8
Toluene	108	1.7
Ethylbenzene	55.5	1.5
p,m-Xylene	288	2.2
o-Xylene	83.2	1.0
Total BTEX	577	

ND - Parameter not detected at the stated detection limit.

Surrogate Recoveries: Parameter		Percent Recovery
	Fluorobenzene	97 %
	1,4-difluorobenzene	97 %
	Bromochlorobenzene	97 %

References:

Method 5030B, Purge-and-Trap, Test Methods for Evaluating Solid Waste, SW-846, USEPA,

December 1996.

Method 8021B, Aromatic Volatile Organics, Test Methods for Evaluating Solid Waste, SW-846,

USEPA, December 1996.

Comments:

Shane GC #1.

Analyst C. Office

Misting Western Western