submitted in lieu of Form 3160-5

UNITED STATES DEPARTMENT OF THE INTERIOR BUREAU OF LAND MANAGEMENT

Unit A (NENW), 885' FNL & 1050' FEL, Section 22, T31N, R12W, NMPM 11. County and State San Juan Co., NM 12. CHECK APPROPRIATE BOX TO INDICATE NATURE OF NOTICE, REPORT, OTHER DATA Type of Submission Type of Action Abandonment Accompletion New Construction Plugging Non-Routine Fracturing Casing Repair Altering Casing Conversion to Injection 13. Describe Proposed or Completed Operations 7/24/06 MIRU MOTE #1. Spud 8 %" hole @ 9:00 7/24/06. Drill ahead to 163'. Condition hole. RIH with 5 jts of 7" J-55, 20# casing. Set at 161'. Pump preflush 4 bibs FW. Pumped 34 sxs, (54 cf - 9.6 bibs slurry), Type 1-11 Portland cement with 20% Fly As DP and displace with FW. Pressured up to 500 PSI. No cement to surface. WOC. TAG cement @ 35' with 3/4" PVC. Pumped 12s (16.7 cf - 3 bbls). Type 1-11 Neat Cement. Circulated 1/4 bbls to surface. Install WH RD and release MOTE 7/24/06. Pressure test will be conducted by the drilling rig and results shown on next report. APD/ROW 14. I hereby certify that the foregoing is true and correct. Signed Tracey N. Monroe Title Regulatory Assistant Date 07/25/06. (This space for Federal or State Office use) APPROVED BY Title Date	Sundry Notices and Reports on W	ells		
2. Name of Operator BURLINGTON RESCURCES OIL & GAS COMPANYLP 3. Address & Phone No. of Operator PO Box 4289, Farmington, NM 87499 (505) 326-9700 4. Location of Well, Footage, Sec., T, R, M 30-045-33721 10. Field and Pool Basin FC/ Glades FS/ Aztec 11. County and State San Juan Co., NM 12. CHECK APPROPRIATE BOX TO INDICATE NATURE OF NOTICE, REPORT, OTHER DATA Type of Submission Type of Action Notice of Intent Abandonment Subsequent Report Plugging Non-Routine Fracturing Final Abandonment Casing Repair Water Shut off Altering Casing Conversion to Injection 13. Describe Proposed or Completed Operations 77.24/06 MIRU MOTE #1. Spud 8 %" hole @ 9:00 7/24/06. Drill ahead to 163". Condition hole. RIH with 5 jts of 7" 1-55, 20# casing, Set at 161". Pump preflush 4 bils F.W. Pumped 34 sts. (54 cf - 9.6 bibs slury), Type 1-11 Portland accement with 20% Fly As pland displace with F.W. Pressured up to 500 PSI. No cement to surface. WOC. TAG cement @ 35" with 20% Fly As pland displace with F.W. Pressured up to 500 PSI. No cement to surface. WOC. TAG cement @ 35" with 20% Fly As pland continued with F.W. Pressured up to 500 PSI. No cement to surface. WOC. TAG cement @ 35" with 20% Fly As pland continued with F.W. Pressured up to 500 PSI. No cement to surface. WOC. TAG cement @ 35" with 20% Fly As pland continued to the drilling rig and results shown on next report. APD/ROW 14. I hereby certify that the foregoing is true and correct. Signed Tracey N. Monroe Title Regulatory Assistant Date 07/25/06.			2006 JUL 25	AM 5 35 Lease Number
2. Name of Operator BURLINGTON RESCURCES OIL & GAS COMPANYLE 3. Address & Phone No. of Operator PO Box 4289, Farmington, NM 87499 (505) 326-9700 4. Location of Well, Footage, Sec., T, R, M 10. Field and Pool Basin FC/ Glades FS/ Aztec 11. County and State San Juan Co., NM 12. CHECK APPROPRIATE BOX TO INDICATE NATURE OF NOTICE, REPORT, OTHER DATA Type of Submission Type of Action X Subsequent Report Pluging Non-Routine Fracturing Final Abandonment Altering Casing Conversion to Injection 13. Describe Proposed or Completed Operations 77/24/06 MIRU MOTE #1. Spud 8 ½* hole @ 9:00 7/24/06. Drill abead to 163*. Condition hole. RIH with 5 its of 7** J-55, 20# casing. Set at 161*. Pump perflush 4 bbls Fw. Pumped 34 sts. (54 cf - 9.6 bbls slurry), Type 1-11 Portland cement with 20% Fly As DP and displace with Fw. Pressured up to 500 PSI. No cement to surface. WOC. TAG cement @ 35* with 3/4* PVC. Pumped 12s (16.7 cf - 3 bbls). Type 1-11 Neat Cement. Circulated 1/4 bbls to surface. Install WH RD and release MOTE 7/24/06. Pressure test will be conducted by the drilling rig and results shown on next report. APD/ROW This space for Federal or State Office use) APPROVED BY Title Title **Basin FC/ Glades FS/ Aztec 11. County and State San Juan Co., NM **Abandonment Altering Ching County and State San Juan Co., NM **Abandonment Altering Ching County and State San Juan Co., NM **Abandonment Altering Ching County and State San Juan Co., NM 10. Field and Pool Basin FC/ Glades FS/ Aztec 11. County and State San Juan Co., NM **Abandonment Altering Ching County and State San Juan Co., NM **Abandonment Altering Ching County and State San Juan Co., NM **Abandonment Altering Ching County and State San Juan Co., NM **Abandonment Altering Ching County and State San Juan Co., NM **Abandonment Altering Ching County and State San Juan Co., NM **Abandonment Altering Ching County and State San Juan Co., NM **Abandonment Altering Ching County and State San Juan Co., NM **Abandonment Altering Ching County and State San Juan		15 10 311 1 2 3 kg	REGEI 070 FARMIN	NMSF-077651 If Indian, All. or G Tribe Name
Address & Phone No. of Operator PO Box 4289, Farmington, NM 87499 (505) 326-9700 4. Location of Well, Footage, Sec., T, R, M 10. Field and Pool Basin FC/ Glades FS/ Aztec 11. County and State San Juan Co., NM 12. CHECK APPROPRIATE BOX TO INDICATE NATURE OF NOTICE, REPORT, OTHER DATA Type of Submission Type of Aubandonment Abandonment Subsequent Report Ploud Recompletion Prinal Abandonment Altering Casing Conversion to Injection 13. Describe Proposed or Completed Operations 7/24/06 MIRU MOTE #1. Spud 8 %" hole @ 9:00 7/24/06. Drill ahead to 163'. Condition hole. RIH with 5 jts of 7" J-55, 20# casing, Set at 161'. Pump preflush 4 bbis FW. Pumped 34 sxs, (54 cf - 9.6 bbls slurry), Type 1-11 Portland cement with 20% Fly As DP and displace with FW. Pressured up to Soop PSI. No cement to surface. WOC. TAG cement (@ 37th 34" PVC. Pumped 12s (16.7 cf - 3 bbls). Type 1-11 Neat Cement. Circulated 1/4 bbls to surface. WOC. TAG cement (@ 37th 34" PVC. Pumped 12s (16.7 cf - 3 bbls). Type 1-11 Neat Cement. Circulated 1/4 bbls to surface. MOC. TAG cement (@ 37th 34" PVC. Pumped 12s (16.7 cf - 3 bbls). Type 1-11 Neat Cement. Circulated 1/4 bbls to surface. Install WH RD and release MOTE 7/24/06. Pressure test will be conducted by the drilling rig and results shown on next report. APD/ROW 14. I hereby certify that the foregoing is true and correct. Signed Tracey N. Monroe Title Regulatory Assistant Date 07/25/06.	BURLINGTON		7. 10.00	Unit Agreement Name
PO Box 4289, Farmington, NM 87499 (505) 326-9700 4. Location of Well, Footage, Sec., T, R, M 10. Field and Pool Basin FC/ Glades FS/ Aztec 11. County and State San Juan Co., NM 12. CHECK APPROPRIATE BOX TO INDICATE NATURE OF NOTICE, REPORT, OTHER DATA Type of Submission Type of Submission Notice of Intent Recompletion Non-Routine Francuring Casing Repair Water Shut off Final Abandonment Altering Casing Conversion to Injection 13. Describe Proposed or Completed Operations 7/24/06 MIRU MOTE #1. Spud 8 ¾" hole @ 9:00 7/24/06. Drill ahead to 163'. Condition hole. RIH with 5 jts of 7" J-55, 20# casing, Set at 161'. Pump preflush 4 bbls FW. Pumped 34 sxs, (54 cf - 9 6 bbls slurry), Type 1-11 Portland cement with 20% Fly As DP and displace with FW. Pressured up to 500 PSI. No cement to surface. WoC. TaG cement @ 35' with 3/4" PVC. Pumped 12s (16.7 cf - 3 bbls). Type 1-11 Neat Cement. Circulated 1/4 bbls to surface. MOC. TaG cement wis 35' with 3/4" PVC. Pumped 12s (16.7 cf - 3 bbls). Type 1-11 Neat Cement. Circulated 1/4 bbls to surface. MOC. TaG cement @ 35' with 3/4" PVC. Pumped 12s (16.7 cf - 3 bbls). Type 1-11 Neat Cement. Circulated 1/4 bbls to surface. MOC. TaG cement @ 35' with 3/4" PVC. Pumped 12s (16.7 cf - 3 bbls). Type 1-11 Neat Cement. Circulated 1/4 bbls to surface. MOC. TaG cement @ 35' with 3/4" PVC. Pumped 12s (16.7 cf - 3 bbls). Type 1-11 Neat Cement. Circulated 1/4 bbls to surface. MOC. TaG cement @ 35' with 3/4" PVC. Pumped 12s (16.7 cf - 3 bbls). Type 1-11 Neat Cement. Circulated 1/4 bbls to surface. MOC. Tag cement @ 35' with 3/4" PVC. Pumped 12s (16.7 cf - 3 bbls). Type 1-11 Neat Cement. Circulated 1/4 bbls to surface. MOC. Tag cement @ 35' with 3/4" PVC. Pumped 12s (16.7 cf - 3 bbls). Type 1-11 Neat Cement. Circulated 1/4 bbls to surface. MOC. Tag cement @ 35' with 3/4" PVC. Pumped 12s (16.7 cf - 3 bbls). Type 1-11 Neat Cement. Circulated 1/4 bbls to surface. MOC. Tag cement @ 35' with 3/4" PVC. Pumped 12s (16.7 cf - 3 bbls). Type 1-11 Neat Cement. Circulated 1/4 bbls to surface. MOC. Tag	3. Address & Phone No. of Operator	Commission with the	8.	
Unit A (NENW), 885' FNL & 1050' FEL, Section 22, T31N, R12W, NMPM 10. Field and Pool Basin FC/ Glades FS/ Aztec 11. County and State San Juan Co., NM 12. CHECK APPROPRIATE BOX TO INDICATE NATURE OF NOTICE, REPORT, OTHER DATA Type of Submission X Other - Spud notice Recompletion New Construction New Construction New Construction New Construction Yeater Shut off Casing Repair Water Shut off Shut MRU MOTE #1. Spud 8 %" hole @ 9:00 7/24/06. Drill ahead to 163'. Condition hole. RIH with 5 jts of 7" J-55, 20# casing, Set at 161'. Pump preflush 4 bbls FW. Pumped 34 sxs, (54 cf - 9.6 bbls slurry), Type 1-11 Portland cement with 20% Fly As DP and displace with FW. Pressured up to 500 PSI. No cement to surface. Woc TAG cement @ 35' with 34' PVC. Pumped 12s (16.7 cf - 3 bbls). Type 1-11 Neat Cement. Circulated 1/4 bbls to surface. Install WH RD and release MOTE 7/24/06. Pressure test will be conducted by the drilling rig and results shown on next report. APD/ROW 14. I hereby certify that the foregoing is true and correct. Signed Tracey N. Monroe Title Regulatory. Assistant. Date07/25/06.	PO Box 4289, Farmington, NM 87499	(505) 326-9700	9.	
Unit A (NENW), 885' FNL & 1050' FEL, Section 22, T31N, R12W, NMPM 11. County and State San Juan Co., NM 12. CHECK APPROPRIATE BOX TO INDICATE NATURE OF NOTICE, REPORT, OTHER DATA Type of Submission Type of Action Abandonment Abandonment Abandonment Abandonment Abandonment Abandonment Abandonment Altering Casing Conversion to Injection 13. Describe Proposed or Completed Operations 7/24/06 MIRU MOTE #1. Spud 8 ¾" hole @ 9:00 7/24/06. Drill ahead to 163'. Condition hole. RIH with 5 jts of 7" J-55, 20# casing, Set at 161'. Pump perflush 4 bbls FW. Pumped 34 sxs, (54 cf-9,6 bbls slurry), Type 1-11 Portland cement with 20% Fly As DP and displace with FW. Pressured up to 500 PSI. No cement to surface. WoC. TAG cement @ 35' with 3/4" PVC. Pumped 12s (16.7 cf - 3 bbls). Type 1-11 Neat Cement. Circulated 1/4 bbls to surface. Install WH RD and release MOTE 7/24/06. Pressure test will be conducted by the drilling rig and results shown on next report. APD/ROW 14. I hereby certify that the foregoing is true and correct. Signed Tracey N. Monroe Title Regulatory Assistant Date 07/25/06.	4. Location of Well, Footage, Sec., T, R, M			30-045-33721
Unit A (NENW), 885' FNL & 1050' FEL, Section 22, T31N, R12W, NMPM 11. County and State San Juan Co., NM 12. CHECK APPROPRIATE BOX TO INDICATE NATURE OF NOTICE, REPORT, OTHER DATA Type of Submission Type of Action Abandonment Accompletion New Construction New Construction Plugging Non-Routine Fracturing Casing Repair Water Shut off Final Abandonment Altering Casing Conversion to Injection 13. Describe Proposed or Completed Operations 17/24/06 MIRU MOTE #1. Spud 8 %" hole @ 9:00 7/24/06. Drill ahead to 163'. Condition hole. RIH with 5 jts of 7" J-55, 20# 20 and displace with FW. Pressured up to 500 PSI. No cement to surface. WOC. TAG cement @ 35' with 3/4" PVC. Pumped 12s (16.7 cf - 3 bbls). Type 1-11 Neat Cement. Circulated 1/4 bbls to surface. Install WH RD and release MOTE 7/24/06. Pressure test will be conducted by the drilling rig and results shown on next report. APD/ROW 14. I hereby certify that the foregoing is true and correct. Tracey N. Monroe Title Regulatory Assistant Date 07/25/06. This space for Federal or State Office use) APPROVED BY Title Date			10.	Field and Pool
12. CHECK APPROPRIATE BOX TO INDICATE NATURE OF NOTICE, REPORT, OTHER DATA Type of Submission Type of Action Abandonment Recompletion New Construction New Con	IL-24 A (NIENNA) 9951 ENIX O 10501 EI	71 - C41 22 /F21N1 T312N7 NIN/I		Basin FC/ Glades FS/ Aztec PC
Type of Submission X Notice of Intent	Unit A (NEAW), 665 FAL & 1030 FEL, Section 22, 131A, R12W, AMITM			•
14. I hereby certify that the foregoing is true and correct. Signed	13. Describe Proposed or Completed Oper 7/24/06 MIRU MOTE #1. Spud 8 3/4" hole @casing. Set at 161'. Pump preflush 4 bbls FW DP and displace with FW. Pressured up to 50 (16.7 cf – 3 bbls). Type 1-11 Neat Cement. C	rations 9:00 7/24/06. Drill ahead to 163'. (Pumped 34 sxs, (54 cf - 9.6 bbls sl 0 PSI. No cement to surface. WOC circulated 1/4 bbls to surface. Install	urry), Type 1-11 Port TAG cement @ 35' WH RD and release N	land cement with 20% Fly Ash. with 3/4" PVC. Pumped 12sxs
Tracey N. Monroe Title Regulatory Assistant Date 07/25/06. (This space for Federal or State Office use) APPROVED BY	APD/ROW			
APPROVED BY Title Date	A Branch College		ry Assistant Date	07/25/06.
CONDITION OF ADDROVAL if any		Title		Date
Title 18 U.S.C. Section 1001, makes it a crime for any person knowingly and willfully to make any department or agency of	CONDITION OF APPROVAL, if any:			3 1 2006