

UNITED STATES
DEPARTMENT OF THE INTERIOR
BUREAU OF LAND MANAGEMENT

SUBMIT IN DUPLICATE*
(See other instructions on reverse side)

FOR APPROVED
OMB NO. 1004-0137

Expires: December 31, 1991

WELL COMPLETION OR RECOMPLETION REPORT AND LOG*

1a. TYPE OF WELL: OIL WELL ☐ GAS WELL ☒ DRY ☐ Other ☐						5. LEASE DESIGNATION AND SERIAL NO. NMNM-03877	
b. TYPE OF COMPLETION: NEW WELL ☒ WORK OVER ☐ DEEP-EN ☐ PLUG BACK ☐ DIFF. RESVR ☐ Other ☐						6. IF INDIAN, ALLOTTEE OR TRIBE NAME	
2. NAME OF OPERATOR BURLINGTON RESOURCES OIL & GAS COMPANY						7. UNIT AGREEMENT NAME	
3. ADDRESS AND TELEPHONE NO. PO Box 4289, Farmington, NM 87499 (505) 326-9700						8. FARM OR LEASE NAME, WELL NO. Fogelson 8 #100S	
4. LOCATION OF WELL (Report location clearly and in accordance with any State requirements) At surface Unit P (SESE), 980' FSL & 795' FEL At top prod. interval reported below SAME At total depth SAME						9. API WELL NO. 30-045-33541	
10. FIELD AND POOL, OR WILDCAT Basin F.C/Fulcher Kutz P.C/ Aztec F.S						11. SEC., T., R., M., OR BLOCK AND SURVEY OR AREA Sec. 8, T29N, R11W, NMPM	
14. PERMIT NO.				DATE ISSUED		12. COUNTY OR PARISH San Juan	13. STATE New Mexico
15. DATE SPUDDED 3/7/06	16. DATE T.D. REACHED 3/12/06	17. DATE COMPL. (Ready to prod.) 6/6/06		18. ELEVATIONS (DF, RKB, RT, BR, ETC.)* KB-5688'; GL-5687'		19. ELEV. CASINGHEAD	
20. TOTAL DEPTH, MD & TVD 2075' 2076		21. PLUG, BACK T.D., MD & TVD 2025'		22. IF MULTIPLE COMPL., HOW MANY* 3	23. INTERVALS DRILLED BY X	ROTARY TOOLS X	
24. PRODUCTION INTERVAL (S) OF THIS COMPLETION-TOP, BOTTOM, NAME (MD AND TVD)* Fulcher Aztec Pictured Cliffs 1882'-1984'						25. WAS DIRECTIONAL SURVEY MADE NO	
26.						27. WAS WELL CORED No	
28. CASING RECORD (Report all strings set in well)							
CASING SIZE/GRADE		WEIGHT, LB./FT.		DEPTH SET (MD)		HOLE SIZE	
7"		20#, J55		132'		8 3/4"	
4 1/2"		10.5#, J55		2069'		6 1/4"	
29. LINER RECORD							
SIZE		TOP (MD)		BOTTOM (MD)		SACKS CEMENT*	
30. TUBING RECORD							
SIZE		DEPTH SET (MD)		PACKER SET (MD)			
2-3/8", 4.7# J-55		2606'		NONE			
31. PERFORATION RECORD (Interval, size and number)							
1978'-1984' @ 1PSF=7 1882'-1914' @ SPF=32 Total holes= 40 <i>FS 1626-1634 FC 1634-1846 PC 1882-1984 per Amanda 8-9-06</i>							
32. ACID, SHOT, FRACTURE, CEMENT SQUEEZE, ETC.							
DEPTH INTERVAL (MD)				AMOUNT AND KIND OF MATERIAL USED			
1882'-1984'				14322 gal 20# linear 70% N2 foam, 329600 SCF N2, 100000# 20/40 Brady sand			
33. PRODUCTION							
DATE FIRST PRODUCTION SI		PRODUCTION METHOD (Flowing, gas lift, pumping—size and type of pump) Pump				WELL STATUS (Producing or shut-in) SI	
DATE OF TEST		HOURS TESTED		CHOKE SIZE		PROD'N FOR TEST PERIOD	
		1 hr		2"		OIL-BBL 0	
FLOW. TUBING PRESS.		CASING PRESSURE		CALCULATED 24-HOUR RATE		OIL-BBL 0	
SI - 136#		SI - 136#		0		6 mcf	
34. DISPOSITION OF GAS (Sold, used for fuel, vented, etc.) To be sold							
35. LIST OF ATTACHMENTS This is a FC/PC/FS well being DHC order # 3662.							
36. I hereby certify that the foregoing and attached information is complete and correct as determined from all available records							
SIGNED <i>Amanda Sanchez</i>		TITLE Regulatory Analyst		DATE 6/8/06			

*(See Instructions and Spaces for Additional Data on Reverse Side)

Title 18 U.S.C. Section 1001, makes it a crime for any person knowingly and willfully to make to any department of agency of the United States any false, fictitious or fraudulent statements or representations as to any matter within its jurisdiction.

B

37. SUMMARY OF POROUS ZONES: (Show all important zones of porosity and contents thereof; cored intervals; and all drill-stem tests, including depth interval tested, cushion used, time tool open, flowing and shut-in pressures, and recoveries);

38. GEOLOGIC MARKERS

FORMATION	TOP	BOTTOM	DESCRIPTION, CONTENTS, ETC.	NAME	TOP	
					MEAS. DEPTH	TRUE VERT. DEPTH
Ojo Alamo	560'	693'	White, cr-gr ss.	Ojo Alamo	560'	
Kirtland	693'	1554'	Gry sh interbedded w/tight, gry, fine-gr ss.	Kirtland	693'	
Fruitland	1554'	1875'	Dk gry-gry carb sh, coal, grn silts, light-med gry, tight, fine gr ss.	Fruitland	1554'	
Pictured Cliffs	1875'		Bn-Gry, fine grn, tight ss.	Pic.Cliffs	1875'	