Page 1

OIL CONSERVATION DIVISION

2002

NORTHWEST NEW MEXICO PACKER-LEAKAGE TEST

Operator	CORDILLERA EN	Lease CLAYTON			Well No.	1B		
Location of Well	Unit L	_ Sec.	2	<u> </u>	30N	_Rge.	12W API	30-045-31341
	NAME OF RESERVOIR OR POOL			TYPE OF PROD. (Oil or Gas)			METHOD OF PROD. (Flow or Art. Lift)	PROD. MEDIUM (Tbg. or Csg.)
Upper Completion	BLANCO MESAVE	GAS			SHUT-IN CSG			
Lower Completion	BASIN DAKOTA	GAS			FLOW	TBG		
			Р	RE-FLOW SHU	JT-IN PRE	SSUF		
Upper	Hour, date shut-in	Length of time shut-in			SI press. psig	Stabilized? (Yes or No)		
Completion	3:00 p.m. 7-12-03			7 days			820	yes
Lower	Hour, date shut-in				gth of time shut-in		SI press. psig	Stabilized? (Yes or No)
Completion	ľ			7 days			1900	yes
				FLO	OW TEST	NO. 1		
Commenced	l at (hour, date) *	5:30 p.m.	6-19-	03	Zone produ	icing (U	pper or Lower):	Lower
TIME	LAPSED TIME		PRESSU	RE	PROD. ZONE			
(hour, date)	Since *	Upper Complet	ion	Lower Completion	TEMP.	l	REMAR	KS
<u> </u>		csg	tbg	tbg	<u> </u>			
6·00 n m	30 minutes	820	n/a	1700	90 F		15	18 19 20 20
0.00 p.m.	30 minutes	020	11/a	1700	30 F			10 10 (0)
0.00	20	000	_,_	4500	00 5	:	(2)	
6:30 p.m.	30 minutes	820	n/a	1500	90 F		—— [\infty	WN 2003
7:00 p.m.	30 minutes	820	n/a	1300	90 F	E OIL COLIVED SI		
							, co	IST. 3 DIV.
7:30 p.m	30 minutes	820	n/a	1000	90 F		40	
8:00 p.m.	30 minutes	820	n/a	700	90 F	Crossover Packer Holding		
8:30 p.m	30 minutes	820	n/a	500	90 F			
	rate during test	1						
Oil:	-0- BOPD bas	sed on	-0-	Bbls. in	3.5	Hours	Grav.	GOR
Gas:			3698	MCFPD: Tested t				
	Hour date shut in	D-TEST SHUT-IN PRESSURE				Ctobilized 2 (Var. 2. N.)		
Jpper Completion	Hour, date shut-in	Length of time shut-in			SI press. psig	Stabilized? (Yes or No		
.ower	Hour, date shut-in	Length of time shut-in			SI press. psig	Stabilized? (Yes or No)		

FLOW TEST NO. 2

Commenced	l at (hour, date)*	•		Zone producing (Upper or Lowr):				
TIME (hour,date)	LAPSED TIME Since**	PRESS Upper Completion		PROD. ZONE	REMARKS			
			-					
	ate during test	D based onMC	BI FPD:Tested thru	ols. inHolorice or Meter)	oursGrav:	GOR		
Remarks:								
I hereby cert	ify that the infor	mation herein c	ontained is true a	and complete to th	e bes of my knowledge.			
Approved JUN 2 0 2003 20 New Mexico Oil Conservation Division			0 Operat	tor <u>Coedi</u>	llera ENERGY Wright			
New Mexico C	Conservation ()	Ву .	DARY	Wright 1	_		
By Cha	LA X		Title	Produc	tion Foreman	.		
Title03PUN	y on a gas insi	PECTOR DIST A	Date .	6-21	0-03			

NORTHWEST NEW MEXICO PACKER LEAKAGE TEST INSTRUCTIONS

- 1. A packer leakage test shall be commenced on each multiply completed well within seven days after actual completion of the well, and annually thereafter as prescribed by the order authorizing the multiple completion. Such tests shall also be commenced on all multiple completions within seven days following recompletion and/or chemical or fracture treatment, and whenever remedial work has been done on a well during which the packer or the tubing have been disturbed. Tests shall also be taken at any time that communication is suspected or when requested by the Division.
- At least 72 hours prior to the commencement of any packer leakage test, the operator shall notify the Division in writing of the exact time the test is to be commenced. Offset operators shall also be so notified.
- 3. The packer leakage test shall commence when both zones of the dual completion are shut-in for pressure stabilization. Both zones shall remain shut-in until the well-head pressure in each has stabilized, provided however, that they need not remain shut-in more than seven days.
- 4. For Flow Test No. 1, one zone of the dual completion shall be produced at the normal rate of production while the other zone remains shut-in. Such test shall be continued for seven days in the case of a gas well and for 24 hours in the case of an oil well. Note: if, on an initial

packer leakage test, a gas well is being flowed to the atmosphere due to the lack of a pipeline connection the flow period shall be three hours.

- 5. Following completion of Flow Test No. 1, the well shall again be shut-in, in accordance with Paragraph 3 above.
- 6. Flow Test No. 2 shall be conducted even though no leak was indicated during Flow Test No. 1. Procedure for Flow Test no. 2 is to be the same as for Flow Test No. 1 except

that the previously produced zone shall remain shut-in while the zone which was previously shut-in is produced.

7. Pressures for gas-zone tests must be measured on each zone with a deadweight pressure gauge at time intervals as follows: 3 hours tests: immediately prior to the beginning of each flow-period, at lifteen-minute intervals during the first hour thereof, and at hourly intervals thereafter, including one pressure measurement immediately prior to the beginning of each flow period, at least one time during each flow period (at approximately the midway point) and immediately prior to the conclusion of each flow period. Other pressures may be taken as desired, or may be requested on wells which have previously shown questionable test date.

24-hour oil zone tests: all pressures, throughout the entire test, shall be continuously measured and recorded with recording pressure gauges the accuracy of which must be checked at least twice, once at the beginning and once at the end of each test, with a deadweight pressure gauge. If a well is a gas-oil or an oil-gas dual completion, the recording gauge shall be required on the oil zone only, with deadweight pressures as required above being taken on the gas zone.

8. The result s of the above-described tests shall be filed in triplicate within 15 days after completion of the test. Tests shall be filed with the Aztec District Office of the New Mexico oil Conservation Division on northwest new Mexico packer leakage Test Form Revised 11-16-98 with all deadweight pressures indicated thereon as well as the flowing temperatures (gas zones only) and gravity and GOR (oil zones only).