

UNITED STATES
DEPARTMENT OF THE INTERIOR
BUREAU OF LAND MANAGEMENT

Sundry Notices and Reports on Wells

RECEIVED

1. Type of Well
GAS

2003 JUL -7 PM 1:35

070 Farmington, NM

2. Name of Operator

BURLINGTON

RESOURCES OIL & GAS COMPANY LP

3. Address & Phone No. of Operator

PO Box 4289, Farmington, NM 87499 (505) 326-2500

4. Location of Well, Footage, Sec., T, R, M

1840' FSL, 1550' FWL, Sec.15, T-29-N, R-7-W, NMPM

5. Lease Number

NMSF-077842

6. If Indian, All. or
Tribe Name

7. Unit Agreement Name

San Juan 29-7 Unit

Well Name & Number

San Juan 29-7 U #102R

API Well No.


30-039-20514

Field and Pool

Blanco Mesaverde

County and State

Rio Arriba Co, NM



12. CHECK APPROPRIATE BOX TO INDICATE NATURE OF NOTICE, REPORT, OTHER DATA

Type of Submission

- ☐ Notice of Intent
☒ Subsequent Report
☐ Final Abandonment

Type of Action

- ☐ Abandonment
☐ Recompletion
☐ Plugging Back
☐ Casing Repair
☐ Altering Casing
☒ Other - Pay add
☐ Change of Plans
☐ New Construction
☐ Non-Routine Fracturing
☐ Water Shut off
☐ Conversion to Injection

13. Describe Proposed or Completed Operations

- 6-14-03 MIRU. ND WH. NU BOP. TOO H w/2 3/8" tbq. TIH, ran CCL-GR @ 3300-5400'. TOO H. TIH w/4 1/2" CIBP, set @ 5250'. TOO H. SD for Sunday.
- 6-16-03 TIH w/4 1/2" RBP & pkr. Set RBP @ 5230' PT CIBP to 3000 psi/15 min, OK. Reset RBP @ 4784'. Roll hole w/2% KCl wtr. TOO H w/RBP & pkr. Attempt to PT csg. Blew hole in csg @ 2100 psi. TIH w/RBP, set @ 3300'. PT lnr top & 4 1/2" csg to 3000 psi, OK. TOO H. PT 7" csg to 1500 psi. Isolate hole in 7" csg @ 250'. Dump sd on RBP @ 4784'. TOO H. SDON.
- 6-17-03 (Verbal approval to squeeze from Steve Mason, BLM). TIH w/7" pkr, set @ 30'. Establish circ to surface. Close surface valve. Pump 50 sx Type III cmt. Circ cmt to surface after 50 sx cmt. Close surface valve. Pump 200 sx Type III cmt behind 7" csg. Pressure up to 550 psi. Displace w/5 bbl wtr. Pressure up to 1200 psi. WOC. SDON.
- 6-18-03 TIH w/6 1/4" bit to TOC @ 120'. Drill cmt @ 120-260'. PT csg to 500 psi/15 min, OK. TOO H w/bit. TIH w/retrieving tool. Establish circ. Circ sd off RBP. Latch RBP, TOO H. TIH w/perforating gun. Gun stuck @ 4850'. SDON.
- 6-19-03 TIH w/fishing tools. Latch fish. TOO H w/perforating gun & fishing tools. TIH, perf Menefee @ 4957-5238' w/25 0.33" diameter holes. Acidize w/1000 gal 15% HCl. TOO H. SDON.
- 6-20-03 Frac Menefee w/1619 bbl slk wtr, 50,000# 20/40 Brady sd. TOO H. TIH w/CIBP, set @ 4774'. Perf Lewis w/1 SPF @ 3873-4752' w/25 0.33" diameter holes. SDON.

14. I hereby certify that the foregoing is true and correct.

Signed
no

Title Regulatory Supervisor

Date 7/2/03


(This space for Federal or State Office use)

APPROVED BY

Title

Date

CONDITION OF APPROVAL, if any:



Title 18 U.S.C. Section 1001, makes it a crime for any person knowingly and willfully to make any department or agency of the United States any false, fictitious or fraudulent statements or representations as to any matter within its jurisdiction.

NMOCDC

6-21-03 Frac Lewis w/686 bbl 20# linear gel, 1,295,300 SCF N2, 200,000# 20/40
Brady sd. CO after frac.
6-22-03 Blow well & CO.
6-23-03 Blow well & CO. TOOH. TIH w/3 7/8" mill to 4635'. Blow well & CO. Mill
out CIBP @ 4774'. TIH, blow well & CO to 5250'.
6-24-03 Mill out CIBP @ 5250'. TIH, blow well & CO to PBTD @ 5575'.
6-25-03 Blow well & CO. TOOH w/mill.
6-26-03 Blow well & CO. TIH w/172 jts 2 3/8" 4.7# J-55 EUE tbg, landed @ 5457'.
(SN @ 5456'). ND:BOP. NU WH. RD. Rig released.