<u>District I</u> 1625 N. French Dr., Hobbs, NM 88240 District II 1301 W. Grand Avenue, Artesia, NM 88210 District III

1000 Rio Brazos Road, Aztec, NM 87410

District IV

1220 S. St. Francis Dr., Santa Fe, NM 87505

## State of New Mexico **Energy Minerals and Natural Resources**

Oil Conservation Division 1220 South St. Francis Dr. Santa Fe, NM 87505

For drilling and production facilities, submit to appropriate NMOCD District Office.
For downstream facilities, submit to Santa Fe office

Form C-144

June 1, 2004

Pit or Below-Grade Tank Registration or Closure

Pit or Below-Grade Tank Registration or Closure						
Is pit or below-grade tank covered by a "general plan"? Yes No						
Type of action: Registration of a pit or below-grade tank Closure of a pit or below-grade tank						
Operator: Elm Ridge Resources Telephone: (505) 632-3476 e-mail address: amackey1@elmridge.net						
Address: P.O. Box 156, Bloomfield, New Mexico, 87413	Address: P.O. Box 156, Bloomfield, New Mexico, 87413					
Facility or well name: Beth Geiger No. 1 API #: 300392	Facility or well name: Beth Geiger No. 1 API #: 3003924056 U/L or Qtr/Qtr A Sec 17 T 23N R 7W					
Address: P.O. Box 156, Bloomfield, New Mexico, 87413         Facility or well name: Beth Geiger No. 1       API #: 3003924056       U/L or Qtr/Qtr A Sec 17 T 23N R 7W         County: Rio Arriba       Latitude 36.231939       Longitude -107.59157       NAD: 1927 ☑ 1983 ☐						
Surface Owner: Federal ☑ State ☐ Private ☐ Indian ☐		25 25 26 Section 1				
<u>Pit</u>	Below-grade tank	- Administration of the second				
Type: Drilling Production Disposal	lling ☐ Production ☑ Disposal ☐ Volume:bbl Type of fluid:					
Workover ☐ Emergency ☐	Construction material:					
Lined Unlined 🛛	Double-walled, with leak detection? Yes If not	, explain why not.				
Liner type: Synthetic Thicknessmil Clay _						
Pit Volumebbl						
	Less than 50 feet	(20 points)				
Depth to ground water (vertical distance from bottom of pit to seasonal	50 feet or more, but less than 100 feet	(10 points)				
high water elevation of ground water.)	100 feet or more	( 0 points) 0				
	Yes	(20 points)				
Wellhead protection area: (Less than 200 feet from a private domestic	No No	( 0 points) 0				
water source, or less than 1000 feet from all other water sources.)	140	( o points)				
Distance to surface water: (horizontal distance to all wetlands, playas,	Less than 200 feet	(20 points)				
irrigation canals, ditches, and perennial and ephemeral watercourses.)	200 feet or more, but less than 1000 feet	(10 points)				
irrigation canais, diteres, and percumar and epitemeral watercourses.)	1000 feet or more	( 0 points) 10				
	Ranking Score (Total Points)	10				
If this is a pit closure: (1) Attach a diagram of the facility showing the pit's	s relationship to other equipment and tanks (2) Indica	ote disposal location: (check the onsite box if				
your are burying in place) onsite \( \square\) offsite \( \square\) If offsite, name of facility \( \square\).	• • • • • • • • • • • • • • • • • • • •	•				
date. (4) Groundwater encountered: No 🛮 Yes 🗌 If yes, show depth belo						
	<del></del>	e resuits.				
(5) Attach soil sample results and a diagram of sample locations and excavat	lons.					
Additional Comments:						
Soil tested clean. No excavation required from tank battery pit.						
I hereby certify that the information above is true and complete to the best of my knowledge and belief. I further certify that the above-described pit or below-grade tank						
has been/will be constructed or closed according to NMOCD guidelines , a general permit , or an (attached) alternative OCD-approved plan .						
Date: 880						
Printed Name/Title Ms. Amy Mackey, Production Technician Signature Mw GCIL						
Your certification and NMOCD approval of this application/closure does not relieve the operator of liability should the contents of the pit or tank contaminate ground water or						
otherwise endanger public health or the environment. Nor does it relieve the operator of its responsibility for compliance with any other federal, state, or local laws and/or regulations.						
Printed Name/TitleSignature Brand DeffDate: AUG 0 9 2006						

CLIENT:	ENVIROTECH INC.  ENVIRONMENTAL SCIENTISTS & ENGINEERS 5796 U.S. HIGHWAY 64-3014  FARMINGTON, NEW MEXICO 67401 PHONE: (305) 632-0615	LOCATION NO			
FIELD REPOR	T: CLOSURE VERIFICA'	TION PAGE NO: of			
QUAD/UNIT: A SEC:	Geigue WELL #:   PIT: Tank &  17 TWP: 23J RNG: 07W PM: JMPM CNTY: PI  705 W CONTRACTOR: Franks				
EXCAVATION APPROX	P FT x O FT x O FT DEEP  N/A REMEDIATION  LEASE:  KS: PIT LOCATED APPROXIMATELY	CUBIC YARDAGE: Ø  METHOD: N/A  FORMATION:			
DEPTH TO GROUNDWATER: >100  NMOCD RANKING SCORE: 10  SOIL AND EXCAVATION	NEAREST WATER SOURCE: > 1000 NEARE  NMOCD TPH CLOSURE STD: 1000 PPM  N DESCRIPTION:	ST SURFACE WATER: 200 - 1000  CHECK DNE:  X PIT ABANDONED  STEEL TANK INSTALLED			
Soil tested (	clean, no excavation required	.ATIONS			
SCALE 0 FT	1215 Bottom Comp 5,0	FREON DILUTION READING CALC. ppm 20 4 47 198			
PIT PERIME	SAMPLE FIELD HEADSPACE PID (ppm)  1 bothon comp  2  3  4  5  LAB SAMPLES  SAMPLE ANALYSIS TIME	PIT PROFILE			
CALLOUT: ONSITE:					



## EPA METHOD 418.1 TOTAL PETROLEUM HYDROCARBONS

Client:

Elm Ridge Resources

Project #:

03056-040-041

Sample No.:

1

Date Reported:

7/14/2006

Sample ID:

Composite sample of bottom of pit

Date Sampled:

7/7/2006

Sample Matrix:

Soil

Date Analyzed:

7/7/2006

Preservative:

Cool

Analysis Needed:

TPH-418.1

Condition:

Cool and Intact

		Det.
	Concentration	Limit
Parameter	(mg/kg)	(mg/kg)

**Total Petroleum Hydrocarbons** 

188.0

5.0

ND = Parameter not detected at the stated detection limit.

References:

Method 418.1, Petroleum Hydrocarbons, Total Recoverable, Chemical Analysis of Water

and Waste, USEPA Storet No. 4551, 1978.

Comments:

Beth Geiger No. 1 Tank Battery Pit

Instrument callibration checked against 200 ppm standard. Zeroed before each sample

Analyst

Review



## CONTINUOUS CALIBRATION EPA METHOD 418.1 TOTAL PETROLEUM HYDROCARBONS

Cal. Date:

7-Jul-06

Parameter	Standard Concentration mg/L	Concentration Reading mg/L	
ТРН	100		
	200	197	
	500		
	1000		

The accepted percent relative deviation (%RSD) of the calibration factor is less than 20% over the working range.

Analyst Cubt

7/14/

Date

Review

Date