

Submit 3 Copies To Appropriate District  
Office  
District I  
1625 N. French Dr., Hobbs, NM 88240  
District II  
1301 W. Grand Ave., Artesia, NM 88210  
District III  
1000 Rio Brazos Rd., Aztec, NM 87410  
District IV  
1220 S. St. Francis Dr., Santa Fe, NM  
87505

State of New Mexico  
Energy, Minerals and Natural Resources

Form C-103  
March 4, 2004

OIL CONSERVATION DIVISION  
1220 South St. Francis Dr.  
Santa Fe, NM 87505

WELL API NO.	30-039-29600
5. Indicate Type of Lease	STATE <input checked="" type="checkbox"/> FEE <input type="checkbox"/>
6. State Oil & Gas Lease No.	E-347-47
7. Lease Name or Unit Agreement Name	San Juan 31-6 Unit
8. Well Number	38F
9. OGRID Number	217817
10. Pool name or Wildcat	Blanco MV / Basin DK

SUNDRY NOTICES AND REPORTS ON WELLS  
(DO NOT USE THIS FORM FOR PROPOSALS TO DRILL OR TO DEEPEN OR PLUG BACK TO A  
DIFFERENT RESERVOIR. USE "APPLICATION FOR PERMIT" (FORM C-101) FOR SUCH  
PROPOSALS.)

1. Type of Well:  
Oil Well ☐ Gas Well ☒ Other

2. Name of Operator  
**ConocoPhillips Company**

3. Address of Operator  
**P.O. Box 4289, Farmington, NM 87499-4289**

4. Well Location

Unit Letter H : 1600' feet from the North line and 400' feet from the East line

Section 2 Township 30N Range R6W NMPM Rio Arriba County

11. Elevation (Show whether DR, RKB, RT, GR, etc.)

12. Check Appropriate Box to Indicate Nature of Notice, Report or Other Data

NOTICE OF INTENTION TO:

PERFORM REMEDIAL WORK ☐ PLUG AND ABANDON ☐

TEMPORARILY ABANDON ☐ CHANGE PLANS ☒

PULL OR ALTER CASING ☐ MULTIPLE COMPLETION ☐

OTHER ☐

SUBSEQUENT REPORT OF:

REMEDIAL WORK ☐ ALTERING CASING ☐

COMMENCE DRILLING OPNS. ☐ PLUG AND ABANDONMENT ☐

CASING TEST AND CEMENT JOB ☐

OTHER: ☐

13. Describe proposed or completed operations. (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work). SEE RULE 1103. For Multiple Completions: Attach wellbore diagram of proposed completion or recompletion.

Conocophillips requests permission to have the option to either drill a 12-1/4" hole for the surface casing, as permitted in our APDs or drilling a 13-1/2" hole. The new H&P rigs COPC is using have the capability of pumping the cement used at a higher rate than the older rigs. The larger hole makes it easier to run and cement of the surface casing.

Our drilling schedules change often and we don't know at the time of permitting which rig will be used to drill the well. This is the reason we need to have the option to use either size hole on the surface casing. The wells drilled with the H&P rigs will use the 13-1/2" hole & will use approx. 225 sx of Class G cement (1.17 yield @ 15.8 density). The cement will be pumped and circulated to surface.

I hereby certify that the information above is true and complete to the best of my knowledge and belief. I further certify that any pit or below-grade tank has been/will be constructed or closed according to NMOCD guidelines ☐, a general permit ☐ or an (attached) alternative OCD-approved plan.

SIGNATURE Patsy Clugston TITLE Sr. Regulatory Specialist DATE 7/31/06

Type or print name Patsy Clugston E-mail address: pclugston@br-inc.com Telephone No. 505-326-9518

(This space for State use)

APPROVED BY [Signature] TITLE DEPUTY OIL & GAS INSPECTOR, DIST. 8 DATE AUG 03 2006

Conditions of approval, if any: