District I
1625 N. French Dr., Hobbs, NM 88240
District II
1301 W. Grand Avenue, Artesia, NM 88210
District III
1000 Rio Brazos Road, Lztec, NM 87410
District IV
1220 S. St. Francis Dr., Santa Fe, NM 87505

State of New Mexico Energy Minerals and Natural Resources

For drilling and production facilities, submit to appropriate NMOCD District Office.
For downstream facilities, submit to Santa Fe office

Form C-144

June 1, 2004

Oil Conservation Division 1220 South St. Francis Dr. Santa Fe, NM 87505

Pit or Below-Grade Tank Registration or Closure
Is pit or below-grade tank covered by a "general plan"? Yes No

Type of action. Registration of a pit of	r below-grade tank L Closure of a pit or below-grad	iculik 🖸			
Operator: Burlington Resources Telephone:	(505) 326-9841 e-mail address: <u>LH</u> :	asely@br-inc.com			
Address: 3401 East 30th Street, Farmington, New Mexico, 87402					
Facility or well name: Thompson No. 3A API #:	: 30045233210000 U/L or Qt	tr/Qtr <u>J</u> Sec <u>34 T_31N_R 12W</u>			
	36.85355 Longitude -108.08207	NAD: 1927 ⊠ 1983 □			
Surface Owner: Federal State Private Indian	20100000				
	Below-grade tank				
Pit Type: Drilling ☐ Production ☑ Disposal ☐					
	Below-grade tank Volume: 60 bbl Type of fluid: Produced Water and Incidental Oil Construction material: Fiberglass Double-walled, with leak detection? Yes If not, explain why not Construction material: Fiberglass No. Tank in place prior to Rule 50. Less than 50 feet (20 points) 50 feet or more, but less than 100 feet (10 points)				
Workover ☐ Emergency ☐	Construction material: Fiberglass AUG 2000				
Lined Unlined	Double-walled, with leak detection? Yes I If not,	explain why not the second of			
Liner type: Synthetic Thicknessmil Clay _	No. Tank in place prior to Rule 50.	See Office Control			
Pit Volumebbl		ES DECOLL			
Depth to ground water (vertical distance from bottom of pit to seasonal	Less than 50 feet	(20 points)			
high water elevation of ground water.)	50 feet or more, but less than 100 feet	(10 points)			
light water cievation of ground water.)	100 feet or more	(0 points) 0			
200.0	Yes	(20 points)			
Wellhead protection area: (Less than 200 feet from a private domestic	No	(0 points) 0			
water source, or less than 1000 feet from all other water sources.)					
Distance to surface water: (horizontal distance to all wetlands, playas,	Less than 200 feet	(20 points)			
irrigation canals, ditches, and perennial and ephemeral watercourses.)	200 feet or more, but less than 1000 feet	(10 points)			
inguiton canado, ancerco, ana porcionas and epitementa material and	1000 feet or more	(0 points) 10			
	Ranking Score (Total Points)	10			
If this is a pit closure: (1) Attach a diagram of the facility showing the pit's		•			
your are burying in place) onsite 🗌 offsite 🔲 If offsite, name of facility					
date. (4) Groundwater encountered: No 🖾 Yes 🔲 If yes, show depth below	-	results.			
(5) Attach soil sample results and a diagram of sample locations and excavat	ions.				
Additional Comments:					
The soils tested clean and no soil remediation was required.					
I hereby certify that the information above is true and complete to the best of my knowledge and belief. I further certify that the above-described pit or below-grade tank					
has been/will be constructed or closed according to NMOCD guidelines , a general permit , or an (attached) alternative OCD-approved plan .					
Date: 8/21/06					
Date: 8/2/36 Printed Name/Title Mr. Ed Hasely, Environmental Advisor Signature					
Your certification and NMOCD approval of this application/closure does not relieve the operator of liability should the contents of the pit or tank contaminate ground water or otherwise endanger public health or the environment. Nor does it relieve the operator of its responsibility for compliance with any other federal, state, or local laws and/or regulations.					
SEPUTY OIL & GAS INSPECTOR, DIST. @8					
1 - 1/					
Printed Name/Title Signature Ball Date:					

CLIENT: BURLINGTUN RESOURCE		5796 Farmin	IROTE (NIAL SCIENTIS U.S. HIGHWA NGTON, NEW A ONE: (505) 6:	EXICO 87401		LOC		10:
FIELD REPOR	T:	CLOSU	RE V	ERIFIC	CATION	J PAGE	E No: _	1_ of _1_
LOCATION: <u>name: Thom</u> quad/unit: J sec: 1 qtr/fddtage:		: 310 RNG:		I NMM CNT	Y: JJ ST: N	DATE	STARTED: FINISHED: ONMENTAL ALIST:	24 July-06 24 - July-06 JT
EXCAVATION APPROX	A	LEASI	 E:	REMEDIATI	ON METI	HOD:	UA	
FIELD NOTES & REMAR DEPTH TO GROUNDWATER:	NEAR	REST VATER SUED TPH CLOSUR	DURCE:	<u>ф</u> N ОСО РРМ	EAREST SURF	CHI	ECK ON ABANDOI	VE_:
	TIME	SAMPLE I.D.	LAB No:	137	mL. FREON		 	
SCALE 0 FT PIT PERIME	TER		OVM		20 PJ'	r pr	0511.F	636
Lizi,	ą N	SAMPI 10 1 2 3 4 5	AB SAMF	HEADSPACE D (ppm)		3.	7.	

COLOR LAND



EPA METHOD 418.1 TOTAL PETROLEUM HYDROCARBONS

Client:

Burlington Resources

Project #:

92115-046-093

Sample No.:

1

Date Reported:

7/24/2006

Sample ID:

Discrete, 3' Below BGT

Date Sampled:

7/24/2006

Sample Matrix:

Soil

Date Analyzed:

7/24/2006

Preservative:

Cool

Analysis Needed:

TPH-418.1

Condition:

Cool and Intact

		Det.
	Concentration	Limit
Parameter	(mg/kg)	(mg/kg)

Total Petroleum Hydrocarbons

636

5.0

ND = Parameter not detected at the stated detection limit.

References:

Method 418.1, Petroleum Hydrocarbons, Total Recoverable, Chemical Analysis

and Waste, USEPA Storet No. 4551, 1978.

Comments:

Thompson No. 3A

Instrument callibrated to 200 ppm standard. Zeroed before each sample

Reviev



CONTINUOUS CALIBRATION EPA METHOD 418.1 TOTAL PETROLEUM HYDROCARBONS

Cal. Date:

24-Jul-06

Parameter	Standard Concentration mg/L	Concentration Reading mg/L	
ТРН	100		
	200	205	
	500		
	1000		

The accepted percent relative deviation (%RSD) of the calibration factor is less than 20% over the working range.

<u>J. Mongson</u> Analyst

25-Jucy-Ob

Date

Review

Date