Form 3160-5 · (August 1999)

Approved by

Conditions of approval, if any, are attached. Approval of this notice does not warrant or certify that the applicant holds legal or equitable title to those rights in the subject lease which would entitle the applicant to conduct operations thereon.

UNITED STATES DEPARTMENT OF THE INTERIOR BUREAU OF LAND MANAGEMENT

SUNDRY NOTICES AND REPORTS ON WELLS

FORM APPROVED OMB NO. 1004-0135 Expires: November 30, 2000

Date 2 > 2003

FARMINGIUM FIELD OFFICE

NM	CFI	ገΩՐ	1/11	OΛ

Do not use this form for abandoned well. Use Fort	proposals to drill or t n 3160-3 (APD) for :	lo re-enteram	23 M 19: 27. If Indian,	Allottee or Tribe Name	
SUBMIT IN TRIPLICATE -	Other instructions	on reverse side Farn	nington, NW7. If Unit or	CA/Agreement, Name and/or	
Type of Well Oil Well		E Out		Init #253A	
3a. Address 5525 Highway 64, NBU 3004, Farmington 4. Location of Well (Footage, Sec., T., R., M., or Survey I Unit P (SESE) 1180' FSL & 690' FEL Setion 27, T32N, R8W	on, NM 87401	3b. Phone No. (include di 505 \$99-3454)	Field an Basin Fru	L671-00-X1 d Pool, or Exploratory Area Litland Coal or Parish, State	
12. CHECK APPROPRIATE	BOX(ES) TO INDI	CATE NATURE OF I	NOTICE, REPORT, OR O	THER DATA	
TYPE OF SUBMISSION		TYPE OF ACTION			
Notice of Intent X Subsequent Report Final Abandonment Notice	Acidize Alter Casing Casing Repair Change Plans Convert to Injection	Deepen Fracture Treat New Construction Plug and Abandon Plug Back	Production (Start/Resume) Reclamation Recomplete Temporarily Abandon Water Disposal	Water Shut-Off Well Integrity X Other NTL - FRA - 90 - 1	
13. Describe Proposed or Completed Operation (clearly If the proposal is to deepen directionally or recomp Attach the Bond under which the work will be per following completion of the involved operations. It testing has been completed. Final Abandonment Metermined that the final site is ready for final inspect Description of cement job to fulf Alamo Formations as per NTL-FRA-9 Date - 7/21/03; Time Started - 00 Hole size 8-3/4"; Casing 7", 20#, Turbo Centralizers - 2596', 2555' Spring Type Centralizers - 3437', Preflush - 30 bbls FW w/dye in la Stage 1 - Lead - 440 sx (1148.4 c Cellophane Flakes (D029), & 0.2% cement w/2% Bentonite (D020), 2% & .2% Antifoam (D046). Volume Circulated - 49.5 sx good Average Pressure - 730 psi; Average	lete horizontally, give subformed or provide the Be filed operation results in lotices shall be filed only stion.) ill requirements 0-1. 00 hrs; Time comp J-55 ST&C (new) , 2513' 3362', 3279', 33st 10 bbls. f - 204.5 bbl slu Flocele (D046). CaCl2 (S001), 5#/	osurface locations and mean and No. on file with BLM. a multiple completion or related a multiple completion or related - 0130 hrs. Set @ 3447'. 197', 3114', 3032' urry) Class G ceme Tail - 105 sx (13/sx Gilsonite (D02) d w/20 bbls FW & 1	sured and true vertical depths of MBIA. Required subsequent representation in a new interval, a cluding reclamation, have been of usable water zones 1. 201' 201	rall pertinent markers and zone orts shall be filed within 30 da Form 3160-4 shall be filed on completed, and the operator has including the Ojo 79), 0.25#/sx urry) 50/50/G/POZ ane Flakes (D029),	
14. I hereby certify that the foregoing is true and correct Name (Printed/Typed)	Paţśy Clugston	Title	Administrative Assist	ant	
Hatser Cluster	racsy cruyston	Date 7/22/0	3		
7) 7	CDACE FOR FERE	DAL OD STATE OF	ACCEPT	ED FOR RECORL	

THIS SPACE FOR FEDERAL OR STATE OFFICE USE

Title

Office