

**UNITED STATES
DEPARTMENT OF THE INTERIOR
BUREAU OF LAND MANAGEMENT**

Sundry Notices and Reports on Wells

2006 SEP 6 5:11 AM
Lease Number
SF-078543

RECEIVED
070 FARMINGTON NM
If Indian, All. or
Tribe Name

1. Type of Well
GAS

2. Name of Operator
ConocoPhillips

3. Address & Phone No. of Operator

PO Box 4289, Farmington, NM 87499 (505) 326-9700

4. Location of Well, Footage, Sec., T, R, M

Unit G, (SWNE) 1685' FNL & 1960' FEL, Sec. 33, T32N, R7W, NMPM

7. Unit Agreement Name

8. San Juan 32-7 Unit
Well Name & Number

9. SJ 32-7 Unit #038
API Well No.

30-045-33690

10. Field and Pool

Basin Dakota/Blanco MV

11. County and State
San Juan, NM

12. CHECK APPROPRIATE BOX TO INDICATE NATURE OF NOTICE, REPORT, OTHER DATA

Type of Submission	Type of Action	
<input type="checkbox"/> Notice of Intent	<input type="checkbox"/> Abandonment	<input type="checkbox"/> Change of Plans
<input checked="" type="checkbox"/> Subsequent Report	<input type="checkbox"/> Recompletion	<input type="checkbox"/> New Construction
<input type="checkbox"/> Final Abandonment	<input type="checkbox"/> Plugging	<input type="checkbox"/> Non-Routine Fracturing
	<input type="checkbox"/> Casing Repair	<input type="checkbox"/> Water Shut off
	<input type="checkbox"/> Altering Casing	<input type="checkbox"/> Conversion to Injection

☒ Other - Casing Report

13. Describe Proposed or Completed Operations

8/18/06 RIH w/8 3/4" bit - tagged cement @ 201'. D/O & ahead to 3801' intermediate. Circ. hole. RU casing crew. RIH w/88 jts, 7" 20#, J-55 casing & set @ 3799'. RU to cement. Pumped preflush. Pumped Scavenger 19 sx(57cf-10 bbls) Premium Lite Cement w/ 3% CaCl, .25 #/sx Cello-Flake, 5#/sx LCM-1, .4% FL-52, & .4% SMS. **Lead**-Pumped 442 sx (942 cf- 168bbls) Premium Lite Cement w/ 3% CaCl, .25 #/sx Cello-Flake, 5 #/sx LCM-1, .4% FL-52, & .4% SMS. **Tailed** w/ sx90 (124 cf - 22 bbls) Type III cement w/1% CaCl, .25 #/sx Cello-Flake, & .2% FL-52. Dropped plug and displaced w/151 bbls H2O. Bumped plug to 1500 psi. Plug down @ 1515 on 8/22/06. Circ. 65 bbls cement to surface. NDNU BOPE. PT 600 #/30 min- Test OK.

Report
Grade
8/23/06 RIH w/6 1/4" bit - tagged cement @ 3735'. D/O & ahead to 8205' (TD). TD reached on 8/25/06. Circ hole. RU casing crew. RIH w/201 jts 4.5" 11.9# ST & C casing set @ 8203'. RU cement. Pumped pre-flush of 10 bbls mud clean/2 bbls FW. **Lead**- Pumped 9 sx(28 cf- 5 bbls) Scavenger cement w/.3% CD-32, 1% FL-52, 6.25 #/sx LCM-1. **Tailed** w/ 312 sx(618cf- 110 bbls) Premium Lite cement w/.25 #/sx Cello-Flake, .3% CD- 32, 6.25 #/sx LCM-1, & 1% FL-52. Bumped plug & displaced w/127 bbls H2O. RD cementers, WOC. ND, BOPE, RD RR @ 0600 hrs.

PT for 4 1/2" casing will be done by completion rig. PT & TOC results will be shown on next report.

14. I hereby certify that the foregoing is true and correct.

Signed Tracey N. Monroe Tracey N. Monroe Title Regulatory Assistant Date 8/28/06

(This space for Federal or State Office use)

APPROVED BY _____ Title _____

CONDITION OF APPROVAL, if any:

Title 18 U.S.C. Section 1001, makes it a crime for any person knowingly and willfully to make any department or agency of the United States any false, fictitious or fraudulent statements or representations as to any matter within its jurisdiction.

ACCEPTED FOR RECORD

Date
SEP 08 2006

FARMINGTON FIELD OFFICE

NMOCD