UNITED STATES DEPARTMENT OF THE INTERIOR BUREAU OF LAND MANAGEMENT

Sundry Notices and Reports on Wells	6010	
R. Service	2006 SEP5.	6 Lease Number
Type of Wall		NMNM-03541
GAS		C Elf/Indian, All. or
	OTOTAN	MINTIPE Name
£2	7.	Unit Agreement Name
. Name of Operator		
BURLINGTON		
RESCURCES OIL & GAS COMPANY LP		
	o	Wall Names & Normalism
Address & Phone No. of Operator	 8.	Well Name & Number
Address to I home two or operator		Hancock #712S
PO Box 4289, Farmington, NM 87499 (505) 326-9700	9.	API Well No.
<u> </u>		·
Location of Well, Footage, Sec., T, R, M		30-045-33519
4. Location of Well, Footage, Sec., T, R, M	10.	Field and Pool
		
Unit P (SESE), 955' FSL & 480' FEL, Sec. 29, T28N, R09W, NMPM		Basin Fruitland Coal
	11.	County and State
	11.	San Juan, Co NM
Type of Submission Type of Action X Notice of Intent Abandonment Change of Plans Recompletion New Construction Plugging Non-Routine Fracturing	EPORT, OTHER X Other – S	
Type of Submission Type of Action X Notice of Intent Abandonment Change of Plans Recompletion New Construction	ŕ	
Type of Submission Type of Action X Notice of Intent Abandonment Change of Plans Recompletion New Construction Plugging Non-Routine Fracturing Casing Repair Water Shut off	ŕ	
Type of Submission X Notice of Intent Abandonment Recompletion New Construction Non-Routine Fracturing Casing Repair Final Abandonment Altering Casing Conversion to Injection 3. Describe Proposed or Completed Operations 8/28/06 MIRU MOTE #1. Spud 8 ¾" hole @ 10:00, 8/28/06. Drilled to 319'. Conditation T&C casing and set @ 313'. Pump pre-flush, pumped 110sxs (141cf – 25 bbl slurry s/sx Cello-flakes. Dropped plug & displaced with 12 BBL H2O. Circ. 12 bbls ceme RDMO.	X Other - Solitioned hole. RU y). Type 5 Cemen	w/13 jts- 7" J-55, 20#, t w/2% CaCl, & .25
Type of Submission X Notice of Intent Abandonment Recompletion New Construction New Const	X Other - Solitioned hole. RU y). Type 5 Cemen	w/13 jts- 7" J-55, 20#, t w/2% CaCl, & .25
Type of Submission X Notice of Intent Abandonment Recompletion New Construction Non-Routine Fracturing Casing Repair Final Abandonment Altering Casing Conversion to Injection 3. Describe Proposed or Completed Operations 8/28/06 MIRU MOTE #1. Spud 8 ¾" hole @ 10:00, 8/28/06. Drilled to 319'. Conditation T&C casing and set @ 313'. Pump pre-flush, pumped 110sxs (141cf – 25 bbl slurry s/sx Cello-flakes. Dropped plug & displaced with 12 BBL H2O. Circ. 12 bbls ceme RDMO.	X Other - Solitioned hole. RU y). Type 5 Cemen	w/13 jts- 7" J-55, 20#, t w/2% CaCl, & .25
Type of Submission X Notice of Intent Abandonment Recompletion New Construction Non-Routine Fracturing Casing Repair Altering Casing Conversion to Injection 3. Describe Proposed or Completed Operations 8/28/06 MIRU MOTE #1. Spud 8 3/4" hole @ 10:00, 8/28/06. Drilled to 319'. Conditation T&C casing and set @ 313'. Pump pre-flush, pumped 110sxs (141cf – 25 bbl slurry s/sx Cello-flakes. Dropped plug & displaced with 12 BBL H2O. Circ. 12 bbls ceme RDMO. T will be conducted by the drilling rig & results shown on next report.	X Other - Solitioned hole. RU y). Type 5 Cemen	w/13 jts- 7" J-55, 20#, t w/2% CaCl, & .25
Type of Submission X Notice of Intent Abandonment Recompletion New Construction Non-Routine Fracturing Casing Repair Altering Casing Conversion to Injection 3. Describe Proposed or Completed Operations 8/28/06 MIRU MOTE #1. Spud 8 3/4" hole @ 10:00, 8/28/06. Drilled to 319'. Conditation T&C casing and set @ 313'. Pump pre-flush, pumped 110sxs (141cf – 25 bbl slurry s/sx Cello-flakes. Dropped plug & displaced with 12 BBL H2O. Circ. 12 bbls ceme RDMO. T will be conducted by the drilling rig & results shown on next report.	X Other - Solitioned hole. RU y). Type 5 Cemen	w/13 jts- 7" J-55, 20#, t w/2% CaCl, & .25
Type of Submission X Notice of Intent Abandonment Recompletion New Construction Non-Routine Fracturing Casing Repair Altering Casing Conversion to Injection 3. Describe Proposed or Completed Operations 8/28/06 MIRU MOTE #1. Spud 8 3/4" hole @ 10:00, 8/28/06. Drilled to 319'. Conditation T&C casing and set @ 313'. Pump pre-flush, pumped 110sxs (141cf – 25 bbl slurry s/sx Cello-flakes. Dropped plug & displaced with 12 BBL H2O. Circ. 12 bbls ceme RDMO. T will be conducted by the drilling rig & results shown on next report.	X Other - Solitioned hole. RU y). Type 5 Cemen	w/13 jts- 7" J-55, 20#, t w/2% CaCl, & .25
Type of Submission X Notice of Intent Abandonment Recompletion New Construction New Construction New Construction Plugging Casing Repair Water Shut off Final Abandonment Altering Casing Conversion to Injection 3. Describe Proposed or Completed Operations 8/28/06 MIRU MOTE #1. Spud 8 ¾" hole @ 10:00, 8/28/06. Drilled to 319'. Conditation T&C casing and set @ 313'. Pump pre-flush, pumped 110sxs (141cf – 25 bbl slurry sixx Cello-flakes. Dropped plug & displaced with 12 BBL H2O. Circ. 12 bbls ceme RDMO. T will be conducted by the drilling rig & results shown on next report. APD/ROW	X Other – Solitioned hole. RU V). Type 5 Cement to surface. WO	w/13 jts- 7" J-55, 20#, t w/2% CaCl, & .25 DC, install wellhead,
Type of Submission X Notice of Intent Abandonment Recompletion New Construction New Construction Plugging Casing Repair Water Shut off Final Abandonment Altering Casing Conversion to Injection 3. Describe Proposed or Completed Operations 8/28/06 MIRU MOTE #1. Spud 8 ¾" hole @ 10:00, 8/28/06. Drilled to 319'. Conditation T&C casing and set @ 313'. Pump pre-flush, pumped 110sxs (141cf – 25 bbl slurry/sx Cello-flakes. Dropped plug & displaced with 12 BBL H2O. Circ. 12 bbls ceme RDMO. T will be conducted by the drilling rig & results shown on next report. APD/ROW	X Other - Solitioned hole. RU y). Type 5 Cemen	w/13 jts- 7" J-55, 20#, t w/2% CaCl, & .25 DC, install wellhead,
Type of Submission X Notice of Intent Abandonment Abandonment Change of Plans Recompletion New Construction New C	X Other – Solitioned hole. RU V). Type 5 Cement to surface. WO	w/13 jts- 7" J-55, 20#, t w/2% CaCl, & .25 DC, install wellhead,
Type of Submission X Notice of Intent Abandonment Recompletion New Construction New Constr	X Other – Solitioned hole. RU V). Type 5 Cement to surface. WO	w/13 jts- 7" J-55, 20#, t w/2% CaCl, & .25 DC, install wellhead,
Type of Submission X Notice of Intent Abandonment Recompletion New Construction New Construction New Construction Plugging Casing Repair Water Shut off Final Abandonment Altering Casing Conversion to Injection 3. Describe Proposed or Completed Operations 8/28/06 MIRU MOTE #1. Spud 8 ¾" hole @ 10:00, 8/28/06. Drilled to 319'. Conditation T&C casing and set @ 313'. Pump pre-flush, pumped 110sxs (141cf – 25 bbl slurry sixx Cello-flakes. Dropped plug & displaced with 12 BBL H2O. Circ. 12 bbls ceme RDMO. T will be conducted by the drilling rig & results shown on next report. APD/ROW	X Other – Solitioned hole. RU V). Type 5 Cement to surface. WO	w/13 jts- 7" J-55, 20#, t w/2% CaCl, & .25 DC, install wellhead,