

UNITED STATES
DEPARTMENT OF THE INTERIOR
BUREAU OF LAND MANAGEMENT

APPLICATION FOR PERMIT TO DRILL, DEEPEN, OR PLUG BACK

1a. Type of Work DRILL	5. Lease Number NMSF-078147 Unit Reporting Number 073322 DK-NMNM-873964	6. If Indian, All. or Tribe
1b. Type of Well GAS	7. Unit Agreement Name	
2. Operator ConocoPhillips	8. Farm or Lease Name	
3. Address & Phone No. of Operator PO Box 4289, Farmington, NM 87499 (505) 326-9700	9. Well Number Moore Com #1M	
4. Location of Well Unit D (NWNW), 660' FNL & 1050' FWL, Latitude 36° 96224'N Longitude 108° 05229'W	10. Field, Pool, Wildcat Blanco MV / Basin DK 11. Sec., Twn, Rge, Mer. (NMPM) Sec. 25, T32N, R12W API # 30-045-33786	
14. Distance in Miles from Nearest Town	12. County San Juan	13. State NM
15. Distance from Proposed Location to Nearest Property or Lease Line 660'	17. Acres Assigned to Well MV 320 - N/2 & DK 320.0 - W/2	
16. Acres in Lease	18. Distance from Proposed Location to Nearest Well, Drig, Compl, or Applied for on this Lease	
19. Proposed Depth 7792'	20. Rotary or Cable Tools Rotary	
21. Elevations (DF, FT, GR, Etc.) 6536' GL	22. Approx. Date Work will Start	
23. Proposed Casing and Cementing Program See Operations Plan attached	24. Authorized by: <i>Patsy Clayton</i> Sr. Regulatory Analyst	
		Date: <i>9/8/06</i>

PERMIT NO.

APPROVAL DATE

APPROVED BY

TITLE

DATE

Archaeological Report attached

Environmental Assessment is attached.

NOTE: This format is issued in lieu of U.S. BLM Form 3160-3

Title 18 U.S.C. Section 1001, makes it a crime for any person knowingly and willfully to make to any department or agency of the United States any false, fictitious or fraudulent statements or presentations as to any matter within its jurisdiction.

This action is subject to technical and procedural review pursuant to 43 CFR 3165.3 and appeal pursuant to 43 CFR 3165.4

DRILLING OPERATIONS AUTHORIZED ARE SUBJECT TO COMPLIANCE WITH ATTACHED "GENERAL REQUIREMENTS".

District II
PO Drawer DD, Artesia, NM 88211-0719

District III
1000 Rio Brazos Rd., Aztec, NM 87410

District IV
PO Box 2088, Santa Fe, NM 87504-2088

OIL CONSERVATION DIVISION
PO Box 2088
Santa Fe, NM 87504-2088

☐ AMENDED REPORT

WELL LOCATION AND ACREAGE DEDICATION PLAT

*API Number 30-045-33786	*Pool Code 72319 / 71599	*Pool Name BLANCO MESAVERDE / BASIN DAKOTA
*Property Code 31832	*Property Name MOORE COM	*Well Number 1M
*OGRID No. 217817	*Operator Name CONOCOPHILLIPS COMPANY	*Elevation 6536'

¹⁰ Surface Location

UL or lot no.	Section	Township	Range	Lot Idn	Feet from the	North/South line	Feet from the	East/West line	County
D	25	32N	12W		660	NORTH	1050	WEST	SAN JUAN

¹¹Bottom Hole Location If Different From Surface

UL or lot no.	Section	Township	Range	Lot Idn	Feet from the	North/South line	Feet from the	East/West line	County
¹² Dedicated Acres	320.0 Acres - N/2 (MV) 320.0 Acres - W/2 (DK)				¹³ Joint or Infill	¹⁴ Consolidation Code	¹⁵ Order No.		

NO ALLOWABLE WILL BE ASSIGNED TO THIS COMPLETION UNTIL ALL INTERESTS HAVE BEEN CONSOLIDATED
OR A NON-STANDARD UNIT HAS BEEN APPROVED BY THE DIVISION

16

5243.04'

660'

1050'

LAT: 36.96224°N
LONG: 108.05229°W
DATUM: NAD83

LEASE SF-078147

LEASE SF-078147

LEASE FEE

1320.00'

1316.70'

5375.04'

25

LEASE SF-078147

LEASE FEE

1327.92'

1318.68'

5196.84'

17 OPERATOR CERTIFICATION

I hereby certify that the information contained herein is true and complete to the best of my knowledge and belief.

Virgil E. Chavez

Signature
Virgil E. Chavez

Printed Name
Projects & Operations Lead

Title
June 6, 2006

Date

18 SURVEYOR CERTIFICATION

I hereby certify that the well location shown on this plat was plotted from field notes of actual surveys made by me or under my supervision, and that the same is true and correct to the best of my belief.

Survey Date: FEBRUARY 20, 2006

Signature and Seal of Professional Surveyor

JASON C. EDWARDS
NEW MEXICO
REGISTERED PROFESSIONAL SURVEYOR
15269

JASON C. EDWARDS
Certificate Number 15269

District I

1625 N. French Dr., Hobbs, NM 88240

District II

1301 W. Grand Ave., Artesia, NM 88210

District III

1000 Rio Brazos Rd., Aztec, NM 87410

District IV

1220 S. St. Francis Dr., Santa Fe, NM 87505

OIL CONSERVATION DIVISION

1220 South St. Francis Dr.

Santa Fe, NM 87505

WELL API NO.

30-045-

5. Indicate Type of Lease

STATE ☐

FEE ☐

6. State Oil & Gas Lease No.

Federal Lease - 078147

7. Lease Name or Unit Agreement Name

Moore Com

8. Well Number

#1M

9. OGRID Number

217817

10. Pool name or Wildcat

Blanco Mesaverde / Basin Dakota

SUNDRY NOTICES AND REPORTS ON WELLS
(DO NOT USE THIS FORM FOR PROPOSALS TO DRILL OR TO DEEPEN OR PLUG BACK TO A DIFFERENT RESERVOIR. USE "APPLICATION FOR PERMIT" (FORM C-101) FOR SUCH PROPOSALS.)

1. Type of Well:

Oil Well ☐

Gas Well ☒

Other

2. Name of Operator

ConocoPhillips Company

3. Address of Operator

3401 E. 30TH STREET, FARMINGTON, NM 87402

4. Well Location

Unit Letter D : 660 feet from the North line and 1050 feet from the West line
Section 25 Township 32N Rng 12W NMPM County San Juan

11. Elevation (Show whether DR, RKB, RT, GR, etc.)

6536'

Pit or Below-grade Tank Application

☐ or Closure ☐

Pit type

New Drill

Depth to Groundwater

>100'

Distance from nearest fresh water well

>1000'

Distance from nearest surface water

2200'
≤1000'

Pit Liner Thickness:

12

mil

Below-Grade Tank:

Volume

bbls;

Construction Material

12. Check Appropriate Box to Indicate Nature of Notice, Report or Other Data

NOTICE OF INTENTION TO:

PERFORM REMEDIAL WORK ☐

PLUG AND ABANDON ☐

TEMPORARILY ABANDON ☐

CHANGE PLANS ☐

PULL OR ALTER CASING ☐

MULTIPLE COMPL ☐

SUBSEQUENT REPORT OF:

REMEDIAL WORK ☐

ALTERING CASING ☐

COMMENCE DRILLING OPNS. ☐

P AND A ☐

CASING/CEMENT JOB ☐

OTHER:

New Drill

☒

OTHER: ☐

13. Describe proposed or completed operations. (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work). SEE RULE 1103. For Multiple Completions: Attach wellbore diagram of proposed completion or recompletion.

We are constructing Drilling and workover pits as per our General plan on file with the OCD dated June 2005 and we are closing all pits as per the November 1, 2004 Guidelines. Please be sure to include this language on all pit NOI's and C-144's.

I hereby certify that the information above is true and complete to the best of my knowledge and belief. I further certify that any pit or below-grade tank has been/will be constructed or closed according to NMOC guidelines ☐, a general permit ☒ or an (attached) alternative OCD-approved plan ☐.

SIGNATURE

Patsy Clugston

TITLE

Sr. Regulatory Analyst

DATE

6/8/2006

Type or print name

Patsy Clugston

E-mail address:

pclugston@br-inc.com

Telephone No.

505-326-9518

For State Use Only

APPROVED BY

[Signature]

TITLE

DEPUTY OIL & GAS INSPECTOR, DIST. ☒


DATE

SEP 15 2006

Conditions of Approval (if any):




CONOCOPHILLIPS COMPANY MOORE COM #1M
660' FNL & 1050' FWL, SECTION 25, T32N, R12W, NMPM
SAN JUAN COUNTY, NEW MEXICO ELEVATION: 6536'

LATITUDE: 36.96224° N
LONGITUDE: 108.05229° W
 DATUM: NAD1983



PLAT NOTE:

SURFACE OWNER
 Bureau of Land
 Management



PROJECT PROPOSAL - New Drill / Sidetrack

San Juan Business Unit

MOORE COM 1M

Lease:	AFE #: WAN.CNV.6144			AFE \$:
Field Name: NEW MEXICO-NORTH	Rig: 486-0597	State: NM	County: SAN JUAN	API #:
Geoscientist: Glaser, Terry J	Phone: (832)486-2332	Prod. Engineer: Piotrowicz, Greg M.	Phone: +1 832-486-3486	
Res. Engineer: Tomberlin, Timothy A	Phone: (832) 486-2328	Proj. Field Lead: Fransen, Eric E.	Phone:	

Primary Objective (Zones):

Zone	Zone Name
R20002	MESAVERDE(R20002)
R20076	DAKOTA(R20076)

Location: Surface Datum Code: NAD 27 Straight Hole

Latitude: 36.962240	Longitude: -108.052290	X:	Y:	Section: 25	Range: 12W
Footage X: 1050 FWL	Footage Y: 660 FNL	Elevation: 6536 (FT)	Township: 32N		
Tolerance:					

Location Type: Year Round	Start Date (Est.):	Completion Date:	Date In Operation:
---------------------------	--------------------	------------------	--------------------

Formation Data: Assume KB = 6552 Units = FT

Formation Call & Casing Points	Depth (TVD in Ft)	SS (Ft)	Depletion (Yes/No)	BHP (PSIG)	BHT	Remarks
SURFACE CSG	216	6336	<input type="checkbox"/>			Possible water flows. 12-1/4 hole. 9 5/8" 32.3 ppf, H-40, STC casing. Circulate cement to surface.
CJAM	1502	5050	<input type="checkbox"/>			Possible water flows.
KRLD	1752	4800	<input type="checkbox"/>			Possible gas.
FRLD	2852	3700	<input type="checkbox"/>			Possible gas.
PCCF	3102	3450	<input type="checkbox"/>			
LEWS	3302	3250	<input type="checkbox"/>			
Intermediate Casing	3402	3150	<input type="checkbox"/>			8 3/4" Hole. 7", 20 ppf, J-55, STC Casing. Circulate cement to surface.
CHRA	4152	2400	<input type="checkbox"/>			
CLFH	4792	1760	<input type="checkbox"/>			Gas; possibly wet
MENF	4902	1650	<input type="checkbox"/>			Gas.
PTLK	5352	1200	<input type="checkbox"/>			Gas.
CLLP	6892	-340	<input type="checkbox"/>			Gas. Possibly wet.
CRHN	7442	-890	<input type="checkbox"/>			Gas possible, highly fractured
PAGU	7652	-1100	<input type="checkbox"/>			Gas. Highly Fractured.
Total Depth	7792	-1240	<input type="checkbox"/>			6-1/4" Hole. 4-1/2", 11.6 ppf, N-80, LTC casing. Circulate cement a minimum of 100' inside the previous casing string. No open hole logs. Cased hole TDT with GR to surface.

Reference Wells:

Reference Type	Well Name	Comments
----------------	-----------	----------

HOLE: 12.25"
CSG OD: 9.625"
CSG ID: 9.001"
WGT: 32.3 ppf
GRADE: H-40
EXCESS: 125 %
DEPTH: 235'

SURFACE:
Option 1
148 sx
30.8 bbls
172.9 cuft
1.17 ft³/sx
15.8 ppg
4.973 gal/sx
Class G Cement
+ 3% S001 Calcium Chloride
+ 0.25 lb/sx D029 Cellophane Flakes

Option 2
143 sx
30.8 bbls
172.9 cuft
1.21 ft³/sx
15.6 ppg
5.29 gal/sx
Standard Cement
+ 3% Calcium Chloride
+ 0.25 lb/sx Floccle

Option 3
65 sx
18.6 bbls
104.3 cuft
1.61 ft³/sx
14.5 ppg
7.41 gal/sx
Type I-II Ready Mix
+ 20% Fly Ash

Comp. Strength
6 hrs 250 psi
8 hrs 500 psi

Comp. Strength
8 hrs 475 psi
24 hrs 1375 psi

HOLE: 8.75"
CSG OD: 7"
CSG ID: 6.456"
WGT: 20 ppf
GRADE: J-55
EXCESS: 150 %
TAIL: 680.4'
DEPTH: 3402'

INTERMEDIATE LEAD:
Option 1
359 sx
173.8 bbls
975.9 cuft
2.72 ft³/sx
11.7 ppg
15.74 gal/sx
Class G Cement
+ 3% D079 Extender
+ 0.20% D046 Antifoam
+ 10 lb/sx Phenoseal

Option 2
375 sx
173.8 bbls
975.9 cuft
2.60 ft³/sx
11.5 ppg
14.62 gal/sx
Type III Ashgrove Cement
+ 30 lb/sx San Juan Poz
+ 3% Bentonite
+ 5.0 lb/sx Phenoseal

Option 3
371 sx
173.8 bbls
975.9 cuft
2.63 ft³/sx
11.7 ppg
15.92 gal/sx
Class G Cement
+ 3% D079 Extender
+ 0.20% D046 Antifoam
+ 1.0 lb/bbl CemNet

Comp. Strength
9 hrs 300 psi
48 hrs 525 psi

Comp. Strength
1:47 hrs 50 psi
12 hrs 350 psi
24 hrs 450 psi

Comp. Strength
3 hrs 100 psi
24 hrs 443 psi

HOLE: 6.25"
CSG OD: 4.5"
CSG ID: 4"
WGT: 11.6 ppf
GRADE: N-80
EXCESS: 50 %
DEPTH: 7792'

INTERMEDIATE TAIL:
Option 1
203 sx
47.3 bbls
265.4 cuft
1.31 ft³/sx
13.5 ppg
5.317 gal/sx
50/50 Poz: Class G Cement
+ 0.25 lb/sx D029 Cellophane Flakes
+ 3% S001 Calcium Chloride
+ 2% D020 Bentonite
+ 1.5 lb/sx D024 Gilsontite Extender
+ 0.1% D046 Antifoamer
+ 6 lb/sx Phenoseal

Option 2
200 sx
47.3 bbls
265.4 cuft
1.33 ft³/sx
13.5 ppg
5.52 gal/sx
50/50 Poz: Standard Cement
+ 2% Bentonite
+ 6.0 lb/sx Phenoseal

Option 3
207 sx
47.3 bbls
265.4 cuft
1.28 ft³/sx
13.5 ppg
5.255 gal/sx
50/50 Poz: Class G Cement
+ 2% D020 Bentonite
+ 5.0 lb/sx D024 Gilsontite Extender
+ 2% S001 Calcium Chloride
+ 0.1% D046 Antifoamer
+ 0.15% D065 Dispersant
+ 1.0 lb/bbl CemNet

Comp. Strength
3:53 500 psi
8:22 1000 psi
24 hrs 3170 psi
48 hrs 5399 psi

Comp. Strength
2:05 50 psi
4:06 500 psi
12 hrs 1250 psi
24 hrs 1819 psi

Comp. Strength
24 hrs 1850 psi
48 hrs 3411 psi

PRODUCTION:
Option 1
486 sx
124.6 bbls
699.3 cuft
1.44 ft³/sx
13.0 ppg
6.47 gal/sx
50/50 Poz: Class G Cement
+ 0.25 lb/sx D029 Cellophane Flakes
+ 3% D020 Bentonite
+ 1.0 lb/sx D024 Gilsontite Extender
+ 0.25% D167 Fluid Loss
+ 0.25% D065 Dispersant
+ 0.1% D800 Retarder
+ 0.1% D046 Antifoamer
+ 3.5 lb/sx Phenoseal

Option 2
482 sx
124.6 bbls
699.3 cuft
1.45 ft³/sx
13.1 ppg
6.55 gal/sx
50/50 Poz: Standard Cement
+ 3% Bentonite
+ 0.2% CFR-3 Friction Reducer
+ 0.1% HR-5 Retarder
+ 0.8% Halad-9 Fluid Loss Additive
+ 3.5 lb/sx Phenoseal

Comp. Strength
9:32 50 psi
12 hrs 500 psi
13:29 1026 psi
24 hrs 2300 psi

Moore Com #1M

HOLE: 12.25 "
CSG OD: 9.625 "
CSG ID: 9.001 "
WGT: 32.3 ppf
GRADE: H-40
EXCESS: 125 %
DEPTH: 235'

SURFACE:

INTERMEDIATE LEAD:

Option 4

339 sx
173.8 bbls
975.9 cuft
2.88 ft³/sx
11.5 ppg
16.85 gal/sx
Standard Cement
+ 3% Econolite (Extender)
+ 10 lb/sx Phenoseal

Option 5
465 sx
173.8 bbls
975.9 cuft
2.10 ft³/sx
11.7 ppg
11,724 gal/sx
75% Type XI / 25% Class G Cement
+ 0.25 lb/sx D029 Cellophane Flakes
+ 3% D079 Extender
+ 0.20% D046 Antifoam

HOLE: 8.75 "
CSG OD: 7 "
CSG ID: 6.456 "
WGT: 20 ppf
GRADE: J-55
EXCESS: 150 %
TAIL: 680.4'

DEPTH: 3402'

INTERMEDIATE TAIL:

HOLE: 6.25 "
CSG OD: 4.5 "
CSG ID: 4 "
WGT: 11.6 ppf
GRADE: N-80
EXCESS: 50 %
DEPTH: 7792'

PRODUCTION:

TOPSET FRUITLAND COAL Wells: (topset casing above coal to prepare for cavitation/DO/UR)

Drilling Mud Program:

Surface: spud mud

Intermediate: fresh water mud with bentonite and polymer as needed

Below Intermediate: air/mist/nitrogen drilling media with foamer, polymer, & corrosion inhibitor as needed

Centralizer Program:

Surface: centralizers placed 10' above the shoe latched over a stop collar and at the top of the 2nd, 3rd, & 4th joints

Intermediate: centralizers placed 10' above the shoe latched over a stop collar and at the top of the 2nd, 4th, 6th, 8th, & 10th joints

Turbolizers placed one per joint from the top of the Ojo Alamo to the top of the Kirtland Shale

Below Intermediate: no centralizers used in air holes. In mud holes centralizers are spaced out appropriately

CASE & FRAC FRUITLAND COAL Wells: (casing set below coal to prepare for frac completion)

Drilling Mud Program:

Surface: spud mud

Production: fresh water mud with bentonite and polymer as needed

Centralizer Program:

Surface: centralizers placed 10' above the shoe latched over a stop collar and at the top of the 2nd, 3rd, & 4th joints

Production: centralizers placed 10' above the shoe latched over a stop collar and at the top of the 2nd, 4th, 6th, 8th, & 10th joints

Turbolizers placed one per joint from the top of the Ojo Alamo to the top of the Kirtland Shale

MESA VERDE Wells:

Drilling Mud Program:

Surface: spud mud

Intermediate: fresh water mud with bentonite and polymer as needed

Below Intermediate: air/mist drilling media with foamer, polymer, & corrosion inhibitor as needed

Centralizer Program:

Surface: centralizers placed 10' above the shoe latched over a stop collar and at the top of the 2nd, 3rd, & 4th joints

Intermediate: centralizers placed 10' above the shoe latched over a stop collar and at the top of the 2nd, 4th, 6th, 8th, & 10th joints

Turbolizers placed one per joint from the top of the Ojo Alamo to the top of the Kirtland Shale

Below Intermediate: no centralizers used in air holes. In mud holes centralizers are spaced out appropriately

DAKOTA Wells:

Drilling Mud Program:

Surface: spud mud

Intermediate: fresh water mud with bentonite and polymer as needed

Below Intermediate: air/mist/nitrogen drilling media with foamer, polymer, & corrosion inhibitor as needed

Centralizer Program:

Surface: centralizers placed 10' above the shoe latched over a stop collar and at the top of the 2nd, 3rd, & 4th joints


Intermediate: centralizers placed 10' above the shoe latched over a stop collar and at the top of the 2nd, 4th, 6th, 8th, & 10th joints

Turbolizers placed one per joint from the top of the Ojo Alamo to the top of the Kirtland Shale


Below Intermediate: no centralizers used in air holes. In mud holes centralizers are spaced out appropriately

BLOWOUT PREVENTER ARRANGEMENT & PROGRAM

For Drilling to TD and Setting 4.5 inch Casing



1. Rotating Head
- 2A. Fill-up Line & valve
- 2B. Bore Line (for Air Drilling)
3. Spacer Spool
4. Double Ram BOP (11", 3000 psi)
5. Pipe Rams
6. Blind Rams
7. Kill Line
8. Kill Line Check Valve
9. Kill Line Valve
10. Inner Choke Line Valve (3")
11. Outer Choke Line Valve (3")
12. Choke Line (3")
13. Variable Choke
14. Choke Line Valve (2")
15. Panic Line Valve (3")
16. Choke Manifold Pressure Gauge
17. Choke Line (2")
18. Mud Cross Spacer Spool
- 19A Csg Spool "B" Section (11", 3M)
- 19B "B" Section Csg Valve (2", 3M)
- 20A Csg Head "A" Section (11", 3M)
- 20B "A" Section Csg Valve (2", 3M)
21. 9 5/8" Casing Collar




After the 7" intermediate casing has been run and cemented, the Casing Spool ("B" Section) will be installed on the wellhead ("A" Section) and the BOP will be installed on the Casing Spool. A test plug will be set in the wellhead and the pipe rams, blind rams, and choke manifold will be tested to 200 psi to 300 psi (low pressure test) for 10 minutes and to 3000 psi (high pressure test) for 10 minutes. Then the test plug will be removed and the 7" casing will be pressure tested against closed blind rams to 200 psi to 300 psi for 10 minutes and to 1800 psi for 30 minutes - this test pressure is 48% of the minimum internal yield strength of 3740 psi for the 7", 20#, J-55, STC casing. Then we will air drill the 6-1/4" hole to TD and run and cement the 4-1/2" casing.

In addition to the equipment in the above diagram the following equipment will comprise the BOP system:


1. Upper Kelly cock Valve with handle
2. Stab-in TIW valve for all drillstrings in use

BLOWOUT PREVENTER ARRANGEMENT & PROGRAM

For Drilling to Intermediate Casing Point & Setting 7" Intermediate Casing



1. Rotating Head
- 2A. Fill-up Line & valve
- 2B. Flowline
3. Spacer Spool
4. Double Ram BOP (11", 3000 psi)
5. Pipe Rams
6. Blind Rams
7. Kill Line
8. Kill Line Check Valve
9. Kill Line Valve
10. Inner Choke Line Valve (3")
11. Outer Choke Line Valve (3")
12. Choke Line (3")
13. Variable Choke
14. Choke Line Valve (2")
15. Panic Line Valve (3")
16. Choke Manifold Pressure Gauge
17. Choke Line (2")
18. Mud Cross Spacer Spool
19. Casing Head "A" Section
20. Casing Head "A" Section 2" Valve
21. 9 5/8" Casing Collar



A 12-1/4" hole will be drilled to approximately 220' and the 9-5/8" surface casing will be run and cemented. The Casing Head 'A' Section will be screwed onto the 9-5/8" surface casing stub. The BOP will be installed on the Casing Head 'A' Section. A test plug will be set in the wellhead and the pipe rams and choke manifold will be tested to 200 psi to 300 psi (low pressure test) for 10 minutes and to 1000 psi (high pressure test) for 10 minutes. Then the test plug will be removed, and the 9-5/8" casing will be pressure tested against closed blind rams to 200 psi to 300 psi for 10 minutes and to 1000 psi for 30 minutes (this value is one 44% of the minimum internal yield pressure of the 9-5/8" casing). (Note: per regulatory requirements we will wait on cement at least 8 hrs after placement before testing the 9-5/8" surface casing). Then an 8-3/4" hole will be drilled to intermediate casing point and 7" intermediate casing will be run and cemented.

In addition to the equipment in the above diagram the following equipment will comprise the BOP system: