## UNITED STATES DEPARTMENT OF THE INTERIOR BUREAU OF LAND MANAGEMENT

	Sundry Notices and Reports on Wells			
		2006 SEP 13 PM 3 55	5.	Lease Number
1.	Type of Well GAS	RECEIVED 070 FARMINGTON NM	6.	NMSF-077092B If Indian, All. or Tribe Name
2.	Name of Operator	w 1915 .	7.	Unit Agreement Name
	CONOCOPHILLIPS		8.	Well Name & Number
3.	Address & Phone No. of Operator PO Box 4289, Farmington, NM 87499 (505) 326-9700	C SEP 2013	9.	Houck Com #1B API Well No.
_		TE STATE		30-045-30139
4.	Location of Well, Footage, Sec., T, R, M		10.	Field and Pool
	Unit O (SWSE), 875' FSL & 2205' FEL, Sec. 1, T29N,	R10W, NMPM	Blan	co MV / Aztec PC
			11.	County and State San Juan Co., NM
13.	X Subsequent Report Plugging Casing Repair	Non-Routine Fracturing Water Shut off Conversion to Injection		
6/27 (500 Mas BJ.	X_Subsequent ReportPluggingCasing RepairVFinal AbandonmentAltering CasingO  Describe Proposed or Completed Operations  7/06 MIRU Key #30. ND WH, Installed BPV, NU BOP. PT-OK Ogal). TIH w/mill & milled on scale. TOH w/mill. TIH w/CBP son 6/29/06 to squeeze. 6/30/06 Pumped 500 sx Type III cement. WOC. 7/5/06 RIH w/3-7/8" bit & D/O EZSV packer & cement.	Non-Routine Fracturing Water Shut off Conversion to Injection  TOH w/tbg. Made a scraper run. Ha & set @ 4200'. PU EZSV packer & se, sting out w/1700 psi below retainer. R D/O below bottom perf & testing at e	et @ 38 eversed very otl	40'. Rec'd verbal from Steve 15 bbls out tbg. & TOH. RD ner jt. Circ. clean w/bit @
6/27 (500 Mas BJ. 414 Blu- 7/11 w/3	Z Subsequent Report Plugging Casing Repair Altering Casing Repair Altering Casing Casing Repair Altering Casing Proposed or Completed Operations  7/06 MIRU Key #30. ND WH, Installed BPV, NU BOP. PT-OK Ogal). TIH w/mill & milled on scale. TOH w/mill. TIH w/CBP son 6/29/06 to squeeze. 6/30/06 Pumped 500 sx Type III cement. WOC. 7/5/06 RIH w/3-7/8" bit & D/O EZSV packer & cement. 9'. 7/6/06 PT P&A squeeze of Cliffhouose & Menefee to 500#/4 e Jet & set 4-1/2" CPlug @ 2440'. PT – 2300# / good test. RD M. 1/06 Spot WL equip. Perf'd PC zone @ 1 spf .34" holes – 2282'. 83 bbls 70 Q 20# Linear gel w/85,172# 20/40 Brady sand w/440,	Non-Routine Fracturing Water Shut off Conversion to Injection  TOH w/tbg. Made a scraper run. Ha & set @ 4200'. PU EZSV packer & se sting out w/1700 psi below retainer. R D/O below bottom perf & testing at e 0 min. good test. TOH. RIH w/bit & s MO WL. ND BOP, NU frac valve. 7/7/6  2305 = 24 holes and 2330' – 2353 = 024 scf N2. Flowed back to CO. 8/28/	et @ 38 eversed very oth craper. 06 Load 24 hole /06 MII	40'. Rec'd verbal from Steve 15 bbls out tbg. & TOH. RD ner jt. Circ. clean w/bit @ Circ. hole. TOH. MIRU I casing to wait for frac.  s. 48 total holes. Frac'd PC RU Key #15. Kill well. ND
6/27 (500 Mas BJ. 414 Blu 7/11 w/3 frac to P	Z Subsequent Report Plugging Casing Repair Altering Casing Repair Altering Casing Casing Repair Altering Casing Proposed or Completed Operations  7/06 MIRU Key #30. ND WH, Installed BPV, NU BOP. PT-OK 0 gal). TIH w/mill & milled on scale. TOH w/mill. TIH w/CBP son 6/29/06 to squeeze. 6/30/06 Pumped 500 sx Type III cement. WOC. 7/5/06 RIH w/3-7/8" bit & D/O EZSV packer & cement. 9'. 7/6/06 PT P&A squeeze of Cliffhouose & Menefee to 500#/4 e Jet & set 4-1/2" CPlug @ 2440'. PT – 2300# / good test. RD M. 1/06 Spot WL equip. Perf'd PC zone @ 1 spf .34" holes – 2282'	Non-Routine Fracturing Water Shut off Conversion to Injection  TOH w/tbg. Made a scraper run. Ha & set @ 4200'. PU EZSV packer & so sting out w/1700 psi below retainer. R D/O below bottom perf & testing at e 0 min. good test. TOH. RIH w/bit & s MO WL. ND BOP, NU frac valve. 7/7/6  2305 = 24 holes and 2330' - 2353 = 024 scf N2. Flowed back to CO. 8/28. @ 2440'. Flow well to C/O fill to CIBI	et @ 38 eversed very oth craper. 06 Load 24 hole /06 MII 2 @ 420	40'. Rec'd verbal from Steve 15 bbls out tbg. & TOH. RD ner jt. Circ. clean w/bit @ Circ. hole. TOH. MIRU d casing to wait for frac.  s. 48 total holes. Frac'd PC RU Key #15. Kill well. ND 00'. D/O CIBP. Circ. Hole
6/27 (500 Mas BJ. 414 Blu- 7/11 w/3 frac to P	Z Subsequent Report Casing Repair Casing Repair Altering Casing Repair Altering Casing Proposed or Completed Operations  7/06 MIRU Key #30. ND WH, Installed BPV, NU BOP. PT-OK Ogal). TIH w/mill & milled on scale. TOH w/mill. TIH w/CBP son 6/29/06 to squeeze. 6/30/06 Pumped 500 sx Type III cement. WOC. 7/5/06 RIH w/3-7/8" bit & D/O EZSV packer & cement. 9'. 7/6/06 PT P&A squeeze of Cliffhouose & Menefee to 500#/4 e Jet & set 4-1/2" CPlug @ 2440'. PT – 2300# / good test. RD M. 1/06 Spot WL equip. Perf'd PC zone @ 1 spf .34" holes – 2282'. 83 bbls 70 Q 20# Linear gel w/85,172# 20/40 Brady sand w/440, e equip. NU BOP. PT-OK. RIH w/mill & MO fill & D/O CIBP (PBTD 5099'). RIH w/145 jts2-3/8" 4.7# J-55 EUE tbg and set @	Non-Routine Fracturing Water Shut off Conversion to Injection  TOH w/tbg. Made a scraper run. Ha & set @ 4200'. PU EZSV packer & se sting out w/1700 psi below retainer. R D/O below bottom perf & testing at e 0 min. good test. TOH. RIH w/bit & s MO WL. ND BOP, NU frac valve. 7/7/6  2305 = 24 holes and 2330' - 2353 = 024 scf N2. Flowed back to CO. 8/28. @ 2440'. Flow well to C/O fill to CIBI 4607' w/FN @ 4606'. ND BOP, NU N	et @ 38 eversed very oth craper. 06 Load 24 hole /06 MII 2 @ 420	40'. Rec'd verbal from Steve 15 bbls out tbg. & TOH. RD ner jt. Circ. clean w/bit @ Circ. hole. TOH. MIRU d casing to wait for frac.  s. 48 total holes. Frac'd PC RU Key #15. Kill well. ND 00'. D/O CIBP. Circ. Hole
6/27 (500 Mas BJ. 414 Blu- 7/11 w/3 frac to P	Z Subsequent Report Casing Repair Altering Casing Repair Altering Casing Prinal Abandonment Prinal Altering Casing Prinal Abandonment Prinal Altering Casing Repair Prinal Altering Casing Repair Prinal Altering Casing Repair Prinal Altering Casing Prinal Alterin	Non-Routine Fracturing Water Shut off Conversion to Injection  TOH w/tbg. Made a scraper run. Ha & set @ 4200'. PU EZSV packer & se, sting out w/1700 psi below retainer. R D/O below bottom perf & testing at e 00 min. good test. TOH. RIH w/bit & s MO WL. ND BOP, NU frac valve. 7/7/6  2305 = 24 holes and 2330' - 2353 = 024 scf N2. Flowed back to CO. 8/28. @ 2440'. Flow well to C/O fill to CIBI 4607' w/FN @ 4606'. ND BOP, NU V	et @ 38 eversec very off craper. 06 Load 24 hole /06 MII P @ 420 WH. Ro	40'. Rec'd verbal from Steve 15 bbls out tbg. & TOH. RD ner jt. Circ. clean w/bit @ Circ. hole. TOH. MIRU 1 casing to wait for frac.  s. 48 total holes. Frac'd PC RU Key #15. Kill well. ND 00'. D/O CIBP. Circ. Hole emoved BPV. RD& released
6/27 (500 Mass BJ. 4144 Bluu 7/111 w/3 frace to P rig ! This 14.	Z Subsequent Report Casing Repair Altering Casing Repair Altering Casing Prinal Abandonment Prinal Abandonm	Non-Routine Fracturing Water Shut off Conversion to Injection  TOH w/tbg. Made a scraper run. Ha & set @ 4200'. PU EZSV packer & se, sting out w/1700 psi below retainer. R D/O below bottom perf & testing at e 00 min. good test. TOH. RIH w/bit & s MO WL. ND BOP, NU frac valve. 7/7/6  2305 = 24 holes and 2330' - 2353 = 024 scf N2. Flowed back to CO. 8/28. @ 2440'. Flow well to C/O fill to CIBI 4607' w/FN @ 4606'. ND BOP, NU V	et @ 38 eversec very off craper. 06 Load 24 hole /06 MII P @ 420 WH. Ro	40'. Rec'd verbal from Steve 15 bbls out tbg. & TOH. RD ner jt. Circ. clean w/bit @ Circ. hole. TOH. MIRU 1 casing to wait for frac.  s. 48 total holes. Frac'd PC RU Key #15. Kill well. ND 00'. D/O CIBP. Circ. Hole emoved BPV. RD& released  st Date 9/13/06  ACCEPTED FOR REC
6/27 (500 Mass BJ. 414 Blu 7/11 w/3 fract to P rig 9 This 14. Sig CTh AP CO Title	Z Subsequent Report Casing Repair Altering Casing Repair Altering Casing Prinal Abandonment Prinal Altering Casing Prinal Abandonment Prinal Altering Casing Repair Prinal Altering Casing Repair Prinal Altering Casing Prinal Al	Non-Routine Fracturing Water Shut off Conversion to Injection  TOH w/tbg. Made a scraper run. Ha & set @ 4200'. PU EZSV packer & se sting out w/1700 psi below retainer. R D/O below bottom perf & testing at e 0 min. good test. TOH. RIH w/bit & s MO WL. ND BOP, NU frac valve. 7/7/6  2305 = 24 holes and 2330' - 2353 = 024 scf N2. Flowed back to CO. 8/28 @ 2440'. Flow well to C/O fill to CIBI 4607' w/FN @ 4606'. ND BOP, NU V 48AZ.  Title Sr. Regulatory S  partment or agency of	et @ 38 eversec very off craper. 06 Load 24 hole /06 MII P @ 420 WH. Ro	40'. Rec'd verbal from Steve 15 bbls out tbg. & TOH. RD her jt. Circ. clean w/bit @ Circ. hole. TOH. MIRU 1 casing to wait for frac.  s. 48 total holes. Frac'd PC RU Key #15. Kill well. ND 00'. D/O CIBP. Circ. Hole emoved BPV. RD& released  st Date