

submitted in lieu of Form 3160-5

UNITED STATES
DEPARTMENT OF THE INTERIOR
BUREAU OF LAND MANAGEMENT

Sundry Notices and Reports on Wells

2006 SEP 22 PM 2 19 5

1. Type of Well

GAS

RECEIVED
070 FARMINGTON NM

6. Lease Number
NMSF- 079403
If Indian, All. or
Tribe Name

2. Name of Operator

BURLINGTON

RESOURCES OIL & GAS COMPANY LP

7. Unit Agreement Name

San Juan 27-5 Unit

3. Address & Phone No. of Operator

PO Box 4289, Farmington, NM 87499 (505) 326-9700

8. Well Name & Number

San Juan 27-5 Unit #118M
API Well No.

4. Location of Well, Footage, Sec., T, R, M

Unit O (SWSE), 1295' FSL & 2045' FEL, Section 22, T27N, R5W, NMPM

30-039-29756

10. Field and Pool

Basin Dakota/Blanco Mesa Verde

11. County and State
Rio Arriba Co., NM

12. CHECK APPROPRIATE BOX TO INDICATE NATURE OF NOTICE, REPORT, OTHER DATA

Type of Submission

Type of Action

☐ Notice of Intent

☐ Abandonment

☐ Change of Plans

☒ Other - casing report

☒ Subsequent Report

☐ Recompletion

☐ New Construction

☐ Plugging

☐ Non-Routine Fracturing

☐ Casing Repair

☐ Water Shut off

☐ Final Abandonment

☐ Altering Casing

☐ Conversion to Injection

13. Describe Proposed or Completed Operations

09/9/06 NU BOP. RIH w/83/4" bit & tagged cement @ 175'. D/O cement & then ahead to 3526' (intermed.). Circ hole. RIH w/81jts 7" 20# J-55 St& C casing set @ 3526'. Set DV tool @ 2783'. RU to cement Pumped pre-flush of 10 bbls FW/10 bbls Mudflush/10 bbls FW. 1st Stage- pumped Scavenger 19 sx(57 cf - 10 bbls) Type III Cement w/.05 #/sx D-29 Cellophane, .30% CD-32, 6.25#/sx LCM-1, 1% FL-52. Tail- pumped 117 sx(162 cf - 29 bbls) Premium Lite Type II Cement w/.25 #/sx Cello-flake, .30% CD-32, 6.25 #/sx LCM-1, & 1 % FL-52. Bumped plug w/ 1500 # @ 1608 hrs on 9/13/06. Opened DV tool & circ. between stages. Circ. 15bbls of cement to pit. 2nd Stage- pumped pre-flush of 10 bbls FW/10 bbls Mudflush/10 bbls FW. Lead- pumped Scavenger 19 sx(57 cf - 10 bbls) Type III cement w/.05 #/sx D-29 Cellophane, .30% CD-32, 6.25 #/sx LCM-1, & 1 % FL-52. Tail- pumped 360 sx(767 cf - 136 bbls) Premium Lite Type III Cement w/.25 gps Cello-flake, .30 % CD-32, .50 #/sx LCM-1, .40% FL-52. Bumped Plug w/ 2600# @ 1532hrs on 9/13/06. Circ. 45 bbls of cement to reserve pit. ND & install B sect.

9/14/06 RIH w/6 1/4" bit. PT casing to 1500 #- test good. D/O DV tool @ 2783'. D/O cement & ahead to 7750' (TD). TD reached 9/17/06. Circ. hole. RIH w/162 jts 4.5" 10.5# J-55 ST & C casing & 19 jts. 4.5" 11.60 # J-55 LT & C casing, set @ 7750'. RU to cement. Pumped pre-flush of 10 bbls chem. Wash/2 bbls H2O. Lead- pumped Scavenger 9sx(28 cf - 5 bbls) Class B Cement w/.25#/sx Cello-flake, .30% CD-32, 6.25 #/sx LCM-1, & 1% FL-52. Tail- pumped 299 sx(592cf - 105 bbls) Premium Lite HS FM ClassB Cement w/ .25 #/sx Cello-flake, .30% CD-32, 6.25 #/sx LCM-1, 1% FL-52. Bumped plug @ 0207 hrs 9/18/06. ND. RR @ 0815hrs on 9/18/06.

PT will be conducted by the completion rig. PT results & TOC will be shown on next report.

14. I hereby certify that the foregoing is true and correct.

Signed Tracey N. Monroe Tracey N. Monroe Title Regulatory Assistant Date 9/19/06

(This space for Federal or State Office use)

APPROVED BY _____ Title _____ Date _____

CONDITION OF APPROVAL, if any:

Title 18 U.S.C. Section 1001, makes it a crime for any person knowingly and willfully to make any department or agency of the United States any false, fictitious or fraudulent statements or representations as to any matter within its jurisdiction.

NMOCDB

ACCEPTED FOR RECORD

SEP 25 2006

FARMINGTON FIELD OFFICE
By Tracy C. Salvo