District 1 1625 N. French Dr., Hobbs, NM 88240 District II 1301 W. Grand Ave., Artesia, NM 88210 District III 1000 Rio Brazos Rd., Aztec, NM 87410 District IV 1220 S. St. Francis Dr., Santa Fe, NM 87505 SUNDRY NC (DO NOT USE THIS FORM FOR PRO DIFFERENT RESERVOIR. USE "APP PROPOSALS.) 1. Type of Well: Oil Well	Energy, Minera OIL CONSE 1220 Sor Santa OTICES AND REPORTS POSALS TO DRILL OR TO D PLICATION FOR PERMIT" (F	EEPEN OR PLUG BAC	SIOS r. 22	OIL CONS. DIV.		C-103 27, 2004 Name
2. Name of Operator					9. OGRID Number	
BP AMERICA PRODUCTION COMPANY 3. Address of Operator P.O. BOX 3092 HOUSTON, TX 77079-2064 4. Well Location					10. Pool name or Wildcat BLANCO MESAVERDE	
	1750 feet from the <u>\$6</u>	OUTH line and	2200	fee	et from the WEST line	
Section 25	Townsh					County
	11. Elevation (Show					
Pit or Below-grade Tank Application	or Closure					
Pit typeDepth to Groun	dwaterDistance from	nearest fresh water wel	·	Dista	nce from nearest surface water	
Pit Liner Thickness:	nil Below-Grade Tank:	Volume	bbls;	Сог	nstruction Material	
NOTICE OF PERFORM REMEDIAL WORK [TEMPORARILY ABANDON [Appropriate Box to INTENTION TO: ☐ PLUG AND ABAND ☐ CHANGE PLANS ☐ MULTIPLE COMPL	ON REM	SU EDIAL W	JBS ORK	SEQUENT REPORT OF: ALTERING CASI LING OPNS. P AND A	NG 🗆
OTHER:					quent Report	\boxtimes
	mpleted operations. (Clean	arly state all pertine	nt details,		give pertinent dates, including estimach wellbore diagram of proposed co	
of starting any proposed or recompletion.	work). SEE RULE 1103	. For Multiple Com	-		.	mpletion
of starting any proposed	work). SEE RULE 1103	. For Multiple Com	-		.	mpletion
of starting any proposed or recompletion.	work). SEE RULE 1103 SITE PLUG @ 5300'.	. For Multiple Com	r CASIN	IG I	ΓΟ 500 PSI TEST OK.	mpletion
of starting any proposed or recompletion. 09/14/06 TIH & SETCOMPO 09/21/06 TIH AND PERFOR. 09/25/06 FRAC. THE POINT	WORK). SEE RULE 1103 SITE PLUG @ 5300'. ATED THE POINT LO LOOKOUT DOWN COAM AND N2. RIG U	. For Multiple Com PRESSURE TEST DOKOUT FROM ASING @ 60 BBI P WIRELINE AN	- Γ CASIN 4,817 ' T -S. / MII D SET A	NG 1 10 4 N. U	ΓΟ 500 PSI TEST OK.	Rady
of starting any proposed or recompletion. 09/14/06 TIH & SETCOMPO 09/21/06 TIH AND PERFOR. 09/25/06 FRAC. THE POINT SAND IN 60 % QUALITY FO PERFORATED THE MENEF	work). SEE RULE 1103 SITE PLUG @ 5300'. ATED THE POINT LO LOOKOUT DOWN COAM AND N2. RIG UI EE FROM 4,534 ' TO	. For Multiple Com PRESSURE TEST DOKOUT FROM ASING @ 60 BBI P WIRELINE AN 4.668 ' WITH 4 JS @ 60 BBLS. / MI	CASIN 4,817 ' T S. / MII D SET A SPF. N. USIN	NG T O 4 N. U A CO	TO 500 PSI TEST OK. -,890 ' WITH 4 - JSPF. JSING 140,019 LBS. OF 16/30 B DMPOSITE BRIDGE PLUG @ 4	RADY ,750 '.
of starting any proposed or recompletion. 09/14/06 TIH & SETCOMPO 09/21/06 TIH AND PERFOR. 09/25/06 FRAC. THE POINT SAND IN 60 % QUALITY FO PERFORATED THE MENEF 09/26/06 FRAC. THE MENE	WORK). SEE RULE 1103 SITE PLUG @ 5300'. ATED THE POINT LO LOOKOUT DOWN C DAM AND N2. RIG UI EE FROM 4,534 ' TO FEE DOWN CASING AND N2. AND SCHI	. For Multiple Com PRESSURE TEST DOKOUT FROM ASING @ 60 BBI P WIRELINE AN 4.668 ' WITH 4 JS @ 60 BBLS. / MI LUMBERGER CL	CASIN 4,817 ' T S. / MII D SET A PF. N. USIN EAR FR	NG T O 4 N. U A CO	TO 500 PSI TEST OK. -,890 ' WITH 4 - JSPF. JSING 140,019 LBS. OF 16/30 B DMPOSITE BRIDGE PLUG @ 4	RADY ,750 '.
of starting any proposed or recompletion. 09/14/06 TIH & SETCOMPO 09/21/06 TIH AND PERFOR. 09/25/06 FRAC. THE POINT SAND IN 60 % QUALITY FO PERFORATED THE MENEF 09/26/06 FRAC. THE MENE AND 60 % QUALITY FOAM	WORK). SEE RULE 1103 SITE PLUG @ 5300'. ATED THE POINT LO LOOKOUT DOWN C DAM AND N2. RIG UI EE FROM 4,534 ' TO FEE DOWN CASING AND N2. AND SCHI	. For Multiple Com PRESSURE TEST DOKOUT FROM ASING @ 60 BBI P WIRELINE AN 4.668 ' WITH 4 JS @ 60 BBLS. / MI LUMBERGER CL	CASIN 4,817 ' T S. / MII D SET A PF. N. USIN EAR FR	NG T O 4 N. U A CO	TO 500 PSI TEST OK. -,890 ' WITH 4 - JSPF. JSING 140,019 LBS. OF 16/30 B DMPOSITE BRIDGE PLUG @ 4	RADY ,750 '.
of starting any proposed or recompletion. 09/14/06 TIH & SETCOMPO 09/21/06 TIH AND PERFOR. 09/25/06 FRAC. THE POINT SAND IN 60 % QUALITY FO PERFORATED THE MENEF 09/26/06 FRAC. THE MENE AND 60 % QUALITY FOAM 09/28/06 PRESSURE TEST B 10/03/06 RD MOL I hereby certify that the informatic	SITE PLUG @ 5300'. SITE PLUG @ 5300'. ATED THE POINT LOOKOUT DOWN COMM AND N2. RIG UND EE FROM 4,534 ' TO SEE DOWN CASING AND N2. AND SCHILLOP 1500# HIGH 250#	PRESSURE TEST DOKOUT FROM ASING @ 60 BBI P WIRELINE AN 4.668 ' WITH 4 JS @ 60 BBLS. / MI LUMBERGER CL LOW CHARTED	CASIN 4,817 'T S. / MII D SET A PF. N. USIN EAR FR	NG 1 N. U NG I RAC	TO 500 PSI TEST OK. -,890 ' WITH 4 - JSPF. JSING 140,019 LBS. OF 16/30 B DMPOSITE BRIDGE PLUG @ 4	RADY 750 '. SAND
of starting any proposed or recompletion. 09/14/06 TIH & SETCOMPO 09/21/06 TIH AND PERFOR. 09/25/06 FRAC. THE POINT SAND IN 60 % QUALITY FO PERFORATED THE MENEF 09/26/06 FRAC. THE MENE AND 60 % QUALITY FOAM 09/28/06 PRESSURE TEST B 10/03/06 RD MOL I hereby certify that the informatic	SITE PLUG @ 5300'. SITE PLUG @ 5300'. ATED THE POINT LOOKOUT DOWN COMM AND N2. RIG UND EE FROM 4,534 ' TO SEE DOWN CASING AND N2. AND SCHILLOP 1500# HIGH 250#	PRESSURE TEST DOKOUT FROM ASING @ 60 BBI P WIRELINE AN 4.668 ' WITH 4 JS @ 60 BBLS. / MI LUMBERGER CL LOW CHARTED Delete to the best of m	CASIN 4,817 'T S. / MII D SET A PF. N. USIN EAR FR	NG 1 N. U NA CO NG 1 RAC	TO 500 PSI TEST OK. .,890 ' WITH 4 - JSPF. JSING 140,019 LBS. OF 16/30 B DMPOSITE BRIDGE PLUG @ 4 31.000 LBS. OF 16/30 BRADY : and belief. 1 further certify that any pit or an (attached) alternative OCD-approved	RADY 750 '. SAND
of starting any proposed or recompletion. 09/14/06 TIH & SETCOMPO 09/21/06 TIH AND PERFOR. 09/25/06 FRAC. THE POINT SAND IN 60 % QUALITY FO PERFORATED THE MENEF 09/26/06 FRAC. THE MENE AND 60 % QUALITY FOAM 09/28/06 PRESSURE TEST B 10/03/06 RD MOL I hereby certify that the information of the proposed of the pr	SITE PLUG @ 5300'. ATED THE POINT LO LOOKOUT DOWN CO DAM AND N2. RIG UN EE FROM 4,534 ' TO FEE DOWN CASING AND N2. AND SCHIL OP 1500# HIGH 250#	PRESSURE TEST DOKOUT FROM ASING @ 60 BBI P WIRELINE AN 4.668 ' WITH 4 JS @ 60 BBLS. / MI LUMBERGER CL LOW CHARTED Delete to the best of m	CASIN 4,817 'T S. / MII D SET A PF. N. USIN EAR FR OO.K. Ty knowled the permit of the control o	NG 1 N. U NA CO NG 1 RAC	TO 500 PSI TEST OK. .,890 ' WITH 4 - JSPF. JSING 140,019 LBS. OF 16/30 B DMPOSITE BRIDGE PLUG @ 4 31.000 LBS. OF 16/30 BRADY : and belief. 1 further certify that any pit or an (attached) alternative OCD-approved	RADY 750 '. SAND
of starting any proposed or recompletion. 09/14/06 TIH & SETCOMPO 09/21/06 TIH AND PERFOR. 09/25/06 FRAC. THE POINT SAND IN 60 % QUALITY FO PERFORATED THE MENEF 09/26/06 FRAC. THE MENEF AND 60 % QUALITY FOAM 09/28/06 PRESSURE TEST B 10/03/06 RD MOL I hereby certify that the information of the properties of the	SITE PLUG @ 5300'. ATED THE POINT LO LOOKOUT DOWN CO DAM AND N2. RIG UN EE FROM 4,534 ' TO FEE DOWN CASING AND N2. AND SCHIL OP 1500# HIGH 250#	PRESSURE TEST DOKOUT FROM ASING @ 60 BBI P WIRELINE AN 4.668 ' WITH 4 JS @ 60 BBLS. / MI LUMBERGER CL LOW CHARTED Dete to the best of m CD guidelines, a genTITLERegula hurtk0@bp.com	CASIN 4,817 'T S. / MII D SET A PF. N. USIN EAR FR OO.K. The control of the cont	NG TO 4 N. U NG I RAC Light Declaration of the second	TO 500 PSI TEST OK. 2,890 ' WITH 4 - JSPF. JSING 140,019 LBS. OF 16/30 B DMPOSITE BRIDGE PLUG @ 4 131,000 LBS. OF 16/30 BRADY S and belief. I further certify that any pit or an (attached) alternative OCD-approved DATE10/20/06 TOP_DISI_	RADY 750 '. SAND