

submitted in lieu of Form 3160-5

UNITED STATES  
DEPARTMENT OF THE INTERIOR  
BUREAU OF LAND MANAGEMENT

RCVD NOV 7 06  
OIL CONS. DIV.

DIST. 3

Sundry Notices and Reports on Wells

2006 NOV 2 PM 4 52

1. Type of Well  
GAS

2. Name of Operator  
ConocoPhillips

3. Address & Phone No. of Operator

PO Box 4289, Farmington, NM 87499 (505) 326-9700

4. Location of Well, Footage, Sec., T, R, M

Unit K (NESW), 2200' FSL & 1955' FWL, Sec. 21, T31N, R8W, NMPM

5. Lease Number  
NM-013364
6. If Indian, All. or  
Tribe Name
7. Unit Agreement Name  
San Juan 32-8 Unit
8. Well Name & Number  
San Juan 32-8 Unit #12F
9. API Well No.  
30-045-33114
10. Field and Pool  
Blanco MV/ Basin DK
11. County and State  
San Juan Co., NM

12. CHECK APPROPRIATE BOX TO INDICATE NATURE OF NOTICE, REPORT, OTHER DATA

Type of Submission

☐ Notice of Intent

☒ Subsequent Report

☐ Final Abandonment

Type of Action

☐ Abandonment

☐ Recompletion

☐ Plugging

☐ Casing Repair

☐ Altering Casing

☐ Change of Plans

☐ New Construction

☐ Non-Routine Fracturing

☐ Water Shut off

☐ Conversion to Injection

☒ Other - Casing Report

13. Describe Proposed or Completed Operations

9/29/06 RIH w/ 8 3/4" bit & tag cement @ 185'. D/O cement & then formation to 3726'. Circ. hole. RIH w/ 87 jts, of 7", 20#, J-55 ST&C casing set @ 3716' w/ DV tool @ 2906'. 10/6/06 RU to cement. Stage 1 pumped preflush of 50 bbls gel. Tail w/ 250 sx (318 cf - 56 bbls) 50/50 G-POZ, 2% D-20, 5#sx D-24, 2% S1, .1% D-46, .15% D-65. Drop plug & displaced w/ 40 bbls FW. Opened DV tool & circ 100 bbls to surface. Stage 2 Pumped preflush of 20bbls gel. Lead w/ 405 sx (1057 cf - 188 bbls) Class G w/ 3% D-79, .2% D-46. Drop plug & displaced w/ 117 bbls of FW. Circ 117 bbls cement to surface. WOC. NU BOP. 10/7/06 PT casing, 1800 #/30min. OK.

10/8/06 RIH w/ 6 1/4" bit & D/O DV tool. D/O cement & then formation to 8040' (TD). TD reached 10/9/06. Circ. hole. RIH w/ 193 jts 4 1/2", 11.6#, N-80, LT&C casing set @ 8035'. 10/10/06 RU cement. Pumped preflush of 20 bbls gel water, 10 bbls L-64 pre-flush. Lead w/ 490 sx (686 cf - 123 bbls) 50/50 G-POZ, 3% D-20, .1% D-46, .25# sx D-29, .25% D-167, .15% D-65, .1% D-800, 3.5#/sx ps. Drop plug & displaced w/ 125 bbls FW. Bumped Plug w/ 2200#. ND. Install trash cap. RD & released rig @ 10/11/2006. Will show TOC & casing PT on the next report.

14. I hereby certify that the foregoing is true and correct.

Signed Kandis Roland Kandis Roland Title Regulatory Technician Date 10/31/06

(This space for Federal or State Office use)

APPROVED BY \_\_\_\_\_ Title \_\_\_\_\_ Date \_\_\_\_\_

CONDITION OF APPROVAL, if any:

Title 18 U.S.C. Section 1001, makes it a crime for any person knowingly and willfully to make any department or agency of the United States any false, fictitious or fraudulent statements or representations as to any matter within its jurisdiction.

NMOC

