submitted in lieu of Form 3160-5

UNITED STATES DEPARTMENT OF THE INTERIOR BUREAU OF LAND MANAGEMENT

RCVD NOV16'06 OIL CONS. DIV. DIST. 3

	Sundry Notices and Reports on Wells	Ž O		
1.	Type of Well GAS	2006 NOV 14 PM 4 RECEIVED OTO FARMINGTON	5.2 6. NM	Lease Number NMSF-079521-A If Indian, All. or Tribe Name
2.	Name of Operator		7.	Unit Agreement Name
3.	BURLINGTON RESOURCES OIL & GAS COMPANY LP		8.	San Juan 28-5 Unit Well Name & Number
	PO Box 4289, Farmington, NM 87499 (505) 326-9700		9.	San Juan 28-5 Unit #42N API Well No.
4.	Location of Well, Footage, Sec., T, R, M Sec., TN, RW, NMPM	·	10.	30-039-27705 Field and Pool
	Unit J (NWSE) 2310' FSL & 2350' FEL, Sec. 31, T28N R5W NMPM		Blanco Mesaverde/ Basin Dakota	
	Ulit J (14WSE) 2310 FSL & 2330 FEL, Sec. 31, 12614 R3	A MAINT M	11.	County and State Rio Arriba Co., NM
13.	X Subsequent Report Plugging Non-Re Casing Repair Water	onstruction outine Fracturing Shut off sion to Injection	******	
10/set sca w/3 stag sca Cel 30r 11/Cir cm cu-	31/06 RIH w/8 ¾" bit & tag cmt. D/O cmt & ahead to 3415'. Ci @3413' w/stage tool (DV) @2644'. 11/3/06 1 st Stage cmt: Prefivenger cmt w/ 3% CaCl2, .25pps Cell-o-Flake, 5pps LCM1, .4% GaCl2, .25pps Cell-o-Flake, 5pps LCM1, .4% FL52, .4% SM ges. Circulated 15bbls of cmt to surface. 2 nd Stage Preflush 10bb venger same additives as first stage. Tail in w/338xxs (720cu-12 l-o-flake, 5pps LMC1. Plug down @ 1422hrs. Circulated 25bbl nins, ok. 4/06 RIH 6 ¼" bit. Tagged DV tool & D/O. Unload hole. D/O F culated hole. 11/8/06 RIH w/4 ½" 18jts of 11.6# and 161jts 10.5t w/9sxs(28cu-5bbls)scavenger cmt w/3% CaCl2, .25pps Cell-o-105bbls)Prem lite w/3% CaCl2, .4% SMS, .4% FL52, 5pps LCN gased @ 1730hrs. Will show top of cmt & csg PT on next report	ush w/10bbls Gel H2O, 5bbls 6FL52, .4%SMS. Lead in w/1. IS. Plug down @ 0928hrs. Op ls H2O, 10bbls gel H2O, 10bbl 8bbls)prem lite cmt w/3% Cats of cmt to surface. ND Install loat collar drill ahead to TD 7 # J55 LT&C csg set @7640'. flake, 5pps LCM1, .4% SMS, M1, .25pps Cell-o-flake. Bump	H2O. 130sxs(1 en DV bls H2CC12, .49 "B" se 641'. T Preflus .4% Fl	Pump 17sxs(55cu-10bbls) 179cu-32bbls)Type 3 cmt tool and circulate between D. Pump 19sxs(56cu-10bbls) % SMS, .4% FL52, .25pps ection. PT csg to 1500psi for TD reached 11/7/06. sh w/10bbls H2O. Pumped L52. Followed w/299sxs(592 g w/1780psi. ND RD Rig
	ned two and a due to the foregoing is true and correct.	Amanda Sanchez Title Reg	ulatory	Tech Date <u>11/13/06</u>
AP	ris space for Federal or State Office use) PROVED BY			Date
Title	NDITION OF APPROVAL, IT any: 18 U.S.C. Section 1001, makes it a crime for any person knowingly and willfully to make any department inited States any false. fictitious or fraudulent statements or representations as to any matter within its jurisc			ACCEPTED FOR RECORD



NOV 1 5 2006