

**UNITED STATES
DEPARTMENT OF THE INTERIOR
BUREAU OF LAND MANAGEMENT**

RCVD NOV 14 06
OIL CONS. DIV.

DIST. 3

Sundry Notices and Reports on Wells

2006 NOV 6 12 4 56

1. Type of Well
GAS

2. Name of Operator

BURLINGTON

RESOURCES OIL & GAS COMPANY LP

3. Address & Phone No. of Operator

PO Box 4289, Farmington, NM 87499 (505) 326-9700

4. Location of Well, Footage, Sec., T, R, M
Sec., T--N, R--W, NMPM

Unit E (SWNW) 1755' FNL & 805' FWL, Sec. 9, T30N R8W NMPM

5. Lease Number
NMSF-078580

6. If Indian, All. or
Tribe Name

7. Unit Agreement Name

8. Well Name & Number

Woodriver #2B

9. API Well No.

30-045-33773

10. Field and Pool

Blanco MV/ Basin DK

11. County and State
San Juan Co., NM

12. CHECK APPROPRIATE BOX TO INDICATE NATURE OF NOTICE, REPORT, OTHER DATA

Type of Submission

☐ Notice of Intent

☒ Subsequent Report

☐ Final Abandonment

Type of Action

☐ Abandonment

☐ Recompletion

☐ Plugging

☐ Casing Repair

☐ Altering Casing

☐ Change of Plans

☐ New Construction

☐ Non-Routine Fracturing

☐ Water Shut off

☐ Conversion to Injection

☒ Other - 7"-4 1/2" Casing

13. Describe Proposed or Completed Operations

10/15/06 RIH w/8 3/4" bit & tagged cement @ 145'. D/O cement & ahead to 3362' Intermediate TD. Circulate hole. RIH w/ 76jts of 7" 20# J55 LT&C csg & set @ 3322', DV tool @ 2471'. Circulate hole. 10/19/06 1st stage: Pumped preflush w/20bbls gel spacer w/3#/sxcemnet. Pump 256sx(328cu-58bbl)50/50 POZ "G" w/1% CaCl₂, 2% Bentonite, 5#/sx gilsonite-extd'r, .15% Do65 dispersant, .1% D046 antifoam, 3#/bbls cement. Drop plug and displaced w/136bbls. Bumped plug w/665psi. Not returns. Called Jim Lovato 10/21/06 and gave verbal to proceed with the agreement that a log needed to be ran and needed to cal Jim back. 10/22/06 Called Jim back for status on logs. Logs were sent to Jim. Open DV tool. Circulated mud w/25% LCM. 2nd Stage: Pumped preflush w/15bbls gel spacer. Pumped 150sx(394cu-70bbls) Class "G" w/3% Do79 extrn'd, .20% Do46 antifoam, 1#/bbls cement. Drop plug and displace w/105bbls H₂O. Set plug w/2400psi. WOC. Plug down @ 1430hrs. NU BOP. PT csg to 1800psi for 30mins, ok.

CBL TOC 430 Per JTSY

10/21/06 RIH 6 1/4" bit and tagged cmt @ 2465'. D/O cmt, DV and ahead to TD 7691'. TD reached 10/24/06. Circulated hole. 10/25/06 RIH w/4 1/2" 20jts of 11.6# N80 LT&C and 160jts 10.5# J55 ST&C csg set @ 7691'. Preflush w/30bbls spacer. Pump 494sx(692cu-122bbls)50/50 G POZ. Drop plug and displace w/122bbls H₂O. Bump plug w/2100ps. TOC @ 1748'. WOC. ND BOPE. RD Rig released @ 2400hrs 10/25/06.

14. I hereby certify that the foregoing is true and correct.

Signed Amanda Sanchez Title Regulatory Tech Date 11/4/06

(This space for Federal or State Office use)

APPROVED BY _____

Title _____

Date 11/4/06 ACCEPTED FOR RECORD

CONDITION OF APPROVAL, if any:

Title 18 U.S.C. Section 1001, makes it a crime for any person knowingly and willfully to make any department or agency of the United States any false, fictitious or fraudulent statements or representations as to any matter within its jurisdiction.

NMOCB

