District I 1625 N. French Dr., Hobbs, NM 88240 District II 1301 W. Grand Avenue, Artesia, NM 88210 District III 1000 Rio Brazos Road, Aztec, NM 87410 District IV 1220 S. St. Francis Dr., Santa Fe, NM 87505

## State of New Mexico Energy Minerals and Natural Resources

Oil Conservation Division 1220 South St. Francis Dr. Santa Fe, NM 87505

For drilling and production facilities, submit to appropriate NMOCD District Office. For downstream facilities, submit to Santa Fe

Form C-144

June 1 2004

## Pit or Below-Grade Tank Registration or Closure

Is pit or below-grade tank covered by a "general plan"? Yes 🔀 No 🗌
Type of action: Registration of a pit or below-grade tank 🔲 Closure of a pit or below-grade tank 🔀 Telephone: (505)326-9200 e-mail address: Operator: BP America Production Company Address: 200 Energy Ct, Farmington, NM 87401 API#: 30045 23949 U/L or Qtr/Qtr M Sec 35 TZ8 N R8 W Facility or well name: STOREY D # 3 Longitude NAD: 1927 🗍 1983 🔀 County: San Juan Surface Owner: Federal State Private Indian Below-grade tank Pit Volume: \_\_\_\_bbl Type of fluid: \_\_\_\_\_ Type: Drilling Production X Disposal Workover Emergency Construction material: Double-walled, with leak detection? Yes If not, explain why not. Lined | Unlined | Liner type: Synthetic Thickness mil Clay Pit Volume \_\_bbl Less than 50 feet (20 points) Depth to ground water (vertical distance from bottom of pit to seasonal 50 feet or more, but less than 100 feet (10 points) high water elevation of ground water.) 100 feet or more ( 0 points) Yes (20 points) Wellhead protection area: (Less than 200 feet from a private domestic No ( 0 points) water source, or less than 1000 feet from all other water sources.) Less than 200 feet (20 points) Distance to surface water: (horizontal distance to all wetlands, playas, 200 feet or more, but less than 1000 feet (10 points) tion canals, ditches, and perennial and ephemeral watercourses.) 1000 feet or more ( 0 points) Ranking Score (Total Points) If this is a pit closure: (1) Attach a diagram of the facility showing the pit's relationship to other equipment and tanks. (2) Indicate disposal location: (check the onsite box if your are burying in place) onsite offsite If offsite, name of facility . (3) Attach a general description of remedial action taken including remediation start date and end date. (4) Groundwater encountered: No 🗷 Yes 🔲 If yes, show depth below ground surface ft. and attach sample results. (5) Attach soil sample results and a diagram of sample locations and excavations. Additional Comments: See Attached Documentation I hereby certify that the information above is true and complete to the best of my knowledge and belief. I further certify that the above-described pit or below-grade tank has been/will be constructed or closed according to NMOCD guidelines X, a general permit , or an (attached) alternative OCD-approved plan . Date: 11/01/2005 Printed Name/Title Jeffrey C. Blagg, Agent Your certification and NMOCD approval of this application/closure does not relieve the operator of liability should the contents of the pit or tank contaminate ground water or otherwise endanger public health or the environment. Nor does it relieve the operator of its responsibility for compliance with any other federal, state, or local laws and/or regulations. PEPUTY OIL & GAS INSPECTOR, DIST. 43 Signature Brandon Towell Date: NOV 3 0 2006 Printed Name/Title

3004523947 LOCATION NO: BOJ33 BLAGG ENGINEERING, INC. BP CLIENT: \_ P.O. BOX 87. BLOOMFIELD, NM 87413 C.D.C. ND: 9727 (505) 632-1199FIELD REPORT: CLOSURE VERIFICATION PAGE No: PIT: BLOW DATE STARTED: \_2/21/02 LOCATION: NAME: STOREY WELL #: 3 DATE FINISHED QUAD/UNIT: M SEC: 35 TWP: 282 RNG: 8W PM: 200 CNTY: 5J ST: CM ENVIRONMENTAL QTR/F00TAGE: 1180'S 390W SWISH CONTRACTOR: LAL OIL AEW SERVICES SPECIALIST: EXCAVATION APPROX. NA FT. x NA FT. x NA FT. DEEP. CUBIC YARDAGE: DISPOSAL FACILITY: OP-SITE \_ REMEDIATION METHOD: CLOSE AS IS LAND USE: KANGE - BLM SF 078566 LEASE: FORMATION: FIELD NOTES & REMARKS: PIT LOCATED APPROXIMATELY 155 FT. N40W FROM WELLHEAD. DEPTH TO GROUNDWATER: >100' NEAREST WATER SOURCE: >1000' NEAREST SURFACE WATER: >1000' NMOCD TPH CLOSURE STD: 5000 PPM NMOCD RANKING SCORE: OVM CALIB. READ. 53-2 ppm PIT ABANDONED SOIL AND EXCAVATION DVM CALIB. GAS = 100 ppm RF = 0.52\_\_\_\_ STEEL TANK INSTALLED **DESCRIPTION:** TIME: 9:00 am pm DATE: 2/21/02 \_\_ FIBERGLASS TANK INSTALLED SOIL TYPE: SAND / SILTY SAND / SILTY CLAD / CLAY / GRAVEL / OTHER REPORK (SANDSTOPE) SOIL COLOR: LT. GRAY TO BLACK BEORDER - IT. GRAY COHESION (ALL OTHERS): NON COHESIVE / SLIGHTLY COHESIVE / COHESIVE / HIGHLY COHESIVE CONSISTENCY (NON COHESTVE SOILS): LODSE / FIRM / DENSE / VERY DENSE PLASTICITY (CLAYS): NON PLASTIC / SLIGHTLY PLASTIC / COHESIVE / MEDIUM PLASTIC / HIGHLY PLASTIC DENSITY (COHESIVE CLAYS & SILTS): SDFT / FIRM / STIFF / VERY STIFF / HARD COOSED MOISTURE: DRY / SLIGHTLY MOIST / MOIST / WET / SATURATED / SUPER SATURATED DISCOLORATION/STAINING OBSERVED VED / NO EXPLANATION - DISCOLORED TOIL MENTIONED ABOVE HC ODOR DETECTED! (ES / NO EXPLANATION - WITHIN TEST HOLE & OWN SAMPLE TYPE: (GRAB) / COMPOSITE - # OF PTS. -ADDITIONAL COMMENTS: BEDROCK ROTTOM FIELD 418.1 CALCULATIONS SCALE SAMP, TIME SAMPLE I.D. WEIGHT (g) ml. FREON DILUTION READING CALC. Dom LAB No: FT 0 PERIMETER PROFILE OVM RESULTS 22 FIELD HEADSPACE PID (ppm) SAMPLE e 6 250 0 16 3 @ NOT APPLICABLE P. D . T.H

APPROX.4 APPROX.2 B.6. B.6.

LAB SAMPLES SAMPLE ANALYSIS TPH(8015B) 1300 81EX (80218) BOTH PROSED

P.D. = PIT DEPRESSION; B.G. = BELOW GRADE T.H. = TEST HOLE

TRAVEL NOTES:

2/21/02 - MORN · ONSITE: CALLOUT:

2/21/02 - AFTER .



## **EPA METHOD 8015 Modified Nonhalogenated Volatile Organics Total Petroleum Hydrocarbons**

Client:	Blagg / BP	Project #:	94034-010
Sample ID:	1 @ 6'	Date Reported:	02-25-02
Laboratory Number:	22078	Date Sampled:	02-21-02
Chain of Custody No:	9727	Date Received:	02-22-02
Sample Matrix:	Soil	Date Extracted:	02-22-02
Preservative:	Cool	Date Analyzed:	02-25-02
Condition:	Cool and Intact	Analysis Requested:	8015 TPH

Parameter	Concentration (mg/Kg)	Limit (mg/Kg)
Gasoline Range (C5 - C10)	296	0.2
Diesel Range (C10 - C28)	1,970	0.1
Total Petroleum Hydrocarbons	2,270	0.2

ND - Parameter not detected at the stated detection limit.

References:

Method 8015B, Nonhalogenated Volatile Organics, Test Methods for Evaluating Solid Waste,

SW-846, USEPA, December 1996.

Comments:

Storey D #3 Blow Pit Grab Sample.



## EPA METHOD 8021 AROMATIC VOLATILE ORGANICS

Client:	Blagg / BP	Project #:	94034-010
Sample ID:	1 @ 6'	Date Reported:	02-25-02
Laboratory Number:	22078	Date Sampled:	02-21-02
Chain of Custody:	9727	Date Received:	02-22-02
Sample Matrix:	Soil	Date Analyzed:	02-25-02
Preservative:	Cool	Date Extracted:	02-22-02
Condition:	Cool & Intact	Analysis Requested:	BTEX

Parameter	Concentration (ug/Kg)	Det. Limit (ug/Kg)	
Benzene	51.1	1.8	
Toluene	318	1.7	
Ethylbenzene	81.4	1.5	
p,m-Xylene	683	2.2	
o-Xylene	244	1.0	
Total BTEX	1.380		

ND - Parameter not detected at the stated detection limit.

Surrogate Recoveries:	Parameter	Percent Recovery
	Fluorobenzene	95 %
	1,4-difluorobenzene	95 %
	Bromochlorobenzene	95 %

References:

Method 5030B, Purge-and-Trap, Test Methods for Evaluating Solid Waste, SW-846, USEPA,

December 1996.

Method 8021B, Aromatic Volatile Organics, Test Methods for Evaluating Solid Waste, SW-846,

USEPA, December 1996.

Comments:

Storey D #3 Blow Pit Grab Sample.

Analyst Column

Review Wolten