<u>District I</u> 1625 N. French Dr., Hobbs, NM 88240 District II 1301 W. Grand Avenue, Artesia, NM 88210 District III 1000 Rio Brazos Road, Aztec, NM 87410 District IV 1220 S. St. Francis Dr., Santa Fe, NM 87505

## State of New Mexico Energy Minerals and Natural Resources

Oil Conservation Division 1220 South St. Francis Dr. Santa Fe, NM 87505

For drilling and production facilities, submit to appropriate NMOCD District Office.
For downstream facilities, submit to Santa Fe

Form C-144

June 1, 2004

office

## Pit or Below-Grade Tank Registration or Closure Is pit or below-grade tank covered by a "general plan"? Yes 🔀 No 🗌

Type of action: Registration of a pit of	or below-grade tank 🔲 Closure of a pit or below-grade	ade tank 🔀
C. DD A veries Deduction Comments	(505)22( 0200 mail address	LOIL CONS.
Operator: BP America Production Company Telephor	ie: (303)326-9200 e-maii address:	
Address: 200 Energy Ct, Farmington, NM 87401  Facility or well name: TRIGG FEDERAL GC & # ( API #: 3	2004576364 HI - 0-10- T	C 129 1 1 2 2 2 2 2 2 2 2 2 2 2 2 2 2 2 2
•		
	Longitude	NAD. 1927   1983
Surface Owner: Federal 🔀 State 🗌 Private 🔲 Indian 🗌		
Pit	Below-grade tank	
Type: Drilling Production Disposal	Volume:bbl Type of fluid:	
Workover	Construction material:	
Lined Unlined U	Double-walled, with leak detection? Yes  If no	or, explain why not.
Liner type: Synthetic Thickness mil Clay C		
Pit Volumebbl	Landa 60 Co.	(20
Depth to ground water (vertical distance from bottom of pit to seasonal	Less than 50 feet	(20 points)
high water elevation of ground water.)	50 feet or more, but less than 100 feet	(10 points)
	100 feet or more	( 0 points)
Wellhead protection area: (Less than 200 feet from a private domestic	Yes	(20 points)
water source, or less than 1000 feet from all other water sources.)	No	( 0 points)
Division of the control of the contr	Less than 200 feet	(20 points)
Distance to surface water: (horizontal distance to all wetlands, playas,	200 feet or more, but less than 1000 feet	(10 points)
tion canals, ditches, and perennial and ephemeral watercourses.)	1000 feet or more	( 0 points)
	Ranking Score (Total Points)	0
If this is a pit closure: (1) Attach a diagram of the facility showing the pit'	s solutionship to other popularism and toulin (2) India	nata disposal logation. (shook the engine has if
your are burying in place) onsite of offsite If offsite, name of facility_	• • • • • • • • • • • • • • • • • • • •	·
remediation start date and end date. (4) Groundwater encountered: No		
(5) Attach soil sample results and a diagram of sample locations and excava	, ,	tt. and attach sample results.
	tions.	
Additional Comments:		
See Attached Documentation		
I hereby certify that the information above is true and complete to the best	of my knowledge and belief. I further certify that	the above-described pit or below-grade tank
has been/will be constructed or closed according to NMOCD guideline	es 🔀, a general permit 🔲, or an (attached) alterna	ative OCD-approved plan .
11/01/2005	4	
Date:	ure Jeffy C. Sligy	
Your certification and NMOCD approval of this application/closure does notherwise endanger public health or the environment. Nor does it relieve to regulations.	not relieve the operator of liability should the contents the operator of its responsibility for compliance with a	s of the pit or tank contaminate ground water or any other federal, state, or local laws and/or
Printed Name/Title	Signature Brandon Tough	Date: NOV 3 0 2006

3004526364 BP BLAGG ENGINEERING, INC. CLIENT: LOCATION NO BOASO P.O. BOX 87, BLOOMFIELD, NM 87413 C.O.C. NO: 97/8 (505) 632-1199FIELD REPORT: CLOSURE VERIFICATION PAGE No: / of / DATE STARTED: 2/13/0る LOCATION: NAME: TRIEG: FED. GE B WELL #: 1 PIT: BLOW DATE FINISHED: QUAD/UNIT: I SEC: 15 TWP: 29N RNG: 9W PM: NM CNTY: 5J ST: NM ENVIRONMENTAL NV OTR/FOOTAGE: 21055 875 E NEISE CONTRACTOR: FLINT SPECIALIST: EXCAVATION APPROX. NA FT. x NA FT. DEEP. CUBIC YARDAGE: NA DISPOSAL FACILITY: PREMEDIATION METHOD: CLOSE AS 15 LAND USE RANGE - BLM FORMATION: FIELD NOTES & REMARKS! PIT LOCATED APPROXIMATELY ZOI FT. NOSE FROM WELLHEAT! NMOCD TPH CLOSURE STD: 5000 PPM NMOCD RANKING SCORE( . CHECK DNE : DVM CALIB. READ. 50.8 ppm PIT ABANDONED SOIL AND EXCAVATION \_\_\_\_ STEEL TANK INSTALLED OVM CALIB. GAS = 100 ppm RF = 0.52 DESCRIPTION: \_ FIBERGLASS TANK INSTALLED TIME: 7:32 @MYPM DATE: 2/13/02 SOIL TYPE: (SAND) SILTY SAND / SILT / SILTY CLAY / CLAY / GRAVEL / OTHER BEOROCK (SANDSTONE) SOIL COLOR: OK. YELL. BROWN BEDROCK - VERY PALE ORANGE
COHESION (ALL OTHERS): (NON COHESIVE) / SLIGHTLY COHESIVE / COHESIVE / HIGHLY COHESIVE CONSISTENCY (NON COHESIVE SOILS): LOOSE / FIRM / DENSE / VERY DENSE <del>PLASTICITY (CLAYS</del>): NON PLASTIC / SLIGHTLY PLASTIC / COHESIVE / MEDIUM PLASTIC / HIGHLY PLASTIC DENSITY (COHESIVE CLAYS & SILTS): SOFT / FIRM / STIFF / VERY STIFF / HARD ( RISK ASSESSED MOISTURE: DRY / SLIGHTLY MOIST / (MOIST) / WET / SATURATED / SUPER SATURATED DISCOLORATION/STAINING OBSERVED (YES) / NO EXPLANATION - C BEORGE SUFFRE HC ODOR DETECTED: (ES / NO EXPLANATION - WITHIN TEST HOLE & OUM SAMPLE SAMPLE TYPE: GRAB / COMPOSITE - # OF PTS. -COLLECTED SOIL ABOUT BEDLOCK ADDITIONAL\_COMMENTS:\_ BEDROCK - VERY HARD -BEDROCK BOTTOM FIELD 418.1 CALCULATIONS SCALE WEIGHT (g) ml. FREON DILUTION READING CALC. ppm SAMP. TIME SAMPLE I.D. LAB No: FT 0 PIT PERIMETER \$ PROFILE OVM RESULTS FIELD HEADSPACE PID (ppm) SAMPLE ID e 4 463 20 3 @ gERM 4 @ 5 @

RESAMPLE
10
1 @ 4'
2 @
3 @
4 @
5 @
4 @
5 @

LAI
SAMPLE
10
Dey

BELOW P.D. BPROX. 2'
BELOW GRADE

P.D. = PIT DEPRESSION; B.G. = BELOW GRADE

NOT APPLICABLE

CALLOUT: zlizbz-AFTER ONSITE: z/13/02-morn.

revised: 08/17/01

T.H. = TEST HOLE TRAVEL NOTES:



## EPA METHOD 8015 Modified Nonhalogenated Volatile Organics Total Petroleum Hydrocarbons

Client:	Blagg / BP	Project #:	94034-010
Sample ID:	1 @ 4'	Date Reported:	02-14-02
Laboratory Number:	22034	Date Sampled:	02-13-02
Chain of Custody No:	9718	Date Received:	02-13-02
Sample Matrix:	Soil	Date Extracted:	02-14-02
Preservative:	Cool	Date Analyzed:	02-14-02
Condition:	Cool and Intact	Analysis Requested:	8015 TPH

Parameter	Concentration (mg/Kg)	Det. Limit (mg/Kg)
Gasoline Range (C5 - C10)	5,600	0.2
Diesel Range (C10 - C28)	447	0.1
Total Petroleum Hydrocarbons	6,050	0.2

ND - Parameter not detected at the stated detection limit.

References:

Method 8015B, Nonhalogenated Volatile Organics, Test Methods for Evaluating Solid Waste,

SW-846, USEPA, December 1996.

Comments:

Trigg Federal GC B #1 Blow Pit.

Analyst

(Review M. Claster



## EPA METHOD 8021 AROMATIC VOLATILE ORGANICS

Client:	Blagg / BP	Project #:	94034-010
Sample ID:	1 @ 4'	Date Reported:	02-14-02
Laboratory Number:	22034	Date Sampled:	02-13-02
Chain of Custody:	9718	Date Received:	02-13-02
Sample Matrix:	Soil	Date Analyzed:	02-14-02
Preservative:	Cool	Date Extracted:	02-14-02
Condition:	Cool & Intact	Analysis Requested:	BTEX

Parameter	Concentration (ug/Kg)	Det. Limit (ug/Kg)
Benzene	1,610	1.8
Toluene	790	1.7
Ethylbenzene	185	1.5
p,m-Xylene	1,630	2.2
o-Xylene	631	1.0
Total BTEX	4,850	

ND - Parameter not detected at the stated detection limit.

Surrogate Recoveries:	Parameter	Percent Recovery
	Fluorobenzene	96 %
	1,4-difluorobenzene	96 %
	Bromochlorobenzene	96 %

References:

Method 5030B, Purge-and-Trap, Test Methods for Evaluating Solid Waste, SW-846, USEPA,

December 1996.

Method 8021B, Aromatic Volatile Organics, Test Methods for Evaluating Solid Waste, SW-846,

USEPA, December 1996.

Comments:

Trigg Federal GC B #1 Blow Pit.

Analyst C. Oglice

Mister Multers
Review