District I 1625 N. French Dr., Hobbs, NM 88240 District II 1301 W. Grand Avenue, Artesia, NM 88210 District III 1000 Rio Brazos Road, Aztec, NM 87410 District IV 1220 S. St. Francis Dr., Santa Fe, NM 87505

State of New Mexico Energy Minerals and Natural Resources

Oil Conservation Division 1220 South St. Francis Dr. Santa Fe, NM 87505

June 1, 2004 For drilling and production facilities, submit to appropriate NMOCD District Office.

For downstream facilities, submit to Santa Fe

office

Form C-144

	de Tank Registration or Closu	
Is pit or below-grade tan	k covered by a "general plan"? Yes 🔀 Nor below-grade tank 🔲 Closure of a pit or below-gr	0 🔛
Operator: BP America Production Company Telephon Address: 200 Energy Ct, Farmington, NM 87401 Facility or well name: BARNES B # 3A API #: 34 County: San Juan Latitude	ne: <u>(505)326-9200</u> e-mail address:	Sec 27 T 32 NR // W
Surface Owner: Federal 🔀 State 🗌 Private 🔲 Indian 🗍	T	
Pit Type: Drilling Production Disposal Workover Emergency Lined Unlined Liner type: Synthetic Thicknessmil Clay Pit Volumebbl	Below-grade tank Volume:bbl Type of fluid: Construction material: Double-walled, with leak detection? Yes If n	of, explain why not.
Depth to ground water (vertical distance from bottom of pit to seasonal high water elevation of ground water.)	Less than 50 feet 50 feet or more, but less than 100 feet 100 feet or more	(20 points) (10 points) (0 points)
Wellhead protection area: (Less than 200 feet from a private domestic water source, or less than 1000 feet from all other water sources.)	Yes No	(20 points) (0 points)
Distance to surface water: (horizontal distance to all wetlands, playas, irrigation canals, ditches, and perennial and ephemeral watercourses.)	Less than 200 feet 200 feet or more, but less than 1000 feet 1000 feet or more	(20 points) (10 points) (0 points)
	Ranking Score (Total Points)	0
f this is a pit closure: (1) Attach a diagram of the facility showing the pit's your are burying in place) onsite do offsite let offsite, name of facility emediation start date and end date. (4) Groundwater encountered: No do it is sample results and a diagram of sample locations and excavate Additional Comments: See Attached Documentation	(3) Attach a general	description of remedial action taken including
I hereby certify that the information above is true and complete to the best has been/will be constructed or closed according to NMOCD guideline: Date:	s (X) , a general permit (), or an (attached) alternure ure ot relieve the operator of liability should the content	ative OCD-approved plan
Approval: Printed Name/Title PUTY OIL & GAS INSPECTOR, DIST. @	Signature Bolo boll	DEC 0 5 2006

The second secon							بالمستجد والمستحدات
CLIENT: BP			NEERING	*	LOC	ATION NO:	81150
CLIENT: ST	P.O. BOX	87, BLO (505) 632		, NM 874	l	CR NO:	10501
FIELD REPORT	: PIT CL	OSURE	VERIF	CATIC	N PAG	E No:	1 of _/
LOCATION: NAME: BARNE QUAD/UNIT: D SEC: 27						STARTED: FINISHED:	2/12/03
QTR/FOOTAGE: 960 N 110	1		RACTOR: HDI			ONMENTAL	NV
EXCAVATION APPROX							Z S
DISPOSAL FACILITY:	ON-517	ξ	REMEDIA	TION METH	OD:	LANDER	orm
LANDUSE: RANGE -	Bun	LEASE:	5F078	039	FORMAT	ION:	my
FIELD NOTES & REMAR			KIMATELY 8				_
DEPTH TO GROUNDWATER: >10			>1000		SURFACE WAT	ER: >1	000'
NMOCD RANKING SCORE:	NMOCD TPH	CLOSURE STD:	_ <u>5000</u> pi				
SOIL AND EXCAVATION	N DESCRIPT	TION:		OVM CALIB. OVM CALIB.	READ. = 5		RF = 0.52
				TIME: 10:5			2/12/03
SOIL TYPE: SAND / SILTY SAN SOIL COLOR: DK. YELL				ER <u> </u>	Ч		
COHESION (ALL OTHERS): NON CO	HESIVEY SLIGHTLY	COHESIVE / CO	HESIVE / HIGHLY				
CONSISTENCY (NON COHESIVE SO PLASTICITY (CLAYS): NON PLASTIC				/ HIGHLY PLAST	TC TO		
DENSITY (COHESIVE CLAYS & SILTS): SOFT / FIRM / ST	IFF / VERY STIFF	/ HARD			(2	rosed)
MOISTURE: DRY / SLIGHTLY MOIST DISCOLORATION/STAINING OBSERV				VEB ATION	(17 70	men con	<u> </u>
HC ODOR DETECTED: YES NO EX	PLANATION - WIT	HIN EXCAU	O + COTTA	ÚM SAMPI	E:	1,60, 94	· · /
SAMPLE TYPE: GRAB/ COMPOSITE ADDITIONAL COMMENTS:	-# OF PTS	MZING HAI	ND ANGER.	STEEL TAN	K TO BE	INSTALLER) 1270
	SOTAU						
		FIE	ELD 418.1 CALC	ULATIONS			
SCALE SAMP. TIM	IE SAMP. ID	LAB NO.	WEIGHT (g)	mL FREON	DILUTION	READING	CALC. (ppm)
DIT DEDIMET	ED ()	<u> </u>			DITE	ואסכוו	
PIT PERIMET		<u> </u>	∨M		PILE	ROFIL	E
10 prod		REA	DING	A			A ¹
TANK	_	SAMPLE ID	FIELD HEADSPACE (ppm)			, /	
		1@6.5′ 2@	994	-		6'	
16		3 @ 4 @		7 -			
	⇒	5@		4.5			}
16	70			- - -			
A	A WELL HEAD						
	<i>(, _ , _ , _ , _ , _ , _ , _ , _ , _ , _</i>						
		LAB S	AMPLES	-			
		SAMPLE A	NALYSIS TIME				
1			X (20518) 11				
DD - DF	OD 105 5 5 5 5 5 5 5 5 5 5 5 5 5 5 5 5 5 5	(BOTH	PASSED				
P.D. = PIT DEPRESSION; B.G. = BELOW T.H. = TEST HOLE; ~ = APPROX.; T.B. =						· · · · · · · · · · · · · · · · · · ·	
TRAVEL NOTES: CALLOUT: Z/12/03 - MORN. ONSITE: Z/12/03 - AFTER.							



EPA METHOD 8015 Modified Nonhalogenated Volatile Organics Total Petroleum Hydrocarbons

Client:	Blagg / BP	Project #:	94034-010
Sample ID:	1 @ 6.5'	Date Reported:	02-14-03
Laboratory Number:	24829	Date Sampled:	02-12-03
Chain of Custody No:	10501	Date Received:	02-13-03
Sample Matrix:	Soil	Date Extracted:	02-14-03
Preservative:	Cool	Date Analyzed:	02-14-03
Condition:	Cool and Intact	Analysis Requested:	8015 TPH

Parameter	Concentration (mg/Kg)	Det. Limit (mg/Kg)
Gasoline Range (C5 - C10)	1,900	0.2
Diesel Range (C10 - C28)	210	0.1
Total Petroleum Hydrocarbons	2,110	0.2

ND - Parameter not detected at the stated detection limit.

References:

Method 8015B, Nonhalogenated Volatile Organics, Test Methods for Evaluating Solid Waste,

SW-846, USEPA, December 1996.

Comments:

Barnes B #3A Production Tank Pit Grab Sample.

Analyst C. Oyluna

Review



EPA METHOD 8021 AROMATIC VOLATILE ORGANICS

Client:	Blagg / BP	Project #:	94034-010
Sample ID:	1 @ 6.5'	Date Reported:	02-14-03
Laboratory Number:	24829	Date Sampled:	02-12-03
Chain of Custody:	10501	Date Received:	02-13-03
Sample Matrix:	Soil	Date Analyzed:	02-14-03
Preservative:	Cool	Date Extracted:	02-14-03
Condition:	Cool & Intact	Analysis Requested:	BTEX

Parameter	Concentration (ug/Kg)	Det. Limit (ug/Kg)	
Benzene	10.6	1.8	
Toluene	20.6	1.7	
Ethylbenzene	384	1.5	
p,m-Xylene	1,090	2.2	
o-Xylene	791	1.0	
Total BTEX	2,300		

ND - Parameter not detected at the stated detection limit.

Surrogate Recoveries:	Parameter	Percent Recovery
	Fluorobenzene	95 %
	1,4-difluorobenzene	95 %
	Bromochlorobenzene	95 %

References:

Method 5030B, Purge-and-Trap, Test Methods for Evaluating Solid Waste, SW-846, USEPA,

December 1996.

Method 8021B, Aromatic Volatile Organics, Test Methods for Evaluating Solid Waste, SW-846,

USEPA, December 1996.

Comments:

Barnes B #3A Production Tank Pit Grab Sample.

Review

Analyst