District | 1625 N. French Dr., Hobbs, NM 88240 District | 1 301 W. Grand Avenue, Artesia, NM 88210 District | 11 1000 Rio Brazos Road, Aztec, NM 87410 District IV 1220 S. St. Francis Dr., Santa Fe, NM 87505

State of New Mexico Energy Minerals and Natural Resources

Oil Conservation Division 1220 South St. Francis Dr. Santa Fe, NM 87505 For drilling and production facilities, submit to appropriate NMOCD District Office.
For downstream facilities, submit to Santa Fe office

PCUD DEC5'06 OIL CONS. DIV.

DIST. 3

Form C-144 June 1, 2004

Pit or Below-Grade Tank Registration or Closure

Is pit or below-grade tank covered by a "general plan"? Yes 🔀 No 🗌

Type of action: Registration of a pit or below-grade tank 🗋 Closure of a pit or below-grade tank 🔀

Operator: BP America Production Company Telephone	e: <u>(505)326-9200</u> e-mail address:	:
Address 200 Energy Ct. Farmington, NM 87401	- 112 - 27 - 211	
	0045 26214 U/Lor Qtr/Qtr L	
	Longitude	NAD: 1927 🗌 1983 🔀
Surface Owner: Federal 🗌 State 🗀 Private 🔀 Indian 🗋		
Pit	Below-grade tank	
Type: Drilling Production 🛛 Disposal 🗌	Volume:bbl Type of fluid:	·
Workover ☐ Emergency ☐	Construction material:	- 🗸
Lined Dunlined D	Double-walled, with leak detection? Yes 11 no	explain why not.
Liner type: Synthetic Thicknessmil Clay	//	
Pit Volumebbl	, , ,	\
Depth to ground water (vertical distance from bottom of pit to seasonal	Less than 50 feet	(20 points)
high water elevation of ground water.)	50 feet or more, but less than 100 feet	(10 points)
	100 feet or more	(0 points)
Wellhead protection area: (Less than 200 feet from a private domestic	Yes	(20 points)
water source, or less than 1000 feet from all other water sources.)	No	(0 points)
water source, or less than 1000 feet from an other water sources.)	1 2006	
Distance to surface water: (horizontal distance to all wetlands, playas,	Less than 200 feet	(20 points)
irrigation canals, ditches, and perennial and ephemeral watercourses.)	200 feet or more, but less than 1000 feet	(10 points)
	1000 feet or more	(0 points)
	Ranking Score (Total Points)	0
If this is a pit closure: (1) Attach a diagram of the facility showing the pit's your are burying in place) onsite offsite foffsite, name of facility remediation start date and end date. (4) Groundwater encountered: No	. (3) Attach a general	description of remedial action taken including
See Attached Documentation		
		·
I hereby certify that the information above is true and complete to the best has been/will be constructed or closed according to NMOCD guideline	of my knowledge and belief. I further certify that is A , a general permit ., or an (attached) altern	the above-described pit or below-grade tank ative OCD-approved plan .
Date: 11/01/2005	111 - 11	
Printed Name/Title <u>Jeffrey C. Blagg, Agent</u> Signat	ure Jeffy C. Slagg	·
Your certification and NMOCD approval of this application/closure does not otherwise endanger public health or the environment. Nor does it relieve to regulations.	not relieve the operator of liability should the content.	s of the pit or tank contaminate ground water or any other federal, state, or local laws and/or
Approval: Printed Name/Title CEPUTY OIL & GAS INSPECTOR, DIST.	Signature Bd Fell	DEC 0 5 2006

CLIENT:	<u>^</u>	P.O. BOX		NEERING OMFIELD 2-1199	-	I13	CATION NO:	1294 1294
FIELD RE	PORT:	PIT CL	OSURE	VERIF	CATIO	N PAG	SE No:	of <u> </u>
LOCATION: NAME QUAD/UNIT: L S QTR/FOOTAGE:/	SEC: T	NP: 29 N RNC	G: 12W PM:	NM CNTY:SJ	ST: MM	DAT	E STARTED: 9- E FINISHED: 9- IRONMENTAL CIALIST:	5-03 5-07
EXCAVATION A								2
DISPOSAL FACILIT	Y:	MA		REMEDIA		OD: FORMA	CLUSE AS	[5
FIELD NOTES &							✓ FROM WEL	LHEAD
DEPTH TO GROUNDWA	TER: >100						TER: >(00)	
NMOCD RANKING SCOI	RE:	_ NMOCD TPH	CLOSURE STD:	5000 PI	РМ			
SOIL AND EXC	CAVATION	DESCRIPT	ION:			GAS =	53.3 ppm <i>OO</i> ppm m DATE: <u>9</u> -4	RF = 0.52
SOIL TYPE: SAND	SILTY SAND	SILT / SILTY (CLAY / CLAY /	GRAVEL / OTH	ER <u>BED</u>	Ruck S	508'0	36
SOIL COLOR: COHESION (ALL OTHER CONSISTENCY (NON C	OHESIVE SOILS): LOOSE / FIRM	/ DENSE / VERY	DENSE		ıc		
DENSITY (COHESIVE C MOISTURE: DRY (SLIG DISCOLORATION/STAIN	PLASTICITY (CLAYS): NON PLASTIC / SLIGHTLY PLASTIC / COHESIVE / MEDIUM PLASTIC / HIGHLY PLASTIC DENSITY (COHESIVE CLAYS & SILTS): SOFT / FIRM / STIFF / VERY STIFF / HARD MOISTURE: DRY (SLIGHTLY MOIST) MOIST LWET / SATURATED / SUPER SATURATED DISCOLORATION/STAINING OBSERVED: YES IND EXPLANATION - MINOR 5 - 0 '							
HC ODOR DETECTED	COMPOSITE - #	OF PTS.			 			
BEDROCK BOTTOM								
			FII	ELD 418.1 CALC	ULATIONS			
SCALE 0 FT	SAMP. TIME	SAMP. ID	LAB NO.	WEIGHT (g)	mL FREON	DILUTIO	NREADING CA	LC. (ppm)
1,	RIMETE	D				PIT	PROFILE	
I Med	.KIIVIETE	PD /5'64	REA SAMPLE	ADING FIELD HEADSPACE			PROFILE	
12'		TANK FRINT PRINT	1 @ B 2 2 @ 3 @ 4 @ 5 @ 5	(ppm) //2_	2	T AF	PLKA BL	€
P.D. = PIT DEPRESSION; B T.H. = TEST HOLE; ~ = API TRAVEL NOTES:	G.G. = BELOW GF PROX.; T.B. = TA CALLOUT:	TO WELL	108 TP	AMPLES NALYSIS TIME VISTEY TUUS THE POSSED ONSITE:		07	50	
	OALLOUI			ONSITE:			<u> </u>	



EPA METHOD 8015 Modified Nonhalogenated Volatile Organics Total Petroleum Hydrocarbons

Client:	Blagg / BP	Project #:	94034-010
Sample ID:	Blow 1 @ 8'	Date Reported:	09-08-03
Laboratory Number:	26521	Date Sampled:	09-05-03
Chain of Custody No:	11295	Date Received:	09-05-03
Sample Matrix:	Soil	Date Extracted:	09-05-03
Preservative:	Cool	Date Analyzed:	09-08-03
Condition:	Cool and Intact	Analysis Requested:	8015 TPH

Parameter	Concentration (mg/Kg)	Det. Limit (mg/Kg)	
Gasoline Range (C5 - C10)	ND	0.2	
Diesel Range (C10 - C28)	ND	0.1	
Total Petroleum Hydrocarbons	ND	0.2	

ND - Parameter not detected at the stated detection limit.

References: Method 80

Method 8015B, Nonhalogenated Volatile Organics, Test Methods for Evaluating Solid Waste,

SW-846, USEPA, December 1996.

Comments: Allen A #1E.

Analyst C. Cy

/ Mistine m Waters
Review



EPA METHOD 8021 AROMATIC VOLATILE ORGANICS

Client:	Blagg / BP	Project #:	94034-010
Sample ID:	Blow 1 @ 8'	Date Reported:	09-08-03
Laboratory Number:	26521	Date Sampled:	09-05-03
Chain of Custody:	11295	Date Received:	09-05-03
Sample Matrix:	Soil	Date Analyzed:	09-08-03
Preservative:	Cool	Date Extracted:	09-05-03
Condition:	Cool & Intact	Analysis Requested:	BTEX

Parameter	Concentration (ug/Kg)	Det. Limit (ug/Kg)
Benzene	4.4	1.8
Toluene	12.4	1.7
Ethylbenzene	ND	1.5
p,m-Xylene	6.6	2.2
o-Xylene	15.5	1.0
Total BTEX	38.9	

ND - Parameter not detected at the stated detection limit.

Surrogate Recoveries:	Parameter	Percent Recovery
	Fluorobenzene	100 %
	1,4-difluorobenzene	100 %
	Bromochlorobenzene	100 %

References:

Method 5030B, Purge-and-Trap, Test Methods for Evaluating Solid Waste, SW-846, USEPA,

December 1996.

Method 8021B, Aromatic Volatile Organics, Test Methods for Evaluating Solid Waste, SW-846,

USEPA, December 1996.

Comments:

Allen A #1E.

Analyst C. Q

Mistine m Walters
Review