Submit 3 Copies To Appropriate District	State of N				Form C-103
Office District I	Energy, Minerals ar	nd Natura		WELL API NO.	Revised March 25, 1999
1625 N. French Dr., Hobbs, NM 88240 District II	OIL CONSERVA	ATIÓNII	A// SIONIS ON A	STREEL ATTIVO.	30-039-27434
District III OIL CONSERVATION DIVISION District III OIL CONSERVATION DIVISION 1220 South St. Francis Dr.			5. Indicate Type of Lease		
1000 Rio Brazos Rd., Aztec, NM 87410 District IV Santa Fe, NM 87505			STATE FEE X 6. State Oil & Gas Lease No.		
1220 S. St. Francis Dr., Santa Fe, NM 87505				do Dougo 110.	
SUNDRY NOTICES AND REPORTS ON WELLS					
(DO NOT USE THIS FORM FOR PROPOSAL DIFFERENT RESERVOIR. USE "APPLICAT					
PROPOSALS.)			RIO ARRIBA		
1. Type of Well: Oil Well Gas Well X Other					
2. Name of Operator				8. Well No.	
TEXAKOMA OIL AND GAS CORPORATION				9. Pool name or	2 Wildest
3. Address of Operator 5400 LBJ FREEWAY, SUITE 500, DALLAS, TEXAS 75240				AND COAL (71629)	
4. Well Location					
Unit Letter J: 1378	feet from the <u>SOUT</u>	H li	ne and 2019	feet from the	EAST line
	· · · · · · · · · · · · · · · · · · ·				
Section 16	Township		Range 13W		County SAN JUAN
10. Elevation (Show whether DR, RKB, RT, GR, etc.) 6476' GR					
11. Check Appropriate Box to Indicate Nature of Notice, Report or Other Data					
NOTICE OF INTE		_		SEQUENT RE	
PERFORM REMEDIAL WORK	PLUG AND ABANDON		REMEDIAL WOR	K L	ALTERING CASING
TEMPORARILY ABANDON	CHANGE PLANS		COMMENCE DRILLING OPNS. PLUG AND ABANDONMENT		
	MULTIPLE COMPLETION		CASING TEST AND		
	COMPLETION		CEMENT JOB		
OTHER:			OTHER:		
12. Describe proposed or completed operations. (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work). SEE RULE 1103. For Multiple Completions: Attach wellbore diagram of proposed completion or					
recompilation.					
THIS WELL SPUDDED ON 08-07-03	3 AND AN 12 1/4" HOL	E WAS I	ORILLED TO 336'	RKB (10' GR TO	RKB) AND 7 JTS OF
NEW 8 5/8" 24 PPF J-55 API CASING WAS SET AT 327' RKB (313.5' GR) AND CEMENTED TO SURFACE WITH 225 SKS					
(265.5 CF) OF CLASS B CEMENT W/2% CACL ₂ & 1/4#/SK FLOCELE @ 15.6 PPG, YIELD 1.18 CF/SK, CIRCULATED 15 BBLS OF GOOD CEMENT TO SURFACE, DISPLACED WITH 18.1 BW, PD @ 11:52 A.M., 02-07-03. WOC FOR 8 HOURS AND					
INSTALLED 8 5/8" CASING HEAD AND DR BOP, TESTED BOP TO 1000 PSIG FOR 15", OK. DRILL AHEAD WITH 7 7/8" BIT					
AND DRILLED CEMENT FROM 286' TO 327' KB AND NOW DRILLING AHEAD WITH A 7 7/8" BIT;					
I hereby certify that the information above is true and complete to the best of my knowledge and belief.					
An ha 11					
SIGNATURE OM	Opinblo 1	ritle	DRILLING MAN	NAGER I	DATE <u>08-8-2003</u>
Type or print name TOM SPRIN	NKLE		Telephone No.	972-764-3828	
(This space for State use) APPPROVED BY		DEF		ISPECTOR, DIST.	AUG 1 1 2005
AFFFRUVEUBY COUNTY	<u> </u>	TITLE			DAIE 4 COO!

Conditions of approval, if any:

0