

UNITED STATES
DEPARTMENT OF THE INTERIOR
BUREAU OF LAND MANAGEMENT

SUBMIT IN DUPLICATE*
(See other instructions on reverse side)

RCVD DEC5'06
OIL CONS. DIV.
DIST. 3

FOR APPROVED
OMB NO. 1004-0137
Expires: December 31, 1991

WELL COMPLETION OR RECOMPLETION REPORT AND LOG*

1a. TYPE OF WELL: OIL ☐ WELL ☒ GAS WELL ☒ DRY ☐ Other ☐		2005 NOV 22 PM 3 30	
b. TYPE OF COMPLETION: NEW WELL ☒ WORK OVER ☐ DEE P-EN ☐ PLUG BACK ☐ DIFF. RESVR ☐ Other ☐		7. UNIT AGREEMENT NAME San Juan 28-4 Unit	
2. NAME OF OPERATOR ConocoPhillips		8. FARM OR LEASE NAME, WELL NO. San Juan 28-4 Unit 28A	
3. ADDRESS AND TELEPHONE NO. PO BOX 4289, Farmington, NM 87499 (505) 326-9700		9. API WELL NO. 30-039-27626	
4. LOCATION OF WELL (Report location clearly and in accordance with any State requirements)* At surface Unit D (NWNW) 230' FNL & 530' FWL At top prod. interval reported below Same as above At total depth Same as above		10. FIELD AND POOL, OR WILDCAT Blanco MV/Basin DK 11. SEC., T., R., M., OR BLOCK AND SURVEY OR AREA Sec. 19, T28N, R04W, NMPM	
14. PERMIT NO.		DATE ISSUED	
12. COUNTY OR PARISH Rio Arriba		13. STATE New Mexico	
15. DATE SPUNDED 7/8/06	16. DATE T.D. REACHED 7/16/06	17. DATE COMPL. (Ready to prod.) 10/19/06	18. ELEVATIONS (DF, RKB, RT, BR, ETC.)* GL - 7401
19. ELEV. CASINGHEAD	20. TOTAL DEPTH, MD & TVD 8810'	21. PLUG, BACK T.D., MD & TVD 8796'	22. IF MULTIPLE COMPL., HOW MANY* 2
23. INTERVALS DRILLED BY ROTARY TOOLS Yes		24. PRODUCTION INTERVAL (S) OF THIS COMPLETION-TOP, BOTTOM, NAME (MD AND TVD)* Blanco Mesaverde	
25. TYPE ELECTRIC AND OTHER LOGS RUN CBL/TDT/GR/CCL Log		26. WAS WELL CORED No	
28. CASING RECORD (Report all strings set in well)			
CASING SIZE/GRADE	WEIGHT, LB./FT.	DEPTH SET (MD)	HOLE SIZE
9 5/8"	32.3# H-40	321'	12 1/4"
7"	20# J-55	4601'	8 3/4"
4 1/2"	11.6# L-80	8809'	6 1/4"
29. LINER RECORD		30. TUBING RECORD	
SIZE	TOP (MD)	BOTTOM (MD)	SACKS CEMENT*
			SCREEN (MD)
			SIZE 2 3/8"
			DEPTH SET (MD) 8695'
			PACKER SET (MD)
31. PERFORATION RECORD (Interval, size and number) Mesaverde @ .34" holes PT/Men 6372' - 6872' = 1 spf = 26 Holes UMNF/CH 5952' - 6313' = 1 spf = 28 Holes Total = 54 Holes		32. ACID, SHOT, FRACTURE, CEMENT SQUEEZE, ETC. DEPTH INTERVAL (MD) 6372' - 6872' Pump 10 bbls of 15% HCL. Frac w/ 100000# 20/40 brady sand. 1201000 SCF N2 5952' - 6313' Pump 10 bbls of 15% HCL. Frac w/ 100000# 20/40 brady sand. 1201000 SCF N2	
33. PRODUCTION			
DATE FIRST PRODUCTION SI	PRODUCTION METHOD (Flowing, gas lift, pumping—size and type of pump) Flow		WELL STATUS (Producing or shut-in) SI
DATE OF TEST 9/28/06	HOURS TESTED 4	CHOKE SIZE 1"	PROD'N FOR TEST PERIOD OIL-BBL 342 mcf
FLOW. TUBING PRESS.	CASING PRESSURE SITP - 812#	CALCULATED 24-HOUR RATE SICP - 796#	GAS-MCF 2054 mcf
34. DISPOSITION OF GAS (Sold, used for fuel, vented, etc.) To be sold			TEST WITNESSED BY
35. LIST OF ATTACHMENTS			

This is a commingled Mesaverde/Dakota well per DHC # 2179AZ.

W/. I hereby certify that the foregoing and attached information is complete and correct as determined from all available records

SIGNED

Kandis Roland

TITLE

Regulatory Assistant

DATE

ACCEPTED FOR RECORD
11/17/06

*(See Instructions and Spaces for Additional Data on Reverse Side)

Title 18 U.S.C. Section 1001, makes it a crime for any person knowingly and willfully to make to any department or agency of the United States any false, fictitious or fraudulent statements or representations as to any matter within its jurisdiction.

DEC 04 2006

FARMINGTON FIELD OFFICE

NMOCDD

86

Ojo Alamo	3717'	3865'	White, cr-gr ss.	Ojo Alamo	3717'
Kirtland	3865'	4184'	Gry sh interbedded w/tight, gry, fine-gr ss.	Kirtland	3865'
Fruitland			Dk gry-gr carb sh, coal, grn silts, light-med gry, tight, fine gr ss.	Fruitland	4184'
Pictured Cliffs	4184'	4372'	Bn-Gry, fine grn, tight ss.	Pic.Cliffs	4372'
Lewis	4372'	4544'	Shale w/siltstone stringers	Lewis	4544'
Huerfanito Bentonite	4544'	4990'	White, waxy chalky bentonite	Huerfanito Bent.	4990'
Chacra	4990'	5343'	Gry fn grn silty, glauconitic sd stone w/drck gry shale	Chacra	5343'
Mesa Verde	5343'	5950'	Light gry, med-fine gr ss, carb sh & coal	Mesa Verde	5950'
Menefee	5950'	6201'	Med-dark gry, fine gr ss, carb sh & coal	Menefee	6201'
Point Lookout	6201'	6514'	Med-light gry, very fine gr ss w/frequent sh breaks in lower part of formation	Point Lookout	6514'
Mancos	6514'	6958'	Dark gry carb sh.	Mancos	6958'
Gallup	6958'	7760'	Lt gry to brn calc carb micac glauc silts & very fine gr gry ss w/irreg.interbed sh	Gallup	7760'
La Ventana	7760'	8495'	Wt to lt buff to med grn sl carb bent	Greenhorn	8495'
Greenhorn	XXXX	XXXX	Highly calc gry sh w/thin lmst.	Graneros	8558'
Graneros	8495'	8558'	Dk gry shale, fossil & carb w/pyrite incl.	Dakota	8621'
Dakota	8558'	8621'	Lt to dk gry foss carb sl calc sl silty ss w/pyrite incl thin sh bands clay & shale breaks		
	8621'				