RCVD DEC15/06 31L CONS. DIV.

Form '3160-5 (April 2004)

UNITED STATES DEPARTMENT OF THE INTERIOR BUREAU OF LAND MANAGEMENT

FORM APPROVED
OMB No. 1004-0137
Expires: March 31, 20

5 Leace Serial No.

DIST. 3

	SU	NDF	RY N	OTIC	ES A	AND	KE	POR	15	ON	WELLS	
ю	not	use	this	form	for p	ropos	als	to dri	ill o	r to	re-enter	· an
bi	ando	ned	well.	Use	Form	3160	- 3	(APD)	for	sugi	propos	aļs.

٠.	NMNM 104609						
6.	If Indian, Allottee or Tribe Name						

	ell. Use Form 3160 - 3 (41	,		
SUBMIT IN TRI	PLICATE- Other inst	ructions on revers	se side.	7. If Unit or	CA/Agreement, Name and/or No.		
1. Type of Well Gas Well Other 070 FARMER GROUP					8. Well Name and No. Juniper West Com 24 #24 9. API Well No.		
2. Name of Operator Coleman Oil & Gas, Inc.							
Ba. Address P.O. Drawer 3337	3b. Phone No. (include 505-327-0356	area code)	30-045-33594 10. Field and Pool, or Exploratory Area				
4. Location of Well (Footage, Sec., T., R., M., or Survey Description) 670' FSL, 1810' FWL N, Section 24, T24N, R11W Latitude 36° 17" 36.4", Longitude 107° 57' 26.5"					Basin Fruitland Coal 11. County or Parish, State San Juan, New Mexico		
12. CHECK A	PPROPRIATE BOX(ES) TO	INDICATE NATUR	E OF NOTICE, R	EPORT, OF	ROTHER DATA		
TYPE OF SUBMISSION	TYPE OF SUBMISSION TYPE OF ACTION						
Notice of Intent ✓ Subsequent Report Final Abandonment Notice	Acidize Alter Casing Casing Repair Change Plans Convert to Injection	Deepen Fracture Treat New Construction Plug and Abandon Plug Back	Production (State Reclamation Recomplete Temporarily Ab		Water Shut-Off Well Integrity Other		
		_	•		ork and approximate duration thereo		

SPUD WELL NOVEMBER 29, 2006 @ 7:30 AM. DRILLED 12 1/4" HOLE TO 136 FT. KB AND RAN 3 JTS OF 8 5/8" 24# J-55 ST&C NEW CASING. RAN A TOTAL FOOTAGE OF 126.35 FT. AND LANDED @ 132.35 FT. KB. CEMENTED W/ 100 SACKS TYPE 5 CEMENT W/3% CALCIUM CHLORIDE AND 1/4# PER SACK CELLOFLAKE. CIRCULATED 7 BARRELS OF CEMENT TO RESERVE PIT. NIPPLED UP BOP AND MANIFOLD. PRESSURE TESTED BOP, MANIFOLD AND CASING TO LOW 250 PSIG AND HIGH 750 PSIG. DRILLED 7 7/8" HOLE TO 1086 FT. KB. TD WELL @ 1086 FT.KB @ 2:30 PM ON DECEMBER 1, 2006. RAN A TOTAL OF 28 JTS 5 1/2" 15.50#/FT LT&C J-55. LANDED CASING @ 1076.10 FT. KB. CEMENTED W/ 90 SACKS CLASS G W 3% D79 AND 1/4# PER SACK D29. TAILED W/ 90 SACKS CLASS G 50/50 POZ W/ 2% GEL D20, 5# PER SACK D24 GILSONITE, .1% D46, 1% S-1 AND 1/4# PER SACK D29. CIRCULATED 20 BARRELS OF CEMENT TO SURFACE. PLUG DOWN AT 1:00 PM DECEMBER 2, 2006. BUMPED PLUG TO 700 PSIG. PLUG AND CASING HELD PRESSURE.

Attach the Bond under which the work will be performed or provide the Bond No. on file with BLM/BIA. Required subsequent reports shall be filed within 30 days following completion of the involved operations. If the operation results in a multiple completion or recompletion in a new interval, a Form 3160-4 shall be filed once testing has been completed. Final Abandonment Notices shall be filed only after all requirements, including reclamation, have been completed, and the operator has

14. I hereby certify that the foregoing is true and correct Name (Printed/Typed) MICHAEL T. HANSON	Title OPERATION	S ENGINEER					
Signature Muhal Thans	Date 12/9/	06					
THIS SPACE FOR FEDERAL OR STATE OFFICE USE							
Approved by	Title	Date					
Conditions of approval, if any, are attached. Approval of this notice does not warrant certify that the applicant holds legal or equitable title to those rights in the subject least which would entitle the applicant to conduct operations thereon.		ACOSPERACIONAD					
Title 18 U.S.C. Section 1001 and Title 43 U.S.C. Section 1212, make it a crime for any particles any false, fictitious or fraudulent statements or representations as to any matter	person knowingly and within its jurisdiction.	willfully to make to any department or agency of the United					

(Instructions on page 2)

determined that the site is ready for final inspection.)

