

submitted in lieu of Form 3160-5

UNITED STATES
DEPARTMENT OF THE INTERIOR
BUREAU OF LAND MANAGEMENT

Sundry Notices and Reports on Wells

2006 DEC 7 PM 3 00

1. Type of Well
GAS

2. Name of Operator
BURLINGTON
RESOURCES OIL & GAS COMPANY LP

3. Address & Phone No. of Operator
PO Box 4289, Farmington, NM 87499 (505) 326-9700

4. Location of Well, Footage, Sec., T, R, M

Unit N (SESW), 1040' FSL & 1630' FWL, Section 34, T28N R8W, NMPM

5. Lease Number
NMSF-078566-A
6. If Indian, All. or
Tribe Name
7. Unit Agreement Name

8. Well Name & Number

9. Howell 100
API Well No.

30-045-31728 33876

10. Field and Pool

Basin FC/Blanco PC

11. County and State
San Juan Co., NM

12. CHECK APPROPRIATE BOX TO INDICATE NATURE OF NOTICE, REPORT, OTHER DATA

Type of Submission	Type of Action
<input type="checkbox"/> Notice of Intent	<input type="checkbox"/> Abandonment <input type="checkbox"/> Change of Plans
<input checked="" type="checkbox"/> Subsequent Report	<input type="checkbox"/> Recompletion <input type="checkbox"/> New Construction
<input type="checkbox"/> Final Abandonment	<input type="checkbox"/> Plugging <input type="checkbox"/> Non-Routine Fracturing
	<input type="checkbox"/> Casing Repair <input type="checkbox"/> Water Shut off
	<input type="checkbox"/> Altering Casing <input type="checkbox"/> Conversion to Injection

X Other - Casing Report

13. Describe Proposed or Completed Operations

11/26/06 RIH w/6 1/4" bit. Tag cement @ 180'. D/O & ahead to 2335' (TD). TD reached on 11/28/06. Circ hole. RIH w/54 jts 4 1/2" 10.5# J-55 Casing set @ 2327'. DV tool @ 1585'. RU cement. Pumped pre-flush 2 bbls FW/5 bbls gel. 1st Stage-Lead pumped Scavenger 19 sx(57 cf- 10 bbls) Type III Cement w/1% CaCl, .25 #/sx Cello-Flake, & .2% FI-52. Tail- pumped 103 sx(142 cf- 25 bbls) Type III Cement w/1% CaCl, .25 #/sx Cello-Flake, & .2% FI-52. Bumped plug & displaced w/15 bbls FW. Opened Stage tool. Circ 15 bbls cement. Circ hole. 2nd Stage- pumped pre-flush 2 bbls FW/10 bbls gel/10 bbls FW. Lead-pumped Scavenger 19sx (57 cf- 10bbls) Premium Lite Cement w/3% CaCl, .25 #/sx Cello-Flake, 5#/sx LCM-1, .4% FI-52 & .4% SMS. Tail- pumped 149 sx(317 cf- 56 bbls) Premium Lite Cement w/3% CaCl, .25 #/sx Cello-flake, 5 #/sx LCM-1, .4% FI-52 & .4% SMS. Bumped plug & displaced w/25 bbls FW. Plug down & closed Stage Tool @ 2000 psi. Circ 35 bbls cement to surface. WOC. RD. RR @ 2330 hrs.

PT will be conducted by completion rig & results shown on next report.

14. I hereby certify that the foregoing is true and correct.

Signed Tracey N. Monroe Tracey N. Monroe Title Regulatory Technician Date 12/5/06

(This space for Federal or State Office use)

APPROVED BY _____ Title _____ Date _____

CONDITION OF APPROVAL, if any:

Title 18 U.S.C. Section 1001, makes it a crime for any person knowingly and willfully to make any department or agency of the United States any false, fictitious or fraudulent statements or representations as to any matter within its jurisdiction.

ACCEPTED FOR RECORD

DEC 08 2006

FARMINGTON FIELD OFFICE

NMOCD 8