

UNITED STATES
DEPARTMENT OF THE INTERIOR
BUREAU OF LAND MANAGEMENTSUBMIT IN DUPLICATE*
(See other instructions on reverse side)FOR APPROVED
OMB NO. 1004-0137RCVD DEC 22 06
OIL CONS. DIV.

Expires: December 31, 1991

DIST. 3

5. LEASE DESIGNATION AND SERIAL NO.

NMSF-078410

6. IF INDIAN, ALLOTTEE OR TRIBE NAME

C 23 PM 4:13

7. UNIT AGREEMENT NAME

San Juan 29-5 Unit

8. FARM OR LEASE NAME, WELL NO.

San Juan 29-5 Unit 21C

9. API WELL NO.

30-039-29553

10. FIELD AND POOL, OR WILDCAT

Blanco MV

11. SEC., T., R., M., OR BLOCK AND SURVEY
OR AREA

Sec. 8, T29N, R05W, NMPM

Amended
WELL COMPLETION OR RECOMPLETION REPORT AND LOG*1a. TYPE OF WELL: OIL ☐ GAS ☒ DRY ☐ Other ☐

b. TYPE OF COMPLETION:

NEW ☒ WORK ☐ DEE ☐ PLUG ☐ DIFF. ☐
WELL ☒ OVER ☐ P-EN ☐ BACK ☐ RESVR ☐ Other ☐

2. NAME OF OPERATOR

ConocoPhillips

3. ADDRESS AND TELEPHONE NO.

PO BOX 4289, Farmington, NM 87499 (505) 326-9700

4. LOCATION OF WELL (Report location clearly and in accordance with any State requirements)*

At surface Unit B (NWNE) 400' FNL & 2500' FEL

At top prod. interval reported below Same as above

At total depth Same as above

14. PERMIT NO. DATE ISSUED

12. COUNTY OR
PARISH

Rio Arriba

13. STATE

New Mexico

15. DATE SPUNDED 16. DATE T.D. REACHED 17. DATE COMPL. (Ready to prod.)

8/11/06

8/17/06

10/05/06

18. ELEVATIONS (OF, RKB, RT, BR, ETC.)

6648' - GL

19. ELEV. CASINGHEAD

20. TOTAL DEPTH, MD & TVD 21. PLUG, BACK T.D., MD & TVD 22. IF MULTIPLE COMPL., HOW MANY*

6180'

6185'

23. INTERVALS
DRILLED BY

ROTARY TOOLS

CABLE TOOLS

Yes

24. PRODUCTION INTERVAL (S) OF THIS COMPLETION-TOP, BOTTOM, NAME (MD AND TVD)*

Blanco Mesaverde 4338' - 5873'

25. WAS DIRECTIONAL
SURVEY MADE

No

26. TYPE ELECTRIC AND OTHER LOGS RUN

CBL/TDT/GR/CCL Log

27. WAS WELL CORED

No

28. CASING RECORD (Report all strings set in well)

CASING SIZE/GRADE	WEIGHT, LB./FT.	DEPTH SET (MD)	HOLE SIZE	TOP OF CEMENT, CEMENTING RECORD	AMOUNT PULLED
9 5/8"	32.3# H-40	242'	13 1/2"	Surface: 240 sx (281 cf)	16 bbls
7"	20# J-55	3928'	8 3/4"	Surface: 660 sx (1440 cf)	15 bbls
4 1/2"	10.5# J-55	6166'	6 1/4"	TOC 3200'; 415 sx (590 cf)	Includes squeeze

29. LINER RECORD

SIZE	TOP (MD)	BOTTOM (MD)	SACKS CEMENT*	SCREEN (MD)	SIZE	DEPTH SET (MD)	PACKER SET (MD)
					2 3/8"	5796'	
					4.7# J-55		

31. PERFORATION RECORD (Interval, size and number)

Mesaverde @ .34" holes
LM/PTL 5714' - 5873' = 1 spf = 30 Holes
CH 5181' - 5619' = 1 spf = 30 Holes
Lewis 4338' - 4796' = 1 spf = 30 Holes

Total = 90 Holes

32. ACID, SHOT, FRACTURE, CEMENT SQUEEZE, ETC.

DEPTH INTERVAL (MD)	AMOUNT AND KIND OF MATERIAL USED
5714' - 5873'	Pump 420 gals of 15% HCL. Frac w/ 60 Q Slickfoam w/ 99420# of 20/40 brady sand.
5181' - 5619'	Pump 420 gals of 15% HCL. Frac w/ 60 Q Slickfoam w/ 100640# of 20/40 brady sand.
4338' - 4796'	Pump 420 gals of 15% HCL. Frac w/ 75 Q Slickfoam w/ 200340# of 20/40 brady sand

33. PRODUCTION

DATE FIRST PRODUCTION	PRODUCTION METHOD (Flowing, gas lift, pumping—size and type of pump)	WELL STATUS (Producing or shut-in)
SI	Flow	SI
DATE OF TEST	HOURS TESTED	CHOKE SIZE
10/5/06	2	1/2"
PROD'N FOR TEST PERIOD	OIL-BBL	GAS-MCF
		95 mcf
WATER-BBL	GAS-MCF	WATER-BBL
FLOW, TUBING PRESS.	CASING PRESSURE	CALCULATED 24-HOUR RATE
SITP-1000#	FCP - 160#	
		1142 mcfd
		15 BWPD

F68 DISPOSITION OF GAS (Sold, used for fuel, vented, etc.)

To be sold

TEST WITNESSED BY

35. LIST OF ATTACHMENTS

This is a standalone Mesaverde well.

I hereby certify that the foregoing and attached information is complete and correct as determined from all available records

SIGNED Xanalis Roland TITLE

Regulatory Technician

DATE

12/19/06

*(See Instructions and Spaces for Additional Data on Reverse Side)

Title 18 U.S.C. Section 1001, makes it a crime for any person knowingly and willfully to make to any department or agency of the United States any false, fictitious or fraudulent statements or representations as to any matter within its jurisdiction.

ACCEPTED FOR RECORD

DEC 21 2006

FARMINGTON FIELD OFFICE

NMOC

Ojo Alamo	2752'	2922'	White, cr-gr ss.	Ojo Alamo	2752'
Kirtland	2922'	3242'	Gry sh interbedded w/tight, gry, fine-gr ss.	Kirtland	2922'
Fruitland			Dk gry-gry carb sh, coal, grn silts, light-med gry, tight, fine gr ss.	Fruitland	3242'
Pictured Cliffs	3242'	3592'	Bn-Gry, fine grn, tight ss.	Pic. Cliffs	3592'
Lewis	3592'	3792'	Shale w/siltstone stringers	Lewis	3792'
Huerfanito Bentonite			White, waxy chalky bentonite	Huerfanito Bent.	
Chacra		4612'	Gry fn-grn-silty, glauconitic sd stone w/drk gry shale	Chacra	4612'
Mesa Verde	4612'	5467'	Light gry, med-fine gr ss, carb sh & coal	Mesa Verde	5467'
Menefee	5467'	5512'	Med-dark gry, fine gr ss, carb sh & coal	Menefee	5512'
Point Lookout	5512'	5792'	Med-light gry, very fine gr ss w/frequent sh breaks in lower part of formation	Point Lookout	5792'
	5792'				