

UNITED STATES
DEPARTMENT OF THE INTERIOR
BUREAU OF LAND MANAGEMENT

DIST. 3

Sundry Notices and Reports on Wells

2007 JAN 3 PM 3 46

1. Type of Well
GASRECEIVED
070 FARMINGTON, NM5. Lease Number
NMSF-078146
6. If Indian, All. or
Tribe Name
7. Unit Agreement Name

2. Name of Operator

ConocoPhillips

8. Well Name & Number
Newberry 1F

3. Address & Phone No. of Operator

PO Box 4289, Farmington, NM 87499 (505) 326-9700

9. API Well No.
30-045-33387

4. Location of Well, Footage, Sec., T, R, M

Unit G (SWNE), 2100' FNL & 1900' FEL, Section 17, T31N, R12W, NMPM

10. Field and Pool
Blanco MV/Basin DK
11. County and State
San Juan Co, NM

12. CHECK APPROPRIATE BOX TO INDICATE NATURE OF NOTICE, REPORT, OTHER DATA

Type of Submission	Type of Action
<input type="checkbox"/> Notice of Intent	<input type="checkbox"/> Abandonment <input type="checkbox"/> Change of Plans
<input checked="" type="checkbox"/> Subsequent Report	<input type="checkbox"/> Recompletion <input type="checkbox"/> New Construction
<input type="checkbox"/> Final Abandonment	<input type="checkbox"/> Plugging <input type="checkbox"/> Non-Routine Fracturing
	<input type="checkbox"/> Casing Repair <input type="checkbox"/> Water Shut off
	<input type="checkbox"/> Altering Casing <input type="checkbox"/> Conversion to Injection

☒ Other - Casing Report

13. Describe Proposed or Completed Operations

12/10/06 PT casing, 1000#/30 min. OK. RIH w/ 8 3/4" bit & tag cement @ 245'. D/O cement & then formation to 4375'. Circ. hole. RIH w/ 122 jts, of 7", 23#, J-55 LT&C casing & 81 jts of 7", 20#, J55 ST&C casing set @ 4368'. 12/15/06 RU to cement. Pumped preflush & lead w/ 490 sx (1260 cf - 224 bbls) premium plus type III w/ 30# pozmix A, 3% bentonite, 5# phenoseal. Tail w/ 255 sx (339 cf - 60 bbls) premium plus type III w/ 30# pozmix A, 3% bentonite, 5# phenoseal. Drop plug & displaced 175 bbls FW. Circ 120 bbls cmt to surface. WOC. NU BOP. 12/15/06 PT casing, 1800 #/30min. OK.

12/16/06 RIH w/ 6 1/4" bit. D/O cement & then formation to 7118' (TD). TD reached 12/17/06. Circ. hole. RIH w/ 171 jts 4 1/2", 11.6#, N-80 LT&C casing & set @ 7117'. 12/18/06 RU cement. Pumped preflush. Lead w/ 310 sx (450 cf - 80 bbls) 50/50 type V w/ 2% bentonite, 3.5# Phenoseal. Drop plug & displaced w/ 110 bbls FW. Bumped Plug w/ 1800#. ND. Install trash cap. RD & released rig @ 12/18/2006. Will show TOC & casing PT on the next report.

14. I hereby certify that the foregoing is true and correct.

Signed Kandis Roland Kandis Roland Title Regulatory Technician Date 12/29/06

(This space for Federal or State Office use)

APPROVED BY _____ Title _____ Date _____

CONDITION OF APPROVAL, if any:

Title 18 U.S.C. Section 1001, makes it a crime for any person knowingly and willfully to make any department or agency of the United States any false, fictitious or fraudulent statements or representations as to any matter within its jurisdiction.

NMOC

