District I 1625 N. French Dr., Hobbs, NM 88240 District | 1 | 1301 W. Grand Avenue, Artesia, NM 88210 1000 Rio Brazos Road, Aztec, NM 87410 District IV 1220 S. St. Francis Dr., Santa Fe, NM 87505

State of New Mexico Energy Minerals and Natural Resources

Oil Conservation Division 1220 South St. Francis Dr. Santa Fe, NM 87505

For drilling and production facilities, submit to appropriate NMOCD District Office.
For downstream facilities, submit to Santa Fe office

Form C-144

June 1, 2004

Pit or Below-Grade Tank Registration or Closure

	ide Tank Registration or Closu	
	k covered by a "general plan"? Yes 🔀 No or below-grade tank 🔲 Closure of a pit or below-gra	
Type of action. Registration of a pirc	is below-grade tank Closure of a pit of below-gra	ade tank 😝 <u>oil colic.</u> DIV.
Operator: BP America Production Company Telephor	ne: <u>(505)326-9200</u> e-mail address:	
Address: 200 Energy Ct, Farmington, NM 87401		9157. 9
Facility or well name: CORNEL DUDIEY A #1E API#: 3		
County: San Juan Latitude	Longitude	NAD: 1927 ☐ 1983 🔀
Surface Owner: Federal State Private Indian		·
Pit	Below-grade tank	
Type: Drilling Production Disposal	Volume:bbl Type of fluid:	
Workover	Construction material:	$\cdot \Delta$
Lined [] Unlined []	Double-walled, with leak detection? Yes D If no	, explain why not.
Liner type: Synthetic Thicknessmil Clay _	//	
Pit Volumebbl	, , ,	\
Depth to ground water (vertical distance from bottom of pit to seasonal	Less than 50 feet	(20 points)
high water elevation of ground water.)	50 feet or more, but less than 100 feet	(10 points)
mgn water elevation or ground water.)	100 feet or more	(0 points)
Wellhead protection area: (Less than 200 feet from a private domestic	Yes	(20 points)
water source, or less than 1000 feet from all other water sources.)	No	(0 points)
water source, or less than 1000 feet from an other water sources.)	Less than 200 feet	(20
Distance to surface water: (horizontal distance to all wetlands, playas,		(20 points)
irrigation canals, ditches, and perennial and ephemeral watercourses.)	200 feet or more, but less than 1000 feet	(10 points)
,	1000 feet or more	(0 points)
	Ranking Score (Total Points)	0
f this is a pit closure: (1) Attach a diagram of the facility showing the pit'	s relationship to other equipment and tanks (2) India	ate disposal location: (check the onsite box if
your are burying in place) onsite 🔀 offsite 🗌 If offsite, name of facility_		•
emediation start date and end date. (4) Groundwater encountered: No 🔝 Y		
5) Attach soil sample results and a diagram of sample locations and excavat		it. and attach sample results.
Additional Comments:		
See Attached Documentation		
See Attached Documentation		
		75.4
I hereby certify that the information above is true and complete to the best	of my knowledge and balief. I further swift shade	
has been/will be constructed or closed according to NMOCD guideline	s 🔀, a general permit 🔲, or an (attached) alterna	itive OCD-approved plan .
	A	
Date: 11/01/2005	Alla C. Sec.	
Printed Name/Title		-Fahr-ia-a-a-l
otherwise endanger public health or the environment. Nor does it relieve the regulations.	the operator of its responsibility for compliance with a	of the pit or tank contaminate ground water or my other federal, state, or local laws and/or
Approval:	1 0.1	DA 500 CO
Printed Name/Title DEPUTY OR & GAS INSPECTOR, DIST. 42	Signature Branch July	DEC 2 7 2006

	BLA	GG ENG	INEERING	, INC.	LOC	CATION NO:	81149
CLIENT: BP	J	•	OMFIELD	, NM 874	413		10500
		(505) 63	2-1199		COC	CR NO:	70303
FIELD REPORT	: PIT CL	OSURI	E VERIF	ICATIO			/ of
LOCATION: NAME: CORNEU	L DUDLEY ?	A WELL#:	TYPE	:: S€P.	I		2/12/03
QUAD/UNIT: 6 SEC: 1	TWP: Z9A RN	G: 12W PM:	MM CNTY: 5,	J ST: NM		FINISHED:	
QTR/FOOTAGE: 1750 %/ に	150E	5WINE CONT	RACTOR: FLINT	r (BEN)		RONMENTAL IALIST:	NV
EXCAVATION APPROX	<u>)</u> 4 FT. >	(17 FT	. x <u>9</u> FT	. DEEP. CL	JBIC YARE	DAGE: _	80
DISPOSAL FACILITY:	577 Z - 40	₹	REMEDIA	TION METHO	OD: _	LANDR	RRM
LAND USE: LANGE -!	sum	LEASE:	SF 069	5557A	FORMAT	ION:	0K
FIELD NOTES & REMAR							
DEPTH TO GROUNDWATER: >10			>10001		URFACE WAT	ГЕR: > 1	000'
NMOCD RANKING SCORE:	NMOCD TPH	CLOSURE STD:	5000 PF	°М			
SOIL AND EXCAVATION	N DESCRIPT	ΓΙΟΝ:		OVM CALIB. I			
		<u> </u>		TIME: /0:5			
SOIL TYPE: SANDY SILTY SAN		CLAY / CLAY /	GRAVEL / OTH				
SOIL COLOR: LT. GRAY COHESION (ALL OTHERS): NON C	To Book OHESIVE/ SLIGHTLY	Y COHESIVE / CO	OHESIVE / HIGHLY	COHESIVE			
CONSISTENCY (NON COHESIVE SC	ILS): (OOSE)(FIRM	DI DENSE / VERY	Y DENSE				
PLASTICITY (CLAYS): NON PLASTIC				/ HIGHLY PLASTI	IC		
DENSITY (COHESIVE SLAYS & SILT) MOISTURE: DRY / SLIGHTLY MOIST	·						CLOSED
DISCOLORATION/STAINING OBSER	VED: YES NO EXP	PLANATION - +	ENTIRE PIT &	- OITAURDY	١.		
HC ODOR DETECTED: (ES) NO EX	XPLANATION	COTRUBOK	5016 & O	um sampl	<u>.</u> ₹.		
SAMPLE TYPE: GRABY COMPOSITE ADDITIONAL COMMENTS: PIT CO	HTALLED APPROX	(. a BRL'S	OF FLAID A	RIOR TO EXC	· MOTTAUA:	mixed 4	COTALIPS L
SOL	•						
		FI	IELD 418.1 CALC	ULATIONS			
SCALE SAMP. TIN	ME SAMP. ID	LAB NO.	WEIGHT (g)	mL FREON	DILUTION	READING	CALC. (ppm)
0 FT					DIT	SOFIL	
PIT PERIMET	ER PN		OVM		PHF	PROFILI	<u>E</u>
1 To			ADING				
/ HEAD		SAMPLE	FIELD HEADSPACE (ppm)	7	-	14 '	-
į ,		1@ 12'	138X		•		_(
18,		2 @ 3 @		+ -	\		
BERM		4@					\int_{0}^{∞}
	7 7	5 @		15	,	1	
	1 21']	\	j	
A 0 141 5							
1					LT. GATY	015000	ews Tips
\		0.4404	AMPLES		C PIT	Bottom	
) <	NZ B. b.	10 A	NALYSIS TIME				
	N12 8.0		X (BOZIE) "				
		(BOTH	PASSED	-			
P.D. ≈ PIT DEPRESSION; B.G. = BELOW							
T.H. = TEST HOLE; ~ = APPROX.; T.B. =							



EPA METHOD 8015 Modified Nonhalogenated Volatile Organics Total Petroleum Hydrocarbons

Client:	Blagg / BP	Project #:	94034-010
Sample ID:	1 @ 12'	Date Reported:	02-14-03
Laboratory Number:	24828	Date Sampled:	02-12-03
Chain of Custody No:	10500	Date Received:	02-13-03
Sample Matrix:	Soil	Date Extracted:	02-14-03
Preservative:	Cool	Date Analyzed:	02-14-03
Condition:	Cool and Intact	Analysis Requested:	8015 TPH

Parameter	Concentration (mg/Kg)	Det. Limit (mg/Kg)
Gasoline Range (C5 - C10)	361	0.2
Diesel Range (C10 - C28)	577	0.1
Total Petroleum Hydrocarbons	938	0.2

ND - Parameter not detected at the stated detection limit.

References:

Method 8015B, Nonhalogenated Volatile Organics, Test Methods for Evaluating Solid Waste,

SW-846, USEPA, December 1996.

Comments:

Cornell Dudley A #1E Separator Pit Grab Sample.

Analyst C. Cerron

Review



EPA METHOD 8021 AROMATIC VOLATILE ORGANICS

Client:	Blagg / BP	Project #:	94034-010
Sample ID:	1 @ 12'	Date Reported:	02-14-03
Laboratory Number:	24828	Date Sampled:	02-12-03
Chain of Custody:	10500	Date Received:	02-13-03
Sample Matrix:	Soil	Date Analyzed:	02-14-03
Preservative:	Cool	Date Extracted:	02-14-03
Condition:	Cool & Intact	Analysis Requested:	BTEX

Parameter	 Concentration (ug/Kg)	Det. Limit (ug/Kg)	
Benzene Toluene Ethylbenzene p,m-Xylene o-Xylene	19.0 128 187 985 375	1.8 1.7 1.5 2.2 1.0	
Total BTEX	1,690		

ND - Parameter not detected at the stated detection limit.

Surrogate Recoveries:	Parameter	Percent Recovery
!	Fluorobenzene	95 %
	1,4-difluorobenzene	95 %
	Bromochlorobenzene	95 %

References:

Method 5030B, Purge-and-Trap, Test Methods for Evaluating Solid Waste, SW-846, USEPA,

December 1996.

Method 8021B, Aromatic Volatile Organics, Test Methods for Evaluating Solid Waste, SW-846,

USEPA, December 1996.

Comments:

Cornell Dudley A #1E Separator Pit Grab Sample.

Analyst . Carl

Review

CLIENT: BP		NEERING, INC. OMFIELD, NM 87413	LOCATION NO 81149	
		632-1199	C.O.C. NO: 13396	
FIELD REPORT:	LANDFARM/COM	POST PILE CLOSURE	VERIFICATION	
LOCATION: NAME: CORNEL		··· , · · · · · · · · · · · · · · · · ·	DATE STARTED. 3/22/05	
	TWP: CTIO RNG: 1200	PM:NM CNTY: ST ST:NM FUNT	ENVIRONMENTAL SPECIALIST:	
LAND USE:		LIFT DEPTH (ft):	90 'ARDAGE:	
		E: O NMOCD TPH CLOSUR NEAREST SURFAC		
SOIL TYPE: AND / SILTY SAND / SILT / SILTY CLAY / CLAY / GRAVEL / DTHER SOIL COLOR: OK. YELL. ORD CHESIVE / SIGNAY COMESION (ALL OTHERS): (MON COMESIVE) / SLIGHTLY COMESIVE / COMESIVE / HIGHLY COMESIVE CONSISTENCY (NON COMESIVE SOILS): (DDSD FIRM) DENSE / VERY DENSE PLASTICITY (CLAYS): NON PLASTIC / SLIGHTLY PLASTIC / COMESIVE / MEDIUM PLASTIC / HIGHLY PLASTIC DENSITY (COMESIVE CLAYS & SILTS): SOFT / FIRM / STIFF / VERY STIFF / HARD MOISTURE: DRY / SLIGHTLY MOIST / MOIST / WET / SATURATED / SUPER SATURATED DISCOLORATION/STAINING OBSERVED: (YES) / NO				
	FIELD 418	3.1 CALCULATIONS		
SAMP. TIME SAM	PLE I.D. LAB No: WEIGHT	(g) mL. FREON DILUTION READIN	IG CALC. ppm	
SKETCH/SAMPLE	LOCATIONS N	DVM CALIB. READ. 5/.5	ppm	
To well HEAD	LANDFARM	DVM CALIB. GAS = 100 pp TIME: 9:15 GTV pm DATE		
35	1		LAB SAMPLES	
64	erm T	SAMPLE FIELD MEADSPACE SAMPLE FID (PPM)		
DESIGNATION DESIGNATION	31	LF-1 1.6 LF-1	(80158) 0930 431	
Designa	FROM HEAD	SCALE O FT	2/12/03	
TRAVEL NOTES: CALLOUT:	NA	ONSITE: _3/22/05		



EPA METHOD 8015 Modified Nonhalogenated Volatile Organics Total Petroleum Hydrocarbons

• •			
Client:	Blagg / BP	Project #:	94034-010
Sample ID:	LF - 1	Date Reported:	03-23-05
Laboratory Number:	32418	Date Sampled:	03-22-05
Chain of Custody No:	13396	Date Received:	03-22-05
Sample Matrix:	Soil	Date Extracted:	03-22-05
Preservative:	Cool	Date Analyzed:	03-23-05
Condition:	Cool and Intact	Analysis Requested:	8015 TPH

Parameter	Concentration (mg/Kg)	Det. Limit (mg/Kg)
Gasoline Range (C5 - C10)	3.3	0.2
Diesel Range (C10 - C28)	428	0.1
Total Petroleum Hydrocarbons	431	0.2

ND - Parameter not detected at the stated detection limit.

References:

Method 8015B, Nonhalogenated Volatile Organics, Test Methods for Evaluating Solid Waste,

SW-846, USEPA, December 1996.

Comments:

Cornell Dudley A #1E - Landfarm 5 Pt. Composite Sample.