District I 1625 N. French Dr., Hobbs, NM 88240 District II
1301 W. Grand Avenue, Artesia, NM 88210
District III
1000 Rio Brazos Road, Aztec, NM 87410 District IV 1220 S. St. Francis Dr., Santa Fe, NM 87505

State of New Mexico Energy Minerals and Natural Resources

For drilling and production facilities, submit to appropriate NMOCD District Office.
For downstream facilities, submit to Santa Fe

Form C-144 June 1, 2004

Oil Conservation Division 1220 South St. Francis Dr. Santa Fe, NM 87505

office

Is pit or below-grade tan	ade Tank Registration or Closu ak covered by a "general plan"? Yes 🔀 No	
Operator: BP America Production Company Telephor Address: 200 Energy Ct, Farmington, NM, 87401	or below-grade tank Closure of a pit or below-grade: (505)326-9200 e-mail address:	
Facility or well name: 6cm #156 API #: 3	0045 07123 U/L or Qtr/Qtr O	Sec 26 T 28 NR 13 W
	Longitude	
Surface Owner: Federal ☐ State ☐ Private ☐ Indian 🗵		·
<u>Pit</u>	Below-grade tank	
Type: Drilling Production 🔀 Disposal 🗌	Volume:bbl Type of fluid:	
Workover	Construction material:	- 🗸
Lined Unlined	Double-walled, with leak detection? Yes 11 if no	explain why not.
Liner type: Synthetic Thicknessmil Clay	/X-/	
Pit Volumebbl	,	:
Depth to ground water (vertical distance from bottom of pit to seasonal	Less than 50 feet	(20 points)
high water elevation of ground water.)	50 feet or more, but less than 100 feet	(10 points)
	100 feet or more	(0 points)
Wellhead protection area: (Less than 200 feet from a private domestic	Yes	(20 points)
water source, or less than 1000 feet from all other water sources.)	No	(0 points)
water source, or less than 1000 feet from an other water sources.	Less than 200 Carl	
Distance to surface water: (horizontal distance to all wetlands, playas,	Less than 200 feet	(20 points)
irrigation canals, ditches, and perennial and ephemeral watercourses.)	200 feet or more, but less than 1000 feet	(10 points)
	1000 feet or more	(0 points)
	Ranking Score (Total Points)	0
f this is a pit closure: (1) Attach a diagram of the facility showing the pit	s relationship to other equipment and tanks. (2) Indic	cate disposal location: (check the onsite box if
our are burying in place) onsite M offsite If offsite, name of facility_		
emediation start date and end date. (4) Groundwater encountered: No [2]		-
5) Attach soil sample results and a diagram of sample locations and excava		
Additional Comments:		
See Attached Documentation	1	THE ROLL OF THE PARTY OF THE PA
See Attached Bootamentagion		on cons. Of
		Supra to trans
I hereby certify that the information above is true and complete to the best	of my knowledge and belief. I further certify that t	he above-described pit or below-grade tank
has been/will be constructed or closed according to NMOCD guideline	s 🔀, a general permit 🔲, or an (attached) alterna	tive OCD-approved plan .
Date: 11/01/2005	1	:
Printed Name/Title	ure Aff C. Sley	
Your certification and NMOCD approval of this application/closure does not otherwise endanger public health or the environment. Nor does it relieve to regulations.	ior remerigate operator or madring situate die contents	of the pit or tank contaminate ground water or my other federal, state, or local laws and/or
Approval: Printed Name/Title Printed Name/Title	Signature By B	Date JAN 1 6 2007

CLIENT: BP P	BLAG O. BOX 8		NEERING	•	112	LOCATION NO	: <u>81148</u>
CLIENT: BY P		505) 632		·, itiis ora	13	COCR NO:	10499
FIELD REPORT:	PIT CLC	SURE	VERIF	CATIO	N	PAGE No:	of
LOCATION: NAME: GCL		WELL#:	56 TYPE	: 5EP		DATE STARTED: _	2/10/03
QUAD/UNIT: O SEC: ZG TW	P: 28/2 RNG:	13W PM:	MW CUTY: 2	J ST: NM	 	DATE FINISHED: _	
QTR/FOOTAGE: 990'5		CONTE	RACTOR: L&L	- (DAN)		ENV!RONMENTAL SPECIALIST:	NV.
EXCAVATION APPROX)5 FT. × _	16 FT.	×_3FT	. DEEP. Cl	JBIC Y	ARDAGE:	30
DISPOSAL FACILITY:	ON-SIFE		REMEDIA	TION METH	OD:	LANDF	Fran
LAND USE: RANGE - NAVATO	JURT. LSE. L	EASE: _^	AUATO		FORM	MATION:	DK
FIELD NOTES & REMARKS	PIT LOCA	TED APPROX	MATELY 18	6 FT.	NID	E_ FROM	WELLHEAD.
DEPTH TO GROUNDWATER: 2100'	NEAREST WAT	ER SOURCE:	10001	_ NEAREST S	URFACE	WATER:	1000
NMOCD RANKING SCORE:	NMOCD TPH C	LOSURE STD:	5000 PI	РМ			
SOIL AND EXCAVATION I	DESCRIPTION	ON:		OVM CALIB.	GAS =	100 ppm	<u>RF = 0.52</u>
SOIL TYPE: SANDI SILTY SAND I	eu T / eu TV CI	AVICIAVI	OBAVEL / OTH			motor DATE: _	2/10/03
SOIL COLOR: LT. GRAY	TO BLACK			BEDROCK -			
COHESION (ALL OTHERS): NON COHES CONSISTENCY (NON COHESIVE SOILS)				COHESIVE			
PLASTICITY (CLAYS): NON PLASTIC / SI	LIGHTLY PLASTIC	/ COHESIVE / I	MEDIUM PLASTIC	HIGHLY PLASTI	С		
DENSITY (COHECIVE CLAYS & SILTS): S MOISTURE: DRY / SLIGHTLY MOIST (MO						((TOSED)
DISCOLORATION/STAINING OBSERVED	YES NO EXPLA	ANATION - &	BOTTOM HALF	OF SIDEWALL	5 + F	TO BOTTOM.	
HC ODOR DETECTED: YES NO EXPLAIN SAMPLE TYPE: GRAB/ COMPOSITE - # 0		N EXCAL	iation 4 e	um sampl	. € 、		
ADDITIONAL COMMENTS: STEEL	TANK TO						
BEDROCK PIT AC	IOR TO ARR	IVAL, OU	ucred same	it from:	50/L:	ABOVE BEDRO	ock.
700111		FIE	LD 418.1 CALC	ULATIONS			
SCALE SAMP. TIME	SAMP. ID	LAB NO.	WEIGHT (g)	mL FREON	DILUT	IONREADING	CALC. (ppm)
0 FT							
	<u> </u>				DI	T DOOLU	
PIT PERIMETER	3 12	0	VM		PI	T PROFIL	
ı		REA	DING	∧		1	A'
15		SAMPLE ID	FIELD HEADSPACE (ppm)		—	15	
,		(A) 6'	929	-			
A		3 @		T, [\supset		,
sanat >0		(Q)		6	刻 了3.	.5 [′] 3	15 T 2
Fr. 7				ť ', [<u> </u>
					1	BEDROCK	-7-/
P.O. SEP				-			
8.6.		LABSA	AMPLES			- Discourse	D/
- · ·	ــا	SAMPLE AN	ALYSIS TIME				
100 L			(80158) 1421 (80218) 11	-			
1 HEAD	_		PASSED)	-			
P.D. = PIT DEPRESSION; B.G. = BELOW GRA T.H. = TEST HOLE; ~ = APPROX.; T.B. = TAN	DE; B = BELOW			-			
TRAVEL NOTES: CALLOUT:	2/10/03-6	ATEMORN	ONSITE: _2	10/03-4	TETES?	<u> </u>	



EPA METHOD 8015 Modified Nonhalogenated Volatile Organics Total Petroleum Hydrocarbons

Client:	Blagg / BP	Project #:	94034-010
Sample ID:	1 @ 6'	Date Reported:	02-11-03
Laboratory Number:	24802	Date Sampled:	02-10-03
Chain of Custody No:	10499	Date Received:	02-11-03
Sample Matrix:	Soil	Date Extracted:	02-11-03
Preservative:	Cool	Date Analyzed:	02-11-03
Condition:	Cool and Intact	Analysis Requested:	8015 TPH

Parameter	Concentration (mg/Kg)	Det. Limit (mg/Kg)
Gasoline Range (C5 - C10)	2,790	0.2
Diesel Range (C10 - C28)	530	0.1
Total Petroleum Hydrocarbons	3,320	0.2

ND - Parameter not detected at the stated detection limit.

References:

Method 8015B, Nonhalogenated Volatile Organics, Test Methods for Evaluating Solid Waste,

SW-846, USEPA, December 1996.

Comments:

GCU #156 Separator Pit

Grab Sample.

Analyst

Review



EPA METHOD 8021 AROMATIC VOLATILE ORGANICS

Client:	Blagg / BP	Project #:	94034-010
Sample ID:	1 @ 6'	Date Reported:	02-11-03
Laboratory Number:	24802	Date Sampled:	02-10-03
Chain of Custody:	10499	Date Received:	02-11-03
Sample Matrix:	Soil	Date Analyzed:	02-11-03
Preservative:	Cool	Date Extracted:	02-11-03
Condition:	Cool & Intact	Analysis Requested:	BTEX

Parameter	Concentration (ug/Kg)	Det. Limit (ug/Kg)	
Panena	452	4.0	
Benzene	153	1.8	
Toluene	445	1.7	
Ethylbenzene	447	1.5	
p,m-Xylene	1,060	2.2	
o-Xylene	676	1.0	
Total BTEX	2,780		

ND - Parameter not detected at the stated detection limit.

Surrogate Recoveries:	Parameter	Percent Recovery
	Fluorobenzene	100 %
	1,4-difluorobenzene	100 %
	Bromochlorobenzene	100 %

References:

Method 5030B, Purge-and-Trap, Test Methods for Evaluating Solid Waste, SW-846, USEPA,

December 1996.

Method 8021B, Aromatic Volatile Organics, Test Methods for Evaluating Solid Waste, SW-846,

USEPA, December 1996.

Comments:

GCU #156 Separator Pit (

Grab Sample.

Analyst

Řeviev

P.O. BOX 87, BLC	INEERING, INC. DOMFIELD, NM 87413
FIELD REPORT: LANDFARM/COM	POST PILE CLOSURE VERIFICATION
QUAD/UNIT: SEC: ZE TWP: 282 RNG: 13W QTR/FOOTAGE: SWISE CONTRACTOR:	PM: Nm CNTY: 5T ST:Nm
SOIL REMEDIATION: REMEDIATION SYSTEM: LANDFARM LAND USE: RAWSE - NAVATO	APPROX. CUBIC YARDAGE: 40 LIFT DEPTH (ft): 1-1.5
FIELD NOTES & REMARKS: NMOCD RANKING SCOR	——————————————————————————————————————
SOIL TYPE: SAND / SILT / SILTY CLAY / C SOIL COLOR: COHESION (ALL OTHERS): KON COHESIVE / SLIGHTLY COHES CONSISTENCY (NON COHESIVE SOILS): COSD / FIRM / DEN PLASTICITY (CLAYS): NON PLASTIC / SLIGHTLY PLASTIC / BENSITY (COHESIVE CLAYS & SILTS): SOFT / FIRM / STIFF MOISTURE: DRY / SLIGHTLY MOIST / MOIST / WET / SATUR DISCOLORATION/STAINING OBSERVED: YES / NO EXPLANATION HC ODOR DETECTED: YES / NO EXPLANATION - SUGHTLY SAMPLING DEPTHS (LANDFARMS): 8 - 12 (INCHES) SAMPLE TYPE: GRAB / COMPOSID - # OF PTS. S ADDITIONAL COMMENTS:	PELL BROWN SIVE / COHESIVE / HIGHLY COHESIVE SE / VERY DENSE COHESIVE / MEDIUM PLASTIC / HIGHLY PLASTIC F / VERY STIFF / HARD RATED / SUPER SATURATED TION -
	B.1 CALCULATIONS (g) mL. FREON DILUTION READING CALC. ppm
SKETCH/SAMPLE LOCATIONS \$\(\bar{\rangle}\)	DVM CALIB. READ. 52.9 ppm CHECK
24	DVM CALIB. GAS = 100 ppm; RF = 0.52 TIME: 8:25 GD/pm DATE: 1/23/04
BERM	OVM RESULTS LAB SAMPLES SAMPLE FIELD HEADSPACE SAMPLE ANALYSIS TIME RESULTS 10 PID (PPM)
180 N76E FROM WELL HEAD	LF-1 Z6.7 LF-1 (8015B) 0930 379
TRAVEL NOTES: CALLOUT: NA	P.C 2/10/03 SCALE ONSITE: 1/23/04
revised: 07/16/01	bei1006A skd



EPA METHOD 8015 Modified Nonhalogenated Volatile Organics Total Petroleum Hydrocarbons

Client:	Blagg / BP	Project #:	94034-010
Sample ID:	LF-1	Date Reported:	01-26-04
Laboratory Number:	27606	Date Sampled:	01-23-04
Chain of Custody No:	11652	Date Received:	01-23-04
Sample Matrix:	Soil	Date Extracted:	01-23-04
Preservative:	Cool	Date Analyzed:	01-26-04
Condition:	Cool and Intact	Analysis Requested:	8015 TPH

Parameter	Concentration (mg/Kg)	Det. Limit (mg/Kg)
Gasoline Range (C5 - C10)	58.1	0.2
Diesel Range (C10 - C28)	321	0.1
Total Petroleum Hydrocarbons	379	0.2

ND - Parameter not detected at the stated detection limit.

References:

Method 8015B, Nonhalogenated Volatile Organics, Test Methods for Evaluating Solid Waste,

SW-846, USEPA, December 1996.

Comments:

GCU Lease #156 5 Pt. Composite Sample.

Misture of Wallers

Landra Rours