

**UNITED STATES  
DEPARTMENT OF THE INTERIOR  
BUREAU OF LAND MANAGEMENT**

Sundry Notices and Reports on Wells

2007 JAN 19 PM 2:26

1. **Type of Well**  
GAS

RECEIVED  
BLM  
210 FARMINGTON NM

2. **Name of Operator****CONOCOPHILLIPS**3. **Address & Phone No. of Operator**

PO Box 4289, Farmington, NM 87499 (505) 326-9700

4. **Location of Well, Footage, Sec., T, R, M**

Unit L (NWSW), 1840' FSL &amp; 990' FWL, Sec. 18, T28N, R7W, NMPM

5. **Lease Number**  
NMSF-078497-A  
6. **If Indian, All. or  
Tribe Name**

7. **Unit Agreement Name**

8. **San Juan 28-7 Unit/  
Well Name & Number**

9. **SJ 28-7 Unit #30  
API Well No.**

30-039-07411

10. **Field and Pool**

Blanco MV / Basin DK

11. **County and State**  
Rio Arriba Co., NM

**12. CHECK APPROPRIATE BOX TO INDICATE NATURE OF NOTICE, REPORT, OTHER DATA****Type of Submission****Type of Action**☐ Notice of Intent☐ Abandonment☐ Change of Plans☒ Other - deepen detail☒ Subsequent Report☒ Recompletion☐ New Construction☐ Plugging☐ Non-Routine Fracturing☐ Final Abandonment☐ Casing Repair☐ Water Shut off☐ Altering Casing☐ Conversion to Injection**13. Describe Proposed or Completed Operations**

12/4/06 RU BWWC. RIH w/guage ring & CCL. Tagged existing plug @ 4955'. Ran CCL from 4955' - 3700'. Dumped bailed 20 sx cement - 100' above existing plug. RIH w/CIBP & set @ 4762'. RD BWWC. 12/7/07 MIRUP 282. NU & test B section to 1800#. NU BOP. PT - OK. PT 7" casing on 12/10/06 to 1800# - OK. RIH w/whipstock. Milled window out of 7" casing - Top @ 4750'. Milled into formation @ 4759'. Milled window & reaming milled section TD @ 4762'. Circ. Start milling out window. Drilled and surveyed to 8001' (TD). TD reached 12/15/06. 12/16/06 RIH w/193 jts 4-1/2", 11.6# N-80 LTC casing and set @ 8001'. Established circ. RU to cement. Pumped preflush of 10 bbls gel water, 10 bbls KI water & 10 bbls gel water + 5 bbls water. Pumped 410 sx (574 cf - 102 bbls) 50/50 G POZ cement + 3% Gel, 0.1% antifoam agent, 0.25#/sx cellophane flakes, 0.25% uniflac-s, 0.15% dispersant, 0.1% retarder, 3.5#/sx phenoseal, 1#/sx gilsonite. Dropped plug and displaced w/10 bbls FW + 50 lbs sugar followed by 114 bbls FW. Bumped plug to 1700#. RD cementer. NU BOP & B section. Set slips and cut off casing. Installed cap.

12/28/06 Ran CBL, GR CCL, cased hole. TOC @ 3140 w/7" shoe @ 5032'. Good overlap.

PT will be conducted by the completion rig and results will be shown on the next report.

**14. I hereby certify that the foregoing is true and correct.**

Signed Patsy Clugston Title Sr. Regulatory Specialist Date 1/17/07

(This space for Federal or State Office use)

APPROVED BY \_\_\_\_\_ Title \_\_\_\_\_

CONDITION OF APPROVAL, if any:

Title 18 U.S.C. Section 1001, makes it a crime for any person knowingly and willfully to make any department or agency of the United States any false, fictitious or fraudulent statements or representations as to any matter within its jurisdiction

ACCEPTED FOR RECORD

JAN 22 2007

FARMINGTON FIELD OFFICE

NMOCD