

**UNITED STATES
DEPARTMENT OF THE INTERIOR
BUREAU OF LAND MANAGEMENT**

Sundry Notices and Reports on Wells

1. **Type of Well**
GAS

2. **Name of Operator**
ConocoPhillips

3. **Address & Phone No. of Operator**

PO Box 4289, Farmington, NM 87499 (505) 326-9700

4. **Location of Well, Footage, Sec., T, R, M**

Unit F (SENW), 1330' FNL & 2420' FWL, Section 16, T28N R7W, NMPM

5. **Lease Number**
SF-078497

6. **If Indian, All. or
Tribe Name**

7. **Unit Agreement Name**

8. **San Juan 28-7 Unit
Well Name & Number**

9. **San Juan 28-7 Unit #231F
API Well No.**

30-039-26974

10. **Field and Pool**

Blanco Mesa Verde/Basin DK

11. **County and State**
Rio Arriba Co., NM

12. CHECK APPROPRIATE BOX TO INDICATE NATURE OF NOTICE, REPORT, OTHER DATA

Type of Submission

Type of Action

☐ Notice of Intent

☐ Abandonment

☐ Change of Plans

☒ Other - Casing Report

☒ Subsequent Report

☐ Recompletion

☐ New Construction

☐ Plugging

☐ Non-Routine Fracturing

☐ Final Abandonment

☐ Casing Repair

☐ Water Shut off

☐ Altering Casing

☐ Conversion to Injection

13. Describe Proposed or Completed Operations

1/8/07 MIRU HP 283. NU BOP. PT 9 5/8" casing 1000 #/30 min- good test. RIH w/8 3/4" bit. D/O cement & ahead to 3425' intermediate. Circ Hole. RIH w/79 jts 20# J-55 ST & C casing, set @ 3413'. RU to cement. 1/13/07 Pumped pre-flush of 20 bbls Gel H2O/5 bbl spacer w/dye. Lead- Pumped 329sx(859 cf-153 bbls) Standard Class G Cement w/1#/sx Cemnet, .2% D046, 3% D079. Tail- Pumped 305sx(387 cf-69 bbls) 50:50 GPOZ Cement w/1% CaCl, 2% Bentonite, 5 #/sx Gilsonite Extender, .15% Dispersant, .10% D046, 1 #/bbl Cemnet. Dropped plug & displaced w/136 bbls H2O. Bump plug @ 11:00 am. Circ 101 bbls cement to surface. WOC.

1/13/07 PT 7" casing @ 1800 #/30 min- good test. RIH w/ 6 1/4" bit. D/O cement & ahead to 7414' (TD) TD reached on 1/16/07. Circ hole. RIH w/15 jts 4 1/2" 11.6# N-80 LT & C & 158 jts 4 1/2" 10.5# J-55 ST & C casing set @ 7413'. RU to cement. 1/17/07 Pump pre-flush of 10 bbls gel/ 10 bbls L64/10 bbls gel/5 bbls H2O, followed by 454 sx(636 cf- 113 bbls) 50:50 POZ Class G Cement w/.1% Retarder, 1 bb/sx Gilsonite, .25 #/sx Cello-flakes, .1% Antifoam, 3 % Bentonite. Dropped plug & displaced w/118 bbls H2O. Bump plug. ND BOP. RR @ 13:00 hrs on 1/17/07.

PT will be conducted by the completion rig. PT results & TOC will be shown on next report.

14. I hereby certify that the foregoing is true and correct.

Signed Tracey N. Monroe Tracey N. Monroe Title Regulatory Technician Date 1/23/07

(This space for Federal or State Office use)

APPROVED BY _____ Title _____ Date _____

CONDITION OF APPROVAL, if any:

Title 18 U.S.C. Section 1001, makes it a crime for any person knowingly and willfully to make any department or agency of the United States any false, fictitious or fraudulent statements or representations as to any matter within its jurisdiction.

ACCEPTED FOR RECORD

JAN 29 2007

NMOCD

FARMINGTON FIELD OFFICE