

UNITED STATES  
DEPARTMENT OF THE INTERIOR  
BUREAU OF LAND MANAGEMENT

SUBMIT IN DUPLICATE\*  
(See other instructions on reverse side)

RCVD FEB 9 '07  
OIL CONS. DIV.

FOR APPROVED  
OMB NO. 1004-0137

Expires: December 31, 1991

5. LEASE DESIGNATION AND SERIAL NO.

NMSF-078138

6. IF INDIAN ALLOTTEE OR TRIBE NAME

PH 3:47

7. UNIT AGREEMENT NAME

8. FARM OR LEASE NAME, WELL NO.

Morris 5S

9. API WELL NO.

30-045-33629 - 00C1

10. FIELD AND POOL, OR WILDCAT

Basin FC/Aztec PC

11. SEC., T., R., M., OR BLOCK AND SURVEY

OR AREA

Sec. 29 T30N R11W, NMPM

WELL COMPLETION OR RECOMPLETION REPORT AND LOG

1a. TYPE OF WELL: OIL WELL ☐ GAS WELL ☒ DRY ☐ Other ☐

b. TYPE OF COMPLETION: NEW WELL ☒ WORK OVER ☐ DEEP-EN ☐ PLUG BACK ☐ DIFF. RESVR ☐ Other ☐

2. NAME OF OPERATOR

BURLINGTON RESOURCES OIL & GAS COMPANY

3. ADDRESS AND TELEPHONE NO.

PO BOX 4289, Farmington, NM 87499 (505) 326-9700

4. LOCATION OF WELL (Report location clearly and in accordance with any State requirements)\*

At surface Unit F (SENW) 1950' FNL, 1645' FWL

At top prod. interval reported below Same as above

At total depth Same as above

14. PERMIT NO. DATE ISSUED

12. COUNTY OR PARISH

13. STATE

San Juan

New Mexico

15. DATE SPUDDED 8/14/06

16. DATE T.D. REACHED 8/21/06

17. DATE COMPL. (Ready to prod.) 1/23/07

18. ELEVATIONS (DF, RKB, RT, BR, ETC.)

GL 5801' KB 5813'

19. ELEV. CASINGHEAD

20. TOTAL DEPTH, MD & TVD 2285'

21. PLUG, BACK T.D., MD & TVD 2240'

22. IF MULTIPLE COMPL., HOW MANY\* 2

23. INTERVALS DRILLED BY

ROTARY TOOLS

CABLE TOOLS

25. WAS DIRECTIONAL SURVEY MADE

No

24. PRODUCTION INTERVAL (S) OF THIS COMPLETION-TOP, BOTTOM, NAME (MD AND TVD)\*

Basin Fruitland Coal 1869' - 2058'

26. TYPE ELECTRIC AND OTHER LOGS RUN

Cement bond Log w/Gamma Ray Casing Collars

27. WAS WELL CORED

No

28. CASING RECORD (Report all strings set in well)

CASING SIZE/GRADE	WEIGHT, LB./FT.	DEPTH SET (MD)	HOLE SIZE	TOP OF CEMENT, CEMENTING RECORD	AMOUNT PULLED
7"	20# J-55	159'	8 3/4"	surface; 34sx (54 cf)	3 bbls
4 1/2"	10.5# J-55	2284'	6 1/4"	TOC surface; 248sx (477cf)	15 bbls

29. LINER RECORD

SIZE	TOP (MD)	BOTTOM (MD)	SACKS CEMENT*	SCREEN (MD)	SIZE	DEPTH SET (MD)	PACKER SET (MD)
					2-3/8"	2133'	

30. TUBING RECORD

31. PERFORATION RECORD (Interval, size and number)

@2SPF  
2038' - 2058' = 40 holes  
@ 1 SPF  
1869' - 1872' = 4 holes  
1928' - 1936' = 9 holes  
1974' - 1981' = 8 holes  
Total holes = 61

32. ACID, SHOT, FRACTURE, CEMENT SQUEEZE, ETC.

1869' - 2058'	Pumped 210 gal B/D, Spearhead 500 gal 15% HCL, 3492 gal 25# Cross Linked pre-pad, 10503 gal 75Q, 25# Linear/foam, 24,445 Gal .25 to 2.5 ppg 20/40 Arizona Sand.

33. PRODUCTION

DATE FIRST PRODUCTION SI

PRODUCTION METHOD (Flowing, gas lift, pumping-size and type of pump)

Flowing

WELL STATUS (Producing or shut-in)

SI

DATE OF TEST 1/23/07

HOURS TESTED 1

CHOKE SIZE 1/2"

PROD'N FOR TEST PERIOD

OIL-BBL

GAS-MCF 2 mcf

WATER-BBL

GAS-OIL RATIO

FLOW. TUBING PRESS. CASING PRESSURE CALCULATED 24-HOUR RATE

SI 220#

SI 220#

50 mcf/d

OIL GRAVITY-API (CORR.)

34. DISPOSITION OF GAS (Sold, used for fuel, vented, etc.)

To be sold

TEST WITNESSED BY

35. LIST OF ATTACHMENTS

This is a Basin FC/Aztec PC well being DHC per order # 2311 AZ.

36. I hereby certify that the foregoing and attached information is complete and correct as determined from all available records

SIGNED *Mary V. Morrow* TITLE Regulatory Technician DATE 1/30/07

\*(See Instructions and Spaces for Additional Data on Reverse Side)

Title 18 U.S.C. Section 1001, makes it a crime for any person knowingly and willfully to make to any department of agency of the United States any false, fictitious or fraudulent statements or representations as to any matter within its jurisdiction.

NMOC

FEB 06 2007

J. Salyers

Ojo Alamo	638'	778'	White, cr-gr ss.	Ojo Alamo	638'
Kirtland	778'	1858'	Gry sh interbedded w/tight, gry, fine-gr ss.	Kirtland	778'
Fruitland	1858'	2086'	Dk gry-gry carb sh, coal, grn silts, light-med gry, tight, fine gr ss.	Fruitland	1858'
Pictured Cliffs	2086'		Bn-Gry, fine grn, tight ss.	Pic.Cliffs	2086'

1000

1000