

5000

DATA SHEET FOR DEEP GROUND BED CATHODIC PROTECTION WELLS
NORTHWESTERN NEW MEXICO
(Submit 3 copies to OCD Aztec Office)

30-039-25060

Operator UNOCAL Oil & Gas Division Location: Unit Sec. 1 Twp 26 Rng 7

Name of Well/Wells or Pipeline Serviced Rincon Unit 192E DK/GL

Elevation Completion Date 10/12/91 Total Depth 400' Land Type* F

Casing, Sizes, Types & Depths NONE

If Casing is cemented, show amounts & types used NONE

If Cement or Bentonite Plugs have been placed, show depths & amounts used

NONE

Depths & thickness of water zones with description of water when possible: Fresh, Clear,
Salty, Sulphur, Etc. Wet at 285'

Depths gas encountered: NONE

Type & amount of coke breeze used: Carbo 60-carbon coke = 2650 lbs.

Depths anodes placed: 395, 385, 375, 365 & 355' deep

Depths vent pipes placed: 0 to 400' deep

Vent pipe perforations: 280' to 400' = laser cut slots

Remarks: First ground bed installed at this location

RECEIVED
OCT 25 1991
OIL CON. DIV.
DIST. 3

If any of the above data is unavailable, please indicate so. Copies of all logs, including Drillers Log, Water Analyses & Well Bore Schematics should be submitted when available. Unplugged abandoned wells are to be included.

*Land Type may be shown: F-Federal; I-Indian; S-State; P-Fee.
If Federal or Indian, add Lease Number.

DATA SHEET FOR DEEP GROUND BED CATHODIC PROTECTION WELLS
NORTHWESTERN NEW MEXICO
(Submit 3 copies to OCD Aztec Office)

Operator UNOCAL Oil & Gas Division Location: Unit Sec. 1 Twp 26 Rng 7

Name of Well/Wells or Pipeline Serviced Rincon Unit 192E DK/GL

Elevation Completion Date 10/12/91 Total Depth 400' Land Type* F

Casing, Sizes, Types & Depths NONE

If Casing is cemented, show amounts & types used NONE

If Cement or Bentonite Plugs have been placed, show depths & amounts used

NONE

Depths & thickness of water zones with description of water when possible: Fresh, Clear,
Salty, Sulphur, Etc. Wet at 285'

Depths gas encountered: NONE

Type & amount of coke breeze used: Carbo 60-carbon coke = 2650 lbs.

Depths anodes placed: 395, 385, 375, 365 & 355' deep

Depths vent pipes placed: 0 to 400' deep

Vent pipe perforations: 280' to 400' = laser cut slots

Remarks: First ground bed installed at this location

RECEIVED
OCT 25 1991
OIL CON. DIV
DIST. 2

If any of the above data is unavailable, please indicate so. Copies of all logs, including Drillers Log, Water Analyses & Well Bore Schematics should be submitted when available. Unplugged abandoned wells are to be included.

*Land Type may be shown: F-Federal; I-Indian; S-State; P-Fee.
If Federal or Indian, add Lease Number.

CID # 751 00156 WELL NAME: Lincoln 192E LOCATION: 1-26-7 DATE: 10-12-91

TOTAL VOLTS: 12.36 TOTAL AMP: 7.7 OHM RESISTANCE: 1.61

												2.1d ANODE HEADLINE			
FEET	100 ANODE	ANODE NO.	FEET	100 ANODE	ANODE NO.	FEET	100 ANODE	ANODE NO.	FEET	100 ANODE	ANODE NO.	NO.	FEET	NO COKE	WITH COKE
5			185			365	2.1		545			1	400	3.1	7.7
10			190			310	2.3	L	550						
15			195			315	2.5		555						
20			200			300	2.7	d	560						
25			205			305	2.9		565						
30			210			390	2.9		570						
35			215			395	3.1		575						
40			220			400	3.1		580						
45			225			405	4.0		585						
50			230			410			590						
55			235			415			595						
60			240			420			600						
65			245			425			605						
70			250			430			610						
75			255			435			615						
80			260			440			620						
85			265			445			625						
90			270			450			630						
95			275			455			635						
100			280			460			640						
105			285			465			645						
110			290			470			650						
115			295			475			655						
120			300			480			660						
125			305			485			665						
130			310	1.6		490			670						
135			315	1.6		495			675						
140			320	1.9		500			680						
145			325	1.7		505			685						
150			330	1.9		510			690						
155			335	2.0		515			695						
160			340	2.1		520			700						
165			345	2.0		525			705						
170			350	1.9		530			710						
175			355	1.9		535			715						
180			360	2.0		540			720						

REMARKS:



MO-TE DRILLING, INC.

DAY Saturday

DRILLER <u>Bob B.</u>	LEFT TOWN	ARRIVED FIELD
HELPER <u>Jack J.</u>	LEFT FIELD	ARRIVED TOWN
HELPER <u>James P.</u>	TOTAL FOOTAGE TODAY	

RIG NO. 201 DATE 10-10-96 CLIENT Chico-Caf

BEGIN WORK ON HOLE NO. Lincon 192 E AT _____ FEET

BEGIN WORK ON HOLE NO. _____ AT _____ FEET

TIME		ACTIVITY
FROM	TO	
0	15	Sand & clay
15	25	brown sandstone
25	45	loose shale
45	80	grey sandstone
80	95	grey shale
95	105	sandstone (grey)
105	120	shale w/ sandstone streaks
120	295	Hard grey sandstone (w/ S&S)
295	360	Grey sandstone w/ shale streaks
360	390	Dark grey shale
390	400	grey sandstone.

BIT RECORD		
SIZE & MAKE	SERIAL NO.	FOOTAGE
1 - 6" special blades		
1 - 5 1/8" wood button bit		
CIRCULATION MATERIAL		
QUAN.	UNIT	MATERIAL

NO. OF LOADS OF WATER _____ SOURCE _____