

3368

85A = 30-039-25599
454 = 30-039-24234DATA SHEET FOR DEEP GROUND BED CATHODIC PROTECTION WELLS
NORTHWESTERN NEW MEXICOOperator Burlington Resources Location: Unit Sec. Twp Rng Name of Well/Wells or Pipeline Serviced San Juan 30-6 #454 + 85A
85A E 16-30-6 A 17-30-6Elevation Completion Date 3/3/97 Total Depth 345' Land Type Casing Strings, Sizes, Types & Depths 20' 8" PVC CasingIf Casing Strings are cemented, show amounts & types used yes - 4 BagsIf Cement or Bentonite Plugs have been placed, show depths & amounts used
NoneDepths & thickness of water zones with description of water: Fresh, Clear,
Salty, Sulphur, Etc. 150', 210' + 250' - FreshDepths gas encountered: NoneGround bed depth with type & amount of coke breeze used: 345'
3700 lbs Coreco SW coke breezeDepths anodes placed: 1-305, 280, 266, 260, 254, 246, 240, 234, 228, 196, 190, 175, 167, 161, 153Depths vent pipes placed: Surface to 345'Vent pipe perforations: Bottom to 150'Remarks:

RECEIVED

FEB 25 1998

OIL CON. DIV.
DIST. 3

If any of the above data is unavailable, please indicate so. Copies of all logs, including Drillers Log, Water Analyses & Well Bore Schematics should be submitted when available. Unplugged abandoned wells are to be included.

Land Type may be shown: F-Federal; I-Indian; S-State; P-Fee.
If Federal or Indian, add Lease Number.

TIERRA DYNAMIC COMPANY

Contractors of Cathodic Protection Services

ENTERED

CPS GROUND BED CONSTRUCTION WORKSHEET

3700# Coke

NPOL to assign
CPS# 9043-W to
another well
2057-W

SPR 2057W W Burlington Resources SS 30-6-#454 +85A
TOTAL VOLTS 3.14 AMPS 16.16 = OHMS 79 DATE 3-13-97 NAME Jack Ledbetter

REMARKS (notes for construction log)
Drill 11" hole 20' and set 20' of 8" casing and cement (4 Bags)
Drill 8" hole from 20' - 350' and set 15 anodes and 3700 lbs.

loresio SW coke breeze

AFE opened -

H₂O At 150', 210' + 250'

4 wells to protect

DEPTH	LOG ANODE	ANODE #	DEPTH	LOG ANODE	ANODE #	DEPTH	LOG ANODE	ANODE #	DEPTH	LOG ANODE	ANODE #
100	1.7		295	1.6		490			685		
105	1.8		300	1.7		495			690		
110	1.6		305	1.8	1	500			695		
115	1.3		310	1.3		505			700		
120	1.2		315	1.2		510			ANODE	DEPTH	NO
125	1.2		320	1.2		515			#	COKE	FULL
130	1.2		325	1.3		520			1	305	1.8
135	1.2		330	1.4		525			2	280	1.2
140	1.2		335	1.2		530			3	266	1.3
145	1.2		340	1.2		535			4	260	1.9
150	1.2		345	2.45	T.D.	540			5	254	1.6
155	1.7	15	350			545			6	246	1.4
160	1.7	14	355			550			7	240	1.7
165	1.6	13	360			555			8	234	1.5
170	1.4		365			560			9	228	1.5
175	1.2	12	370			565			10	196	1.1
180	1.9		375			570			11	190	1.1
185	1.6		380			575			12	175	1.2
190	1.1	10	385			580			13	169	1.5
195	1.0	10	390			585			14	161	1.6
200	1.9		395			590			15	155	1.6
205	1.6		400			595			16		
210	1.6		405			600			17		
215	1.4		410			605			18		
220	1.3		415			610			19		
225	1.9		420			615			20		
230	1.6	9	425			620			21		
235	1.5	8	430			625			22		
240	1.6	7	435			630			23		
245	1.0	6	440			635			24		
250	1.7		445			640			25		
255	1.5	5	450			645			26		
260	1.8	4	455			650			27		
265	1.3	3	460			655			28		
270	1.2		465			660			29		
275	1.4		470			665			30		
280	1.1	2	475			670					
285	1.7		480			675					
290	1.5		485			680					