

3361 30039-25619
9060W

DATA SHEET FOR DEEP GROUND BED CATHODIC PROTECTION WELLS
NORTHWESTERN NEW MEXICO

Operator Burlington Resources Location: Unit Sec. 29 Twp 30 Rng 6

Name of Well/Wells or Pipeline Serviced SS 30-6 #55A

Elevation Completion Date 5-15-97 Total Depth 340 Land Type P

Casing Strings, Sizes, Types & Depths 8" PVL

If Casing Strings are cemented, show amounts & types used 4 Bags

Portland cement

If Cement or Bentonite Plugs have been placed, show depths & amounts used

None

Depths & thickness of water zones with description of water: Fresh, Clear,

Salty, Sulphur, Etc. 100', Seep

Depths gas encountered: None

Ground bed depth with type & amount of coke breeze used: 340'

Loresco SW

Depths anodes placed: 325, 319, 313, 307, 301, 295, 289, 255

Depths vent pipes placed: 340'

Vent pipe perforations: Bottom 100 ft.

Remarks:

RECEIVED
FEB 25 1998

OIL CON. DIV.
DIST. 3

If any of the above data is unavailable, please indicate so. Copies of all logs, including Drillers Log, Water Analyses & Well Bore Schematics should be submitted when available. Unplugged abandoned wells are to be included.

Land Type may be shown: F-Federal; I-Indian; S-State; P-Fee.
If Federal or Indian, add Lease Number.

90606

FEE

TIERRA DYNAMIC COMPANY

DEEP WELL GROUNDED LOG DATA SHEET

ENTERED

COMPANY NAME: Burlington Resources

WELL NAME: 55 30-6 #55A

LEGAL LOCATION: NWSE 29-30-6

COUNTY: R.D. Arriba

CPS#

DATE: 5-15-97

TYPE OF COKE: Loresco SW

DEPTH: 340'

AMT. OF COKE BACKFILL: 2000 lbs

BIT SIZE: 7 7/8

VENT PIPE: 340

DRILLER NAME: Jack Ledbetter

PERF. PIPE: Bottom 100 Ft.

SIZE AND TYPE OF CASING: 8" PPK

ANODE AMT. & TYPE: 8 - Anotrc

BOULDER DRILLING:

DEPTH			DEPTH			DEPTH			COMPLETION INFORMATION:			
FT.	LOG	ANODE	FT.	LOG	ANODE	FT.	LOG	ANODE	WATER DEPTHS: 100' Seep			
									ISOLATION PLUGS:			
100	1.5		265	1.6		430						
105	1.6		270	1.3		435					OUTPUT	OUTPUT
110	1.6		275	1.1		440			ANODE#	DEPTH	NO COK	COKED
115	.9		280	1.1		445			1	325	1.8	4.2
120	.9		285	1.0		450			2	319	2.2	5.6
125	1.1		290	1.2	7	455			3	313	2.4	6.2
130	1.0		295	2.1	6	460			4	307	2.1	6.1
135	1.6		300	1.9	5	465			5	301	1.9	5.8
140	1.4		305	2.1		470			6	295	2.2	5.5
145	1.5		310	2.2	4	475			7	289	1.1	3.8
150	1.1		315	2.4	3	480			8	255	2.7	6.1
155	.8		320	2.0	2	485			9			
160	.8		325	1.8	1	490			10			
165	.8		330	1.4		495			11			
170	.8		335	3.35	T.D.	500			12			
175	.9		340			505			13			
180	1.0		345			510			14			
185	1.0		350			515			15			
190	1.1		355			520			16			
195	1.6		360			525			17			
200	1.9		365			530			18			
205	1.5		370			535			19			
210	1.6		375			540			20			
215	1.7		380			545			21			
220	2.1		385			550			22			
225	1.7		390			555			23			
230	2.3		395			560			24			
235	2.1		400			565			25			
240	2.7		405			570			26			
245	3.3		410			575			27			
250	3.0		415			580			28			
255	2.6	8	420			585			29			
260	1.9		425			590			30			
						595						

LOGGING VOLTS: 11.57

VOLTAGE SOURCE: Auto

TOTAL AMPS: 14.0

TOTAL G/B RESISTANCE: .82

REMARKS: