

3367 30-039-25675

DATA SHEET FOR DEEP GROUND BED CATHODIC PROTECTION WELLS
NORTHWESTERN NEW MEXICO

Operator Burlington Resources Location: Unit _____ Sec. 24 Twp 30 Rng 7

Name of Well/Wells or Pipeline Serviced SS 30-6 #76A

Elevation 6197 Completion Date 11-26-97 Total Depth 300 Land Type SF

Casing Strings, Sizes, Types & Depths 8" PVC X 20'

If Casing Strings are cemented, show amounts & types used 4 Bags Portland Cement

If Cement or Bentonite Plugs have been placed, show depths & amounts used NONE

Depths & thickness of water zones with description of water: Fresh, Clear, Salty, Sulphur, Etc. 100 S&P

Depths gas encountered: NONE

Ground bed depth with type & amount of coke breeze used: 300' 1800 lbs. Loresco SW

Depths anodes placed: 265, 258, 230, 223, 215, 209, 200, 185

Depths vent pipes placed: 300'

Vent pipe perforations: Bottom 140'

Remarks: _____

RECEIVED
FEB 25 1998

OIL CON. DIV.
DIST. 3

If any of the above data is unavailable, please indicate so. Copies of all logs, including Drillers Log, Water Analyses & Well Bore Schematics should be submitted when available. Unplugged abandoned wells are to be included.

Land Type may be shown: F-Federal; I-Indian; S-State; P-Fee.
If Federal or Indian, add Lease Number.

TIERRA DYNAMIC COMPANY

DEEP WELL GROUNDED LOG DATA SHEET

SF 079382

COMPANY NAME:

FID. 6197

WELL NAME 5530-6 #76A

LEGAL LOCATION: SEC 24-30-7

COUNTY: RIO Arriba

DATE: 11-21-97

TYPE OF COKE: Loresco SW

DEPTH: 300'

AMT. OF COKE BACKFILL: 1800 lbs.

BIT SIZE: 6 3/4

VENT PIPE: 300'

DRILLER NAME: Jack Ledbetter

PERF. PIPE: Bottom 140'

SIZE AND TYPE OF CASING: 8" PVC X 20'

ANODE AMT. & TYPE: Anotrc Duriton

BOULDER DRILLING: 0

DEPTH			DEPTH			DEPTH			COMPLETION INFORMATION:			
FT.	LOG	ANODE	FT.	LOG	ANODE	FT.	LOG	ANODE	WATER DEPTHS: 100 Serp			
									ISOLATION PLUGS:			
100			265	1.2		430						
105			270	1.1		435					OUTPUT	OUTPUT
110			275	1.0		440			ANODE#	DEPTH	NO COK	COKED
115			280	.7		445			1	265	1.2	3.9
120			285	.7		450			2	258	1.9	4.1
125			290	.8		455			3	230	1.2	3.5
130			295	1.0		460			4	223	2.1	3.6
135			300			465			5	215	2.0	4.2
140	1.3		305			470			6	209	2.2	7.0
145	1.4		310			475			7	200	2.4	6.9
150	1.9		315			480			8	✓ 185	2.4	5.6
155	1.9		320			485			9			
160	1.3		325			490			10			
165	1.2		330			495			11			
170	1.3		335			500			12			
175	1.3		340			505			13			
180	1.9		345			510			14			
185	2.6		350			515			15			
190	2.1		355			520			16			
195	1.5		360			525			17			
200	2.4		365			530			18			
205	2.5		370			535			19			
210	2.3		375			540			20			
215	2.2		380			545			21			
220	1.9		385			550			22			
225	2.1		390			555			23			
230	1.5		395			560			24			
235	1.7		400			565			25			
240	1.4		405			570			26			
245	1.6		410			575			27			
250	1.5		415			580			28			
255	1.6		420			585			29			
260	1.8		425			590			30			
						595						

LOGGING VOLTS: 11.38

VOLTAGE SOURCE: Auto

TOTAL AMPS: 12.2

TOTAL G/B RESISTANCE: 93

REMARKS: