

DATA SHEET FOR DEEP GROUND BED CATHODIC PROTECTION WELLS

MA-6

NORTHWESTERN NEW MEXICO
(Submit 3 Copies to OCD Aztec Office)

3584

Operator: BLACKWOOD & NICHOLS CO. Location: Unit D, Sec. 16, Twp 31N, Rng 7W.Name of Well/Wells or Pipeline Serviced NEBU 218 30-045-25709Elevation 6640' Completion Date 10-10-93 Total Depth 370' Land Type* Surface: P Mineral: E-178-1Casing, Sizes, Types & Depths 8-5/8" SCH 40 P.V.C. - 100', 7-7/8" Open HoleIf Casing is cemented, show amounts & types used 20 sks Portland Zia I-IIIf Cement or Bentonite Plugs have been placed, show depths & amounts used N/A

Depths & thickness of water zones with description of water when possible:

Fresh, Clear, Salty, Sulphur, Etc. No water.

RECEIVED

NOV 23 1993

Depths gas encountered: N/AOIL CON. DIV.
DIST. 3Type & amount of coke breeze used: Asbury Flo-Coke, 4,300#Depths anodes placed: 160' - 331' (10)Depths vent pipes placed: Bottom to 4' Above Ground LevelVent pipe perforations: Bottom - 240'Remarks: Groundbed located 182° N - 148' from NEBU 218 wellhead.

If any of the above data is unavailable, please indicate so. Copies of all logs, including Drillers Log, Water Analyses & Well Bore Schematics should be submitted when available. Unplugged abandoned wells are to be included.

*Land Type may be shown: F-Federal; I-Indian; S-State; P-Fee.
If Federal or Indian, add Lease Number.

Signed by: James K. AeblyTitle: Operations EngineerDate: 11/19/93

BLACKWOOD & NICHOLS
CATHODIC PROTECTANT
DRILLERS REPORT

P# MA-6 WELL# NEBU#218

S 16 T 31N R 2

DEPTH	STRATA	NOTES	DEPTH	STRATA	NOTES
5'					
10'					
15'	↑				
20'					
25'					
30'					
35'					
40'					
45'	H				
50'	L				
55'	H				
60'	H				
65'	S				
70'					
75'	L				
80'	A				
85'					
90'					
95'					
100'	✓				

DRILLER jeff martinez

INSPECTOR Joe Matyssek

CATHODIC GROUND BED DRILLERS REPORT

7A-6 WELL# N.E.B.U. # 218

Ps 16 T 31-7

[illegible]

BY Mark A. Spruill (Loftis) INSPECTOR MSM