

13- 30-039-20371
19- 30-039-20505

3860

DATA SHEET FOR DEEP GROUND BED CATHODIC PROTECTION WELLS
NORTHWESTERN NEW MEXICO

Operator Meridian Oil Inc. Location: Unit G Sec. 27 Twp 26 Rng 06

Name of Well/Wells or Pipeline Serviced _____

VRAUGHN #13 AND #19

Elevation 6670 Completion Date 7/15/93 Total Depth 466' Land Type F

Casing Strings, Sizes, Types & Depths 5/20 SET 59" OF 8" PVC CASING

NO GAS, WATER, OR BOULDERS WERE ENCOUNTERED DURING CASING

If Casing Strings are cemented, show amounts & types used Cemented

WITH 12 SACKS.

If Cement or Bentonite Plugs have been placed, show depths & amounts used

NONE

Depths & thickness of water zones with description of water: Fresh, Clear,

Salty, Sulphur, Etc. DAMP AT 90', MAJOR WATER VEIN AT 405'

WATER SAMPLE WAS TAKEN. WATER WAS FRESH.

Depths gas encountered: NONE

Ground bed depth with type & amount of coke breeze used: 466' DEPTH.

USED 70 BAGS OF ASBURY, AND 32 BAGS OF LOTESCO (6700#)

Depths anodes placed: 400', 390', 370', 360', 351', 325', 315', 290', 230', 220', 165', 150', 140', 130', 1120'

Depths vent pipes placed: 466' TO SURFACE.

Vent pipe perforations: BOTTOM 360'.

Remarks: _____

RECEIVED

JAN 31 1994

OIL CON. I
DIST 2

If any of the above data is unavailable, please indicate so. Copies of all logs, including Drillers Log, Water Analyses & Well Bore Schematics should be submitted when available. Unplugged abandoned wells are to be included.

Land Type may be shown: F-Federal; I-Indian; S-State; P-Fee.

If Federal or Indian, add Lease Number.