

292 = 30-039-22202
163 = 30-039-20309

3640

DATA SHEET FOR DEEP GROUND BED CATHODIC PROTECTION WELLS
NORTHWESTERN NEW MEXICO

Operator Meridian Oil Inc. Location: Unit H Sec. 10 Twp 25 Rng 06

Name of Well/Wells or Pipeline Serviced _____

CANYON Largo UNITS #292 AND #163

Elevation 6743 Completion Date 7/21/93 Total Depth 430' Land Type F

Casing Strings, Sizes, Types & Depths 6/20 SET 59' OF 8" PVC CASING.

NO GAS, WATER, OR BOULDERS WERE ENCOUNTERED DURING CASING.

If Casing Strings are cemented, show amounts & types used Cemented

WITH 12 SACKS.

If Cement or Bentonite Plugs have been placed, show depths & amounts used

NONE

Depths & thickness of water zones with description of water: Fresh, Clear,
Salty, Sulphur, Etc. HIT A FRESH WATER Seep AT 98', AND
More AT 425'.

Depths gas encountered: NONE

Ground bed depth with type & amount of coke breeze used: 430' DEPTH.

USED 120 SACKS OF Asbury (6000#)

Depths anodes placed: 370', 359', 353', 347', 329', 323', 317', 264', 258', 220', 209', 201', 156', 138', 113'.

Depths vent pipes placed: SURFACE TO 430'

Vent pipe perforations: BOTTOM 320'.

Remarks: _____

RECEIVED

JAN 31 1994

OIL CON. DIV.,
DIST. 2

If any of the above data is unavailable, please indicate so. Copies of all logs, including Drillers Log, Water Analyses & Well Bore Schematics should be submitted when available. Unplugged abandoned wells are to be included.

Land Type may be shown: F-Federal; I-Indian; S-State; P-Fee.
If Federal or Indian, add Lease Number.