

3868

DATA SHEET FOR DEEP GROUND BED CATHODIC PROTECTION WELLS
NORTHWESTERN NEW MEXICO

30-039-23790

Operator Meridian Oil Inc. Location: Unit M Sec. 28 Twp 26 Rng 06

Name of Well/Wells or Pipeline Serviced _____

Vaughn #27

Elevation 6248 Completion Date _____ Total Depth _____ Land Type F

Casing Strings, Sizes, Types & Depths 5/13 Set 98' of 8" PVC Casing

NO GAS, WATER, OR BOULDERS WERE ENCOUNTERED DURING CASING. ^{AND 120'} ~~2nd CAS.~~

If Casing Strings are cemented, show amounts & types used Cemented 1st CASING

WITH 51 SACKS. 2nd CASING CEMENTED WITH 38 BAGS CEMENT

If Cement or Bentonite Plugs have been placed, show depths & amounts used

NO

Depths & thickness of water zones with description of water: Fresh, Clear,
Salty, Sulphur, Etc. AT CASING 120' NO SAMPLE

Depths gas encountered: NO

Ground bed depth with type & amount of coke breeze used: 487' deep with
6700 lbs of Asbury 218-R

Depths anodes placed: 455, 445, 435, 425, 415, 405, 320, 310, 260, 250, 215, 205, 195, 185, 175

Depths vent pipes placed: 487'

Vent pipe perforations: BOTTOM 350'

Remarks: _____

RECEIVED

JUN 31 1994

OIL CON. DIV.

057

If any of the above data is unavailable, please indicate so. Copies of all logs, including Drillers Log, Water Analyses & Well Bore Schematics should be submitted when available. Unplugged abandoned wells are to be included.

Land Type may be shown: F-Federal; I-Indian; S-State; P-Fee.
If Federal or Indian, add Lease Number.