

1 = 30-045-09804
251 = 30-045-26937
E2 = 30-045-26425

3551

DATA SHEET FOR DEEP GROUND BED CATHODIC PROTECTION WELLS
NORTHWESTERN NEW MEXICO
(Submit 3 copies to OCD Aztec Office)

Operator MERIDIAN OIL Location: Unit NE Sec. 4 Twp 30 Rng 9

Name of Well/Wells or Pipeline Serviced RIDDLE #1, #251, E #2

cps 2089w

Elevation N/A Completion Date 11/10/61 Total Depth 180' Land Type* N/A

Casing, Sizes, Types & Depths N/A

If Casing is cemented, show amounts & types used N/A

If Cement or Bentonite Plugs have been placed, show depths & amounts use
N/A

Depths & thickness of water zones with description of water when possible
Fresh, Clear, Salty, Sulphur, Etc. N/A

Depths gas encountered: N/A

Type & amount of coke breeze used: 1156 lbs.

Depths anodes placed: 160', 145', 127', 117', 110'


Depths vent pipes placed: N/A

Vent pipe perforations: N/A

Remarks: gb #1 LOST 15' HOLE

If any of the above data is unavailable, please indicate so. Copies of all logs, including Drillers Log, Water Analyses & Well Bore Schematics should be submitted when available. Unplugged abandoned wells are to be included.

*Land Type may be shown: F-Federal; I-Indian; S-State; P-Fee.
If Federal or Indian, add Lease Number.



SAN JUAN DIVISION
WELL CASING CATHODIC PROTECTION
DAILY CONSTRUCTION
PROGRESS REPORT

DATE 11-10-61 41W 2089W

WELL NAME - Riddle #1 WORK ORDER NO. 184-20051-50-10

NUMBER AND DEPTH OF HOLES: #1 180', #2 , #3 , #4 , #5 .

DEPTH OF EACH ANODE: #1 160', #2 145', #3 127, #4 117, #5 110, #6 , #7
#8 , #9 , #10 .

ANODE RESISTANCES: #1 2.9, #2 3.3, #3 3.0, #4 2.7, #5 2.8, #6 , #7
#8 , #9 , #10 .

TOTAL CIRCUIT RESISTANCE: 1.1 OHMS.

DRILLING LOG: (ATTACH HERETO)

AMOUNT OF COKE BREEZE PLACED IN EACH HOLE: #1 1156/65 7# / 41 #2 , #3
#4 , #5 .

ANY DIFFICULTIES ENCOUNTERED IN DRILLING:

ROCKS-

LOST CIRCULATION-

CASING INSTALLED-

DATE ALL CONSTRUCTION COMPLETED .

REMARKS:

Lost 15' hole

SIGNED: Toolpusher _____ Company Supervisor _____

1