

3274

**DATA SHEET FOR DEEP GROUND BED CATHODIC PROTECTION WELLS
NORTHWESTERN NEW MEXICO
(Submit 3 copies to OCD Aztec Office)**

Rincon Unit Well 91 30-039-06627

Operator: UNOCAL -- Bloomfield, NM Location: Unit D Sec. 11 Twp. 26N Rng. 7W

Name of Well/Wells or Pipeline Serviced: RINCON UNIT WELL: 91 PC

Elevation: 6731 DF Completion Date: 10/25/95 Total Depth: 300 Land Type* F

Casing, Sizes, Types & Depths: NONE

If Casing is cemented, show amounts & types used: NONE

If Cement or Bentonite Plugs have been placed, show depths & amounts used: NONE

Depths & thickness of water zones with description of water when possible: _____

WET SANDSTONE AT 120'

Fresh, Clear, Salty, Sulfur, Etc.: NONE

Depths gas encountered: NONE

Type & amount of coke breeze used: 2500 LBS., SWB METALURGICAL PETROLEUM COKE

Depths anodes placed: 135' 145' 155' 165' 175' 185' 195' 205' 215' 225'

Depths vent pipes placed: 0' -- 300', 1" PVC

Vent pipe perforations: 1/8" PERFORATIONS FROM 100' TO 300'

Remarks: SECOND GROUND BED INSTALLED ON THIS LOCATION.

If any of the above data is unavailable, please indicate so. Copies of all logs, including Drillers Log, Water Analysis & Well Bore Schematics should be submitted when available. Unplugged abandoned wells are to be included.

*Land Type may be shown: F--Federal; I--Indian; S--State; P--Fee
If Federal or Indian, add Lease Number.

RECEIVED
FEB - 5 1996
OIL CON. DIV.
DIST. 3

019 748 7701 141



SCALE: NONE

UNOCAL

COMPANY: Amocal DATE: 10-25-95
WELL: Rincon 91 PIPELINE:
LOCATION: 14 14 SEC. 11-26-7 STATE: N.M.
GROUNDBED: DEPTH: 300' DIAMETER: 6 3/4" BACKFILL: Metallurgical ANODES TYPE: Durachlor 51

DEPTH FT.	DRILLERS LOG	ANODE LOG			ANODE DEPTH	REMARKS
		I Logged	I Coked	R		
20	Shale					
30	Sand Stone					
40	Sand Stone					
50	Sand Stone					
60	Sand Stone					
70	Sand Stone					
80	Sand Stone					
90	Shale					
100	Shale					
110	Sand Stone					
120	Sand Stone					Wet
130	Shale	1.4	3.4		135'	
140	Shale	1.1	3.6		145'	
150	Shale	1.2	4.4		155'	
160	Shale	1.5	4.8		165'	
170	Shale	1.1	3.8		175'	
180	Shale	1.4	4.5		185'	
190	Shale	1.4	4.3		195'	
200	Shale	1.6	4.6		205'	
210	Shale	1.5	4.2		215'	
220	Shale	1.7	5.0		225'	
230	Sandy Shale	1.1				
240	Sand Stone	.2				
250	Sand Stone	.2				
260	Sand Stone	.1				
270	Sand Stone	.1				
280	Sand Stone	.3				
290	Sand Stone	.3				
300	Sand Stone	.3				
310						
320						
330						
340						
350						

NOTES:

POWER SOURCE: Battery VOLTS: 9.67
INDICATE WATER ZONE DEPTHS 120'
CASING RUN: YES / ☒ NO TYPE: _____ DEPTH: _____ CEMENTED: YES / ☒ NO
ISOLATION PLUGS SET: YES / ☒ NO IF SO, WHERE: _____
TOTAL: AMPS 12.1 RESISTANCE: 799

ON UNIT

