

3279

**DATA SHEET FOR DEEP GROUND BED CATHODIC PROTECTION WELLS
NORTHWESTERN NEW MEXICO**

(Submit 3 copies to OCD Aztec Office)

Rincon Unit well #55
30-039-06741

Rincon Unit well #201
30-039-20774

Rincon Unit well #294
30-039-24732

Operator: UNOCAL – Bloomfield, NM Location: Unit G Sec. 02 Twp. 26N Rng. 7W

Name of Well/Wells or Pipeline Serviced: RINCON UNIT WELLS: 201 DK; 294 FC; 55 PC

Elevation: 6611 GR Completion Date: 10/25/95 Total Depth: 300' Land Type* S

Casing, Sizes, Types & Depths: NONE

If Casing is cemented, show amounts & types used: NONE

If Cement or Bentonite Plugs have been placed, show depths & amounts used: NONE

Depths & thickness of water zones with description of water when possible: _____

WET SANDSTONE AT 140'

Fresh, Clear, Salty, Sulfur, Etc.: NONE

Depths gas encountered: NONE

Type & amount of coke breeze used: 2500 LBS., SWB METALURGICAL PETROLEUM COKE

Depths anodes placed: 150' 160' 170' 180' 190' 200' 210' 220' 230' 240' 250' 290'

Depths vent pipes placed: 0' – 300', 1" PVC

Vent pipe perforations: 1/8" PERFORATIONS FROM 100' TO 300'

Remarks: SECOND GROUND BED INSTALLED ON THIS LOCATION.

If any of the above data is unavailable, please indicate so. Copies of all logs, including Drillers Log, Water Analysis & Well Bore Schematics should be submitted when available. Unplugged abandoned wells are to be included.

*Land Type may be shown: F–Federal; I–Indian; S–State; P–Fee
If Federal or Indian, add Lease Number.

RECEIVED
FEB - 5 1996

OIL CON. DIV.
DIST. 3

Roto

#55

PT

1869' NEG

Roto

← PIPELINE CROSSING

METER NO. 25

25

new Ground Bed

#201

PT

3

1290' NEG

PT

#56

POS. 25'
NEG. 114' WELL #201
NEG. 1869' WELL #55
NEG. 1290' WELL #56



Cathodic Protection Services

A LUKEN COMPANY

RINCON UNIT #55
" " #201
" " #56

DES. PB
CR. SK
SCALE NEG

CR.
APP.
DATE 12/21/89

DWG. NO. 00027-15
REV.

NO.

REVISION

DATE

COMPANY: Unocal DATE: 10-25-95
 WELL: Rincon 201; 294, 55
 LOCATION: 14 14 SEC. 2-26-7 PIPELINE:
 STATE: N.M.
 GROUND BED: DEPTH: 300 DIAMETER: 6 3/4" BACKFILL: Metallurgical ANODES TYPE: Durachlor 51

DEPTH FT.	DRILLERS LOG	ANODE LOG			ANODE DEPTH	REMARKS
		Logged	Coked	R		
20	shale					
30	sand stone					
40	sand stone					
50	sand stone					
60	shale					
70	shale					
80	sand stone					
90	sand stone					
100	sand stone					
110	sandy shale					
120	sandy shale					
130	sand stone					
140	sand stone					Wet
150	sandy shale	1.0	2.7		150'	
160	shale	1.5	3.5		160'	
170	shale	2.2	3.7		170'	
180	shale	1.5	2.9		180'	
190	sandy shale	.6	1.7		190'	
200	sandy shale	.4	2.5		200'	
210	shale	1.1	2.5		210'	
220	shale	1.0	1.9		220'	
230	sand stone	.2	1.0		230'	
240	sand stone	.2	.7		240'	
250	sand stone	.2	.4		250'	
260	sand stone	.2				
270	sand stone	.1				
280	sand stone	.1				
290	sand shale	.4	.6		290'	
300	sandy shale	.4				
310						
320						
330						
340						
350						

NOTES:

POWER SOURCE: Battery VOLTS: 8.85
 INDICATE WATER ZONE DEPTHS 140'
 CASING RUN: YES / ☒ NO TYPE: _____ DEPTH: _____ CEMENTED: YES / ☒ NO
 ISOLATION PLUGS SET: YES / ☒ NO IF SO, WHERE: _____
 TOTAL: AMPS 7.95 RESISTANCE: 1.120

CON UNIT

