

3277

**DATA SHEET FOR DEEP GROUND BED CATHODIC PROTECTION WELLS
NORTHWESTERN NEW MEXICO**

(Submit 3 copies to OCD Aztec Office)

Rincon Unit Well #52
30-039-06986

Rincon Unit Well #113
30-039-06985

Rincon Unit Well #175
30-039-06983

Operator: UNOCAL - Bloomfield, NM Location: Unit H Sec. 20 Twp. 27N Rng. 6W

Name of Well/Wells or Pipeline Serviced: RINCON UNIT WELLS: 113 PC; 175 DK; 52 PC

Elevation: 6589 DF Completion Date: 10/17/95 Total Depth: 340' Land Type* F

Casing, Sizes, Types & Depths: NONE

If Casing is cemented, show amounts & types used: NONE

If Cement or Bentonite Plugs have been placed, show depths & amounts used: NONE

Depths & thickness of water zones with description of water when possible: _____

WET SANDSTONE AT 120'

Fresh, Clear, Salty, Sulfur, Etc.: NONE

Depths gas encountered: NONE

Type & amount of coke breeze used: 2500 LBS., SWB METALURGICAL PETROLEUM COKE

Depths anodes placed: 145' 155' 165' 200' 210' 220' 230' 240' 310' 320'

Depths vent pipes placed: 0' - 340', 1" PVC

Vent pipe perforations: 1/8" PERFORATIONS FROM 100' TO 300'

Remarks: THIRD GROUND BED INSTALLED ON THIS LOCATION.

If any of the above data is unavailable, please indicate so. Copies of all logs, including Drillers Log, Water Analysis & Well Bore Schematics should be submitted when available. Unplugged abandoned wells are to be included.

*Land Type may be shown: F-Federal; I-Indian; S-State; P-Fee
If Federal or Indian, add Lease Number.

RECEIVED
FEB - 5 1996
OIL CON. DIV.
DIST. 3

#12



new Ground Bed
10 ANODES
GND BED

245'

2 #8 CABLES

45V-30A
RECT.

225'

#52

#113

#175

METER BOX
FLO-LINE RETURN

NE20-27-6

CATHODIC PROTECTION

EL PASO NATURAL GAS COMPANY CPS-6901

RINCON #52 & #113 & #175

SCALE NONE DATE 5-20-65 No.

DRAWN BY G. S. H. CHECKED BY

12

COMPANY: Unocal DATE: 10-17-95
 WELL: Rincon Unit 113, 175, 52 PIPELINE:
 LOCATION: 14 14 SEC. 20-27.6 STATE: N.M.
 GROUND BED: DEPTH: 340' DIAMETER: 6 3/4" BACKFILL: Metallurgen ANODES TYPE: Durath 51

DEPTH FT.	DRILLERS LOG	ANODE LOG			ANODE DEPTH	REMARKS
		Logged	Coked	R		
20	Sand Stone					
30	Sand Stone					
40	Sand Stone					
50	Sand Stone					
60	Sand Stone					
70	Sand Stone					
80	Shale					
90	Shale					
100	Shale					
110	Shale					
120	Sand Stone	.8				Wet
130	Sand Stone	.2				
140	Shale	1.3	2.9		145'	
150	Shale	1.2	2.8		155'	
160	Sandy Shale	.8	1.9		165'	
170	Sand Stone	.1				
180	Sand Stone	.2				
190	Sand Stone	.5				
200	Sandy Shale	1.0	2.0		200'	
210	Sandy Shale	1.0	2.0		210'	
220	Sandy Shale	.8	1.5		220'	
230	Sandy Shale	1.0	1.8		230'	
240	Sandy Shale	1.3	2.8		240'	
250	Sand Stone	.5				
260	Sand Stone	.4				
270	Sand Stone	.3				
280	Sand Stone	.4				
290	Sand Stone	.3				
300	Sand Stone	.5				
310	Sandy Shale	.8	1.5		310'	
320	Sandy Shale	.8	1.0		320'	
330	Sand Stone	.4				
340	Sand Stone	.4				
350						

NOTES:

POWER SOURCE: Battery VOLTS: 8.86
 INDICATE WATER ZONE DEPTHS 120' wet sand stone
 CASING RUN: YES / ☒ NO TYPE: _____ DEPTH: _____ CEMENTED: YES / ☒ NO
 ISOLATION PLUGS SET: YES / ☒ NO IF SO, WHERE: _____
 TOTAL: AMPS 7.2 RESISTANCE: 1.231

