

3233

**DATA SHEET FOR DEEP GROUND BED CATHODIC PROTECTION WELLS
NORTHWESTERN NEW MEXICO**
(Submit 3 copies to OCD Aztec Office)

30-045-11621

Operator EL PASO Field Services Location: Unit N Sec. 14 Twp 28 Rng 12

Name of Well/Wells or Pipeline Served GALLEGOS CANYON UNIT 216

#75365

Elevation _____ Completion Date 5-8-97 Total Depth _____ Land Type * SF 078828-A

Casing, Sizes, Types & Depths 8 5/8" P.V.C.

If Casing is cemented, show amounts & types used 6 Bags - 2.14 Type 1 & 2.

If Cement or Bentonite Plugs have been placed, show depths & amounts used _____

Depths & thickness of water zones with description of water when possible:

Fresh, Clear, Salty, Sulphur, Etc. wet @ 50' more @ 110

RECEIVED
OCT 14 1997

OIL CON. DIV.
DIST. 3

Depths gas encountered: _____

Type & amount of coke breeze used: oresco 5.0. 5200 lbs

Depths anodes placed: 14.5 - 340

Depths vent pipes placed: 340 -

Vent pipe perforations: 200

Remarks: _____

If any of the above data is unavailable, please indicate so. Copies of all logs, including Drillers Log, Water Analyses & Well Bore Schematics should be submitted when available. Unplugged abandoned wells are to be included.

* Land Type may be shown: F-Federal; I-Indian; S-State; P-Fee.
If Federal or Indian, add Lease Number.

DEEP WELL GROUND BED DATA

DATE May 8, 1997COMPANY EPFS/AmocoCOUNTY San Juan STATE NMCONTRACT NO. FC-96-1000UNIT NO. 75365LOCATION Gallegos CU #216GROUNDBED: DEPTH 400 Ft., DIA. 7 7/8 In., ANODES (15) 2 x 60 SHA-2CASING: SIZE 8 In., DEPTH 20 Ft.

DEPTH FT.	DRILLER'S LOG	RESISTIVITY OHMS	AMPS	ANODE NUMBER	DEPTH TO ANODE TOP	BEFORE COKE	AFTER COKE
5	Casing						
10	"						
15	"						
20	Sand						
25	"						
30	"						
35	"						
40	"						
45	"						
50	"		1.1				
55	"		1.5				
60	"		1.4				
65	"		1.2				
70	"		1.2				
75	"		1.4				
80	"		1.2				
85	"		1.2				
90	"		1.1				
95	"		1.1				
100	"		1.2				
105	"		1.0				
110	"		1.1				
115	"		1.0				
120	Blue Sand		1.0				
125	"		0.9				
130	"		0.9				
135	"		1.0				
140	Shale		1.0				
145	"		1.1				
150	"		1.3	15	145	1.5	5.9
155	"		1.6				
160	"		1.7	14	153	2.0	7.2
165	"		1.6	13	161	2.1	7.2
170	"		1.3				
175	"		1.1	12	169	1.2	5.3
180	"		1.0				
185	"		1.0				
190	"		1.0				
195	"		1.2	11	191	1.6	6.2
200	"		1.5				
205	"		1.4	10	199	1.6	6.8
210	"		1.6	9	207	1.9	7.5
215	"		1.3				
220	"		1.8	8	215	1.9	7.6
225	"		1.7				
230	"		1.7	7	223	1.8	7.4
235	"		1.7	6	231	1.8	7.2
240	Shale		1.7	5	239	1.8	7.4

COMPANY EPFS/AmocoDATE May 8, 1997LOCATION Gallegos CU #216UNIT NO. 75365

DEPTH Ft	DRILLER'S LOG	RESISTIVITY OHMS	AMPS	ANODE NUMBER	DEPTH TO ANODE TOP	BEFORE COKE	AFTER COKE
245	Shale		1.4	4	247	1.6	6.4
250	"		1.3				
255	"		1.0	3	255	1.1	5.2
260	"		1.0				
265	"		1.0				
270	"		1.0				
275	"		1.0				
280	Sandstone		1.0				
285	"		0.9				
290	"		0.9				
295	"		0.8				
300	"		0.9				
305	"		0.8				
310	"		0.8				
315	"		0.7				
320	"		0.7				
325	"		0.7				
330	"		0.7	2	332	1.1	4.2
335	"		1.2				
340	"		1.6	1	340	1.6	4.6
345	"		0.9				
350	"		0.7				
355	"		0.6				
360	"		0.6				
365	"		0.7				
370	"		0.6				
375	"		0.5				
380	"		0.6				
385	"		0.7				
390	"						
395	"						
400	Sandstone						
405							
410							
415							
420							
425							
430							
435							
440							
445							
450							
455							
460							
465							
470							
475							
480							
485							
490							
495							
500							
505							
510							