

3264

**OCD CATHODIC PROTECTION DEEPWELL GROUND BED REPORT
DATA SHEET: NORTHWESTERN NEW MEXICO**

SUBMIT 2 COPIES TO O.C.D. AZTEC OFFI

OPERATOR: PHILLIPS PETROLEUM CO
FARMINGTON, NM 87401
PHONE: 599-3400

RECEIVED
FEB 10 1998

OIL CON. DIV.
DIST. 3

LOCATION INFORMATION

WELLNAME OR PIPELINE SERVED: GOBERNADOR #6 MV/PC → 30-039-224 DIST. 3

ADDITIONAL WELLS: N/A

LEGAL LOCATION H 15 29 5

DATE OF INSTALLATION: 4/21/97

LEASE NUMBER: NA

TYPE OF LEASE: FEDERAL

PPCO RECTIFIER NUMBER: FM-503

TOTAL G/B DEPT 420

GROUND BED INFORMATION

CASING SIZE: 8 **CASING TYPE:** PVC **CASING DEPTH:** 20

CASING CEMENT: YES

TOP ANODE: 260 **BOTTOM ANODE** 405

INDIVIDUAL ANODE DEPTHS 260,270,330,340,350,360,370,380,395,405

AMOUNT OF COKE: 2800

WATER INFORMATION

WATER DEPTH (1): NONE

WATER DEPTH (2):

CEMENT PLUGS: NO

OTHER INFORMATION

GAS DEPTH: NA

VENT PIPE DEPTH 413

TOP OF VENT PERFORATIONS: 213

REMARKS: NEW G/B DRILLED 4/21/97

IF ANY OF THE ABOVE DATA IS UNAVAILABLE, PLEASE INDICATE SO. COPIES OF ALL LOGS, INCLUDING DRILLERS LOGS, WATER ANALYSIS, AND WELL BORE SCHEMATICS SHOULD BE SUBMITTED WHEN AVAILABLE. UNPLUGGED UNABANDONED WELLS ARE TO BE INCLUDED.

*- LAND TYPE MAY BE SHOWN: F-FEDERAL; I-INDIAN; S-STATE; P-FEE
IF FEDERAL OR INDIAN, ADD LEASE NUMBER.

FIN 503

PPCO.GROUNDBED LOG

PHILLIPS PERTROLEUM CO.			GROUNDBED LOG—DATA SHEET		
DEEP WELL CATHODIC PROTECTION GROUNDBED					
LOCATION NAME:		Gobernador #6		DATE: 4-21-97	
LEGAL LOCATION:		H/15 29-5		SIZE AND TYPE OF CASING: 8" PVC casing	
PPCO ID NO. (FM NO.):		503		DEPTH OF CASING: 20'	
TOTAL DEPTH:		420		TYPE OF COKE BACKFILL: PETROLEUM	
DIAMETER:		16 1/8		BRAND NAME OF BACKFILL: LORESCO SW	
CITY:		Rio Arriba		BRAND AND TYPE OF ANODES: ANODE 60" SILICON	

DEPTH			DEPTH			DEPTH			COMPLETION INFORMATION:			
FT.	LOG	ANODE	FT.	LOG	ANODE	FT.	LOG	ANODE	WATER DEPTHS: — — —			
									ISOLATION PLUGS:			
									ANODE#	DEPTH	OUTPUT NO COKE	OUTPUT COKED
100			265	3.0		435						
105			270	2.8	9	440						
110			275	1.9		445			1	4105	2.1	3.3
115			280	1.5		450			2	395	1.5	3.4
120			285	1.4		455			3	370	2.2	5.4
125			290	1.2		460			4	350	2.5	6.1
130			300	.8		465			5	330	1.9	6.0
135			305	.6		470			6	310	2.2	6.1
140			310	.6		475			7	290	2.6	6.3
145			315	.7		480			8	270	2.4	6.3
150			320	.9		485			9	250	2.9	6.3
155			325	1.0		490			10	230	3.3	6.1
160			330	1.8	2	495			11			
165			335	2.7		500			12			
170			340	2.4	7	505			13			
175			345	2.3		510			14			
180			350	2.2	6	515			15			
185			355	2.0		520			16			
190			360	1.7	3	525			17			
195			365	1.8		530			18			
200	.9		370	2.1	4	535			19			
205	.9		375	2.7		540			20			
210	.7		380	2.1	3	545			21			
215	.4		385	1.6		550			22			
220	.7		390	1.5		555			23			
225	.3		395	1.6	2	560			24			
230	.3		400	1.3		565			25			
235	.9		405	2.2	1	570			26			
240	1.1		410	1.8		575			27			
245	1.1		415	4/3	T.O.	580			28			
250	1.3		420			585			29			
255	2.0		425			590			30			
260	3.1	10	430			600						

LOGGING VOLTS: 13.46
TOTAL AMPS: 20.3

VOLTAGE SOURCE: Auto
TOTAL G/B RESISTANCE: 2.6

REMARKS: Pour 3x3 Pad and run conduit for positive lead
423' vent pipe with 200' pad
28 SACKS COKE - 2800 LBS